

**e-Szignó Certification Authority**

**eIDAS conform  
Certificate for Website Authentication  
Certification Practice Statement**

**ver. 2.0**

**Date of effect: 01/07/2016**



OID	1.3.6.1.4.1.21528.2.1.1.67.2.0
Version	2.0
First version date of effect	01/07/2016
Security classification	PUBLIC
Approved by	Gergely Vanczák
Date of approval	31/05/2016
Date of effect	01/07/2016

Microsec Micro Software Engineering & Consulting Private Company Limited by Shares  
Hungary, H-1031 Budapest, Záhony u. 7. D

Version	Description	Effect date	Author(s)
2.0	New policies according to the RFC 3647 and the eIDAS requirements.	01/07/2016	Csilla Endrődi, Szabóné Sándor Szőke, Dr. Kornél Réti

© 2016, Microsec Ltd. All rights reserved.

## Table of Contents

<b>1</b>	<b>Introduction</b>	<b>12</b>
1.1	Overview . . . . .	12
1.2	Document Name and Identification . . . . .	13
1.2.1	Certificate Policies . . . . .	13
1.2.2	Effect . . . . .	15
1.2.3	Security Levels . . . . .	16
1.3	PKI Participants . . . . .	17
1.3.1	Certification Authorities . . . . .	17
1.3.2	Registration Authorities . . . . .	24
1.3.3	Subscribers . . . . .	25
1.3.4	Relying Parties . . . . .	25
1.3.5	Other Participants . . . . .	25
1.4	Certificate Usage . . . . .	25
1.4.1	Appropriate Certificate Uses . . . . .	25
1.4.2	Prohibited Certificate Uses . . . . .	26
1.5	Policy Administration . . . . .	26
1.5.1	Organization Administering the Document . . . . .	26
1.5.2	Contact Person . . . . .	26
1.5.3	Person or Organization Responsible for the Suitability of the Practice Statement for the <i>Qualified Signature Certificate Policy</i> . . . . .	26
1.5.4	Practice Statement Approval Procedures . . . . .	26
1.6	Definitions and Acronyms . . . . .	27
1.6.1	Definitions . . . . .	27
1.6.2	Acronyms . . . . .	32
<b>2</b>	<b>Publication and Repository Responsibilities</b>	<b>33</b>
2.1	Repositories . . . . .	33
2.2	Publication of Certification Information . . . . .	33
2.3	Time or Frequency of Publication . . . . .	34
2.3.1	Frequency of the Publication of Terms and Conditions . . . . .	34
2.3.2	Frequency of the Certificates Disclosure . . . . .	34
2.3.3	The Changed Revocation Status Publication Frequency . . . . .	35
2.4	Access Controls on Repositories . . . . .	35
<b>3</b>	<b>Identification and Authentication</b>	<b>35</b>
3.1	Naming . . . . .	35
3.1.1	Types of Names . . . . .	35
3.1.2	Need for Names to be Meaningful . . . . .	40

3.1.3	Anonymity or Pseudonymity of Subscribers . . . . .	40
3.1.4	Rules for Interpreting Various Name Forms . . . . .	40
3.1.5	Uniqueness of Names . . . . .	40
3.1.6	Recognition, Authentication, and Role of Trademarks . . . . .	41
3.2	Initial Identity Validation . . . . .	41
3.2.1	Method to Prove Possession of Private Key . . . . .	41
3.2.2	Authentication of an Organization Identity . . . . .	41
3.2.3	Authentication of an Individual Identity or e Domain . . . . .	43
3.2.4	Non-Verified Subscriber Information . . . . .	45
3.2.5	Validation of Authority . . . . .	46
3.2.6	Criteria for Interoperation . . . . .	46
3.3	Identification and Authentication for Re-key Requests . . . . .	46
3.3.1	Identification and Authentication for Routine Re-key . . . . .	46
3.3.2	Identification and Authentication for Re-key After Revocation . . . . .	47
3.4	Identification and Authentication in Case of Certificate Renewal Requests . . . . .	47
3.4.1	Identification and Authentication in Case of a Valid Certificate . . . . .	47
3.4.2	Identification and Authentication in Case of an Invalid Certificate . . . . .	48
3.5	Identification and Authentication for Certificate Modification requests . . . . .	48
3.5.1	Identification and Authentication in Case of a Valid Certificate . . . . .	48
3.5.2	Identification and Authentication in Case of an Invalid Certificate . . . . .	49
3.6	Identification and Authentication for Revocation Request . . . . .	49
<b>4</b>	<b>Certificate Life-Cycle Operational Requirements</b>	<b>49</b>
4.1	Application for a Certificate . . . . .	50
4.1.1	Who May Submit a Certificate Application . . . . .	51
4.1.2	Enrolment Process and Responsibilities . . . . .	51
4.2	Certificate Application Processing . . . . .	52
4.2.1	Performing Identification and Authentication Functions . . . . .	52
4.2.2	Approval or Rejection of Certificate Applications . . . . .	52
4.2.3	Time to Process Certificate Applications . . . . .	53
4.3	Certificate Issuance . . . . .	53
4.3.1	CA Actions During Certificate Issuance . . . . .	53
4.3.2	Notification of the Subscriber about the Issuance of the Certificate . . . . .	53
4.4	Certificate Acceptance . . . . .	53
4.4.1	Conduct Constituting Certificate Acceptance . . . . .	53
4.4.2	Publication of the Certificate by the CA . . . . .	54
4.4.3	Notification of Certificate Issuance by the CA to Other Entities . . . . .	54
4.5	Key Pair and Certificate Usage . . . . .	54
4.5.1	Subscriber Private Key and Certificate Usage . . . . .	54

4.5.2	Relying Party Public Key and Certificate Usage	54
4.6	Certificate Renewal	55
4.6.1	Circumstances for Certificate Renewal	55
4.6.2	Who May Request Renewal	55
4.6.3	Processing Certificate Renewal Requests	56
4.6.4	Notification of the Client about the New Certificate Issuance	56
4.6.5	Conduct Constituting Acceptance of a Renewed Certificate	56
4.6.6	Publication of the Renewed Certificate by the CA	57
4.6.7	Notification of Other Entities about the Certificate Issuance	57
4.7	Certificate Re-Key	57
4.7.1	Circumstances for Certificate Re-Key	57
4.7.2	Who May Request Certification of a New Public Key	57
4.7.3	Processing Certificate Re-Key Requests	58
4.7.4	Notification of the Client about the New Certificate Issuance	58
4.7.5	Conduct Constituting Acceptance of a Re-Keyed Certificate	58
4.7.6	Publication of the Re-Keyed Certificate	58
4.7.7	Notification of Other Entities about the Certificate Issuance	58
4.8	Certificate Modification	58
4.8.1	Circumstances for Certificate Modification	59
4.8.2	Who May Request Certificate Modification	59
4.8.3	Processing Certificate Modification Requests	60
4.8.4	Notification of the Client about the New Certificate Issuance	60
4.8.5	Conduct Constituting Acceptance of Modified Certificate	60
4.8.6	Publication of the Modified Certificate by the CA	60
4.8.7	Notification of Certificate Issuance by the CA to Other Entities	60
4.9	Certificate Revocation and Suspension	61
4.9.1	Circumstances for Revocation	61
4.9.2	Who Can Request Revocation	64
4.9.3	Procedure for Revocation Request	64
4.9.4	Revocation Request Grace Period	65
4.9.5	Time Within Which CA Must Process the Revocation Request	65
4.9.6	Revocation Checking Requirement for Relying Parties	65
4.9.7	CRL Issuance Frequency (If Applicable)	65
4.9.8	Maximum Latency for CRLs (If Applicable)	65
4.9.9	Online Revocation/Status Checking Availability	66
4.9.10	Online Revocation Checking Requirements	66
4.9.11	Other Forms of Revocation Advertisements Available	66
4.9.12	Special Requirements for Key Compromise	66
4.9.13	Circumstances for Suspension	66

4.9.14	Who Can Request Suspension . . . . .	66
4.9.15	Procedure for Suspension Request . . . . .	66
4.9.16	Limits on Suspension Period . . . . .	66
4.10	Certificate Status Services . . . . .	66
4.10.1	Operational Characteristics . . . . .	67
4.10.2	Service Availability . . . . .	69
4.10.3	Optional Features . . . . .	69
4.11	End of Subscription . . . . .	69
4.12	Key Escrow and Recovery . . . . .	70
4.12.1	Key Escrow and Recovery Policy and Practices . . . . .	70
4.12.2	Symmetric Encryption Key Encapsulation and Recovery Policy and Practices . . . . .	70
<b>5</b>	<b>Facility, Management, and Operational Controls</b>	<b>70</b>
5.1	Physical Controls . . . . .	70
5.1.1	Site Location and Construction . . . . .	71
5.1.2	Physical Access . . . . .	71
5.1.3	Power and Air Conditioning . . . . .	72
5.1.4	Water Exposures . . . . .	72
5.1.5	Fire Prevention and Protection . . . . .	72
5.1.6	Media Storage . . . . .	73
5.1.7	Waste Disposal . . . . .	73
5.1.8	Off-Site Backup . . . . .	73
5.2	Procedural Controls . . . . .	73
5.2.1	Trusted Roles . . . . .	74
5.2.2	Number of Persons Required per Task . . . . .	75
5.2.3	Identification and Authentication for Each Role . . . . .	75
5.2.4	Roles Requiring Separation of Duties . . . . .	75
5.3	Personnel Controls . . . . .	76
5.3.1	Qualifications, Experience, and Clearance Requirements . . . . .	76
5.3.2	Background Check Procedures . . . . .	76
5.3.3	Training Requirements . . . . .	77
5.3.4	Retraining Frequency and Requirements . . . . .	77
5.3.5	Job Rotation Frequency and Sequence . . . . .	77
5.3.6	Sanctions for Unauthorized Actions . . . . .	78
5.3.7	Independent Contractor Requirements . . . . .	78
5.3.8	Documentation Supplied to Personnel . . . . .	78
5.4	Audit Logging Procedures . . . . .	79
5.4.1	Types of Events Recorded . . . . .	79

5.4.2	Frequency of Audit Log Processing . . . . .	81
5.4.3	Retention Period for Audit Log . . . . .	82
5.4.4	Protection of Audit Log . . . . .	82
5.4.5	Audit Log Backup Procedures . . . . .	82
5.4.6	Audit Collection System (Internal vs External) . . . . .	83
5.4.7	Notification to Event-causing Subject . . . . .	83
5.4.8	Vulnerability Assessments . . . . .	83
5.5	Records Archival . . . . .	83
5.5.1	Types of Records Archived . . . . .	83
5.5.2	Retention Period for Archive . . . . .	84
5.5.3	Protection of Archive . . . . .	84
5.5.4	Archive Backup Procedures . . . . .	84
5.5.5	Requirements for Time-stamping of Records . . . . .	85
5.5.6	Archive Collection System (Internal or External) . . . . .	85
5.5.7	Procedures to Obtain and Verify Archive Information . . . . .	85
5.6	CA Key Changeover . . . . .	85
5.7	Compromise and Disaster Recovery . . . . .	86
5.7.1	Incident and Compromise Handling Procedures . . . . .	86
5.7.2	Computing Resources, Software, and/or Data are Corrupted . . . . .	86
5.7.3	Entity Private Key Compromise Procedures . . . . .	86
5.7.4	Business Continuity Capabilities After a Disaster . . . . .	87
5.8	CA or RA Termination . . . . .	87
<b>6</b>	<b>Technical Security Controls</b>	<b>88</b>
6.1	Key Pair Generation and Installation . . . . .	89
6.1.1	Key Pair Generation . . . . .	89
6.1.2	Private Key Delivery to Subscriber . . . . .	90
6.1.3	Public Key Delivery to Certificate Issuer . . . . .	91
6.1.4	CA Public Key Delivery to Relying Parties . . . . .	91
6.1.5	Key Sizes . . . . .	92
6.1.6	Public Key Parameters Generation and Quality Checking . . . . .	92
6.1.7	Key Usage Purposes (as per X.509 v3 Key Usage Field) . . . . .	93
6.2	Private Key Protection and Cryptographic Module Engineering Controls . . . . .	94
6.2.1	Cryptographic Module Standards and Controls . . . . .	94
6.2.2	Private Key (N out of M) Multi-Person Control . . . . .	95
6.2.3	Private Key Escrow . . . . .	95
6.2.4	Private Key Backup . . . . .	95
6.2.5	Private Key Archival . . . . .	95
6.2.6	Private Key Transfer Into or From a Cryptographic Module . . . . .	95



6.2.7	Private Key Storage on Cryptographic Module . . . . .	95
6.2.8	Method of Activating Private Key . . . . .	96
6.2.9	Method of Deactivating Private Key . . . . .	96
6.2.10	Method of Destroying Private Key . . . . .	96
6.2.11	Cryptographic Module Rating . . . . .	97
6.3	Other Aspects of Key Pair Management . . . . .	97
6.3.1	Public Key Archival . . . . .	97
6.3.2	Certificate Operational Periods and Key Pair Usage Periods . . . . .	97
6.4	Activation Data . . . . .	98
6.4.1	Activation Data Generation and Installation . . . . .	98
6.4.2	Activation Data Protection . . . . .	99
6.4.3	Other Aspects of Activation Data . . . . .	99
6.5	Computer Security Controls . . . . .	99
6.5.1	Specific Computer Security Technical Requirements . . . . .	99
6.5.2	Computer Security Rating . . . . .	100
6.6	Life Cycle Technical Controls . . . . .	100
6.6.1	System Development Controls . . . . .	100
6.6.2	Security Management Controls . . . . .	101
6.6.3	Life Cycle Security Controls . . . . .	101
6.7	Network Security Controls . . . . .	102
6.8	Time-stamping . . . . .	102
<b>7</b>	<b>Certificate, CRL, and OCSP Profiles</b>	<b>102</b>
7.1	Certificate Profile . . . . .	102
7.1.1	Version Number(s) . . . . .	102
7.1.2	Certificate Extensions . . . . .	104
7.1.3	Algorithm Object Identifiers . . . . .	108
7.1.4	Name Forms . . . . .	108
7.1.5	Name Constraints . . . . .	108
7.1.6	Certificate Policy Object Identifier . . . . .	108
7.1.7	Usage of Policy Constraints Extension . . . . .	108
7.1.8	Policy Qualifiers Syntax and Semantics . . . . .	109
7.1.9	Processing Semantics for Critical Certificate Policy Extension . . . . .	109
7.2	CRL Profile . . . . .	109
7.2.1	Version Number(s) . . . . .	109
7.2.2	CRL and CRL Entry Extensions . . . . .	109
7.3	OCSP Profile . . . . .	110
7.3.1	Version Number(s) . . . . .	110
7.3.2	OCSP Extensions . . . . .	110

<b>8</b>	<b>Compliance Audit and Other Assessments</b>	<b>111</b>
8.1	Frequency or Circumstances of Assessment	111
8.2	Identity/Qualifications of Assessor	112
8.3	Assessor's Relationship to Assessed Entity	112
8.4	Topics Covered by Assessment	112
8.5	Actions Taken as a Result of Deficiency	113
8.6	Communication of Results	113
<b>9</b>	<b>Other Business and Legal Matters</b>	<b>113</b>
9.1	Fees	113
9.1.1	Certificate Issuance or Renewal Fees	113
9.1.2	Certificate Access Fees	113
9.1.3	Revocation or Status Information Access Fees	113
9.1.4	Fees for Other Services	114
9.1.5	Refund Policy	114
9.2	Financial Responsibility	114
9.2.1	Insurance Coverage	114
9.2.2	Other Assets	114
9.2.3	Insurance or Warranty Coverage for End-entities	114
9.3	Confidentiality of Business Information	114
9.3.1	Scope of Confidential Information	115
9.3.2	Information Not Within the Scope of Confidential Information	115
9.3.3	Responsibility to Protect Confidential Information	115
9.4	Privacy of Personal Information	116
9.4.1	Privacy Plan	117
9.4.2	Information Treated as Private	117
9.4.3	Information Not Deemed Private	117
9.4.4	Responsibility to Protect Private Information	117
9.4.5	Notice and Consent to Use Private Information	117
9.4.6	Disclosure Pursuant to Judicial or Administrative Process	117
9.4.7	Other Information Disclosure Circumstances	118
9.5	Intellectual Property Rights	118
9.6	Representations and Warranties	118
9.6.1	CA Representations and Warranties	118
9.6.2	RA Representations and Warranties	120
9.6.3	Subscriber Representations and Warranties	121
9.6.4	Relying Party Representations and Warranties	124
9.6.5	Representations and Warranties of Other Participants	124
9.7	Disclaimers of Warranties	124

---

9.8	Limitations of Liability . . . . .	125
9.9	Indemnities . . . . .	126
9.9.1	Indemnification by the <i>Trust Service Provider</i> . . . . .	126
9.9.2	Indemnification by Subscribers . . . . .	126
9.9.3	Indemnification by Relying Parties . . . . .	126
9.10	Term and Termination . . . . .	126
9.10.1	Term . . . . .	126
9.10.2	Termination . . . . .	126
9.10.3	Effect of Termination and Survival . . . . .	126
9.11	Individual Notices and Communications with Participants . . . . .	127
9.12	Amendments . . . . .	127
9.12.1	Procedure for Amendment . . . . .	127
9.12.2	Notification Mechanism and Period . . . . .	128
9.12.3	Circumstances Under Which OID Must Be Changed . . . . .	128
9.13	Dispute Resolution Provisions . . . . .	128
9.14	Governing Law . . . . .	129
9.15	Compliance with Applicable Law . . . . .	129
9.16	Miscellaneous Provisions . . . . .	129
9.16.1	Entire Agreement . . . . .	129
9.16.2	Assignment . . . . .	129
9.16.3	Severability . . . . .	129
9.16.4	Enforcement (Attorneys' Fees and Waiver of Rights) . . . . .	129
9.16.5	Force Majeure . . . . .	130
9.17	Other Provisions . . . . .	130
<b>A</b>	<b>REFERENCES</b>	<b>131</b>

## 1 Introduction

This document is the *Certification Practice Statement* concerning the certificate for website authentication service of e-Szignó Certification Authority operated by Microsec Ltd. (hereinafter: Microsec or *Trust Service Provider*).

The *Trust Service Provider* provides its services for its *Clients* those have contractual relationship. The present *Certification Practice Statement* describes the framework of the provision of the aforementioned services and includes the detailed procedures and miscellaneous operating rules.

It makes recommendations for the *Relying Parties* for the verification of the and *Certificates* created by the services.

The *Certification Practice Statement* complies with the requirements set by the eIDAS Regulation [1], the service provided according to these regulations is an EU trust service.

### 1.1 Overview

The aim of the present *Certification Practice Statement* is to summarize all the information that the *Clients* coming into contact with the *Trust Service Provider* should know. This aims to foster that:

- its *Clients* and future *Clients* get better acquainted with the details and requirements of the services provided by the *Trust Service Provider*, and the practical background of the service provision;
- the *Clients* be able to see through the operation of the *Trust Service Provider*, and thus more easily decide whether the services comply or which type of services meet their individual needs and expectations.

Furthermore the role of present document is to help the users and acceptors of *Certificates*, *Certificate* revocation lists and online *Certificate* status responses issued by the *Trust Service Provider* in the clear identification of the ways of managing them, the level of security guaranteed by them as well as the relevant technical, commercial, financial guarantees and legal responsibility related to them. The content and format of the present document complies with the requirements of the RFC 3647 [17] framework. It consists of 9 sections that contain the security requirements, processes defined by the *Trust Service Provider* and the practices to be followed during the provision of services. To strictly preserve the outline specified by RFC 3647, section headings where the document does not impose a requirement have the statement "No stipulation".

Requirements for end user activity related to the used services can be contained besides the present *Certification Practice Statement* in the General Terms and Conditions the service agreement concluded with the provider, the Certificate Policies applied by the *Trust Service Provider* (see section 1.2.1 ), the *Time-Stamping Policy* [29] and other regulation or document independent from the *Trust Service Provider* as well.

## 1.2 Document Name and Identification

Issuer	e-Szignó Certification Authority
Document name	eIDAS conform Certificate for Website Authentication Certification Practice Statement
Document version	2.0
Date of effect	01/07/2016

The listing and identification information of the *Certificate Policies* that can be used according to the *Certification Practice Statement* is in section 1.2.1.

### 1.2.1 Certificate Policies

All *Certificates* issued by the *Trust Service Provider* refers to that *Certificate Policy* based on which they were issued.

The first seven numbers of the *Certificate Policy* identifier OID is the unique identifier of Microsec as follows:

(1)	International Organization for Standardization (ISO)
(3)	Organization identification schemes registered according to ISO/IEC 6523-2
(6)	United States Department of Defense (DoD)
(1)	Internet
(4)	Private projects
(1)	Private enterprises
(21528)	MICROSEC Ltd.

The system of the following numbers was allocated within Microsec own competence, interpretation as follows:

(1.3.6.1.4.1.21528)	MICROSEC Ltd.
(2)	e-Szignó Certification Authority
(1)	documents
(1)	public documents
(x)	unique identifier number of the document
(y)	document version
(z)	document subversion

The *Trust Service Provider* issues *Certificates* according to the following *Certificate Policies* based on the present *Certification Practice Statement*:

OID	DENOMINATION	SHORT NAME
1.3.6.1.4.1.21528.2.1.1.59.2.0	certification class III., for website authentication certificates, prohibiting the use of pseudonyms.	HWxxN

1.3.6.1.4.1.21528.2.1.1.61.2.0	certification class II., for website authentication certificates, prohibiting the use of pseudonyms.	KWxxN
1.3.6.1.4.1.21528.2.1.1.62.2.0	Issued during automatic issuance, controlling website authentication certificate issuance, Certificate Policy prohibiting the use of pseudonyms.	AWxxN

Formation and interpretation of the *Qualified Signature Certificate Policy* short name happens according to the following rules:

- First character [Xxxxx]
  - M: qualified *Certificate Qualified Signature Certificate Policy*
  - N: non-qualified *Certificate Qualified Signature Certificate Policy*
  - H: non-qualified, III. certificate class *Certificate Qualified Signature Certificate Policy*
  - K: non-qualified, II. certificate class *Certificate Qualified Signature Certificate Policy*
  - A: non-qualified, automatic issuance *Certificate Qualified Signature Certificate Policy*
  - x: no stipulation
- Second character [xXxxx]
  - A: Signing purpose *Certificate Qualified Signature Certificate Policy*
  - B: Seal creation purpose *Certificate Qualified Signature Certificate Policy*
  - W: *Website Authentication Certificate Qualified Signature Certificate Policy*
  - K: Code signing *Certificate Qualified Signature Certificate Policy*
  - E: Other purpose *Certificate Qualified Signature Certificate Policy*
  - x: no stipulation
- Third character [xxXxx]
  - T: *Certificate* issued to a natural person *Qualified Signature Certificate Policy*
  - J: *Certificate* issued to a legal person *Qualified Signature Certificate Policy*
  - x: no stipulation
- Fourth character [xxxXx]
  - B: *Certificate* issued on *Qualified Electronic Signature Creation Device Qualified Signature Certificate Policy*
  - H: *Certificate* issued on *Hardware Security Module Qualified Signature Certificate Policy*
  - S: *Certificate* issued by software *Qualified Signature Certificate Policy*
  - x: no stipulation
- Fifth character [xxxxX]

- A: pseudonymous *Certificate Qualified Signature Certificate Policy*
- N: pseudonym excluding *Certificate Qualified Signature Certificate Policy*
- x: no stipulation

The detailed requirements of the listed *Qualified Signature Certificate Policy(s)* are in "e-Szignó Certification Authority - eIDAS Regulation Non-Qualified Webserver Certificate Policies ver. 2.0 ." [28]

The issuance of *Certificates* belonging to the III. certification class is bound to the personal identification in advance by the *Trust Service Provider*, and for the II. class certification *Certificate* issuance, the remote registration is permitted.

In case of *Certificate Policies* concerning *Certificates* issued to non-natural persons, the *Subject* is a legal person.

In case of *Website Authentication Certificates* at the name of the *Subject* the domain name or IP address is indicated. The *Website Authentication Certificate* can not be pseudonymous.

All of the present *Certificate Policies* prohibit the use of pseudonyms, the real name of the *Subject* is indicated on the *Certificate* in all cases.

The operation of the *Trust Service Provider* complies with the current version of the Baseline Requirements Certificate Policy for the Issuance and Management of Publicly-Trusted Certificates [23] requirements issued by the CA/Browser Forum, which is available at the <https://cabforum.org/baseline-requirements-documents/> url.

In case of a contradiction between the present *Certification Practice Statement* and the Baseline Requirements the requirements of the Baseline Requirements shall prevail.

Among the present *Certificate Policies*:

- each *Certificate Policy* complies with the [DVCP] *Certificate Policy* defined in the ETSI EN 319 411-1 [8] standard;
- each *Certificate Policy* complies with the [OVCP] *Certificate Policy* defined in the ETSI EN 319 411-1 [8] standard, if the organization name is indicated on the *Certificate*;

### Compliance with the ETSI Certificate Policies

	[DVCP]	[OVCP]
HW <sub>xx</sub> N	X	X*
KW <sub>xx</sub> N	X	X*
AW <sub>xx</sub> N	X	X*

\* if the name of the *Organization* is indicated on the *Certificate*

### 1.2.2 Effect

#### Subject Scope

The *Certification Practice Statement* is related to the provision and usage of the services described in section 1.3.1.

### Temporal Scope

The present version of the *Certification Practice Statement* is effective from the 01/07/2016 date of effect, until withdrawal. The effect automatically terminates at the cessation of services.

### Personal Scope

The effect of the *Certification Practice Statement* extends each of the participants mentioned in section 1.3.

### Geographical Scope

The present *Certification Practice Statement* includes specific requirements for services primarily provided for Hungarian *Clients*, operating by the Hungarian law in Hungary in Hungarian language. The *Trust Service Provider* can extend the geographical scope of the service, in this case, it shall use not less stringent requirements than those applicable to Hungarian conditions.

#### 1.2.3 Security Levels

The *Trust Service Provider* defined security levels by taking into account the relevant requirements as follows.

The authentication strength of the *Certificate Subject* in descending order:

- qualified *Certificates* [Mxxxx];
- non-qualified III. certification class *Certificates* [Hxxxx] issued by e-Szignó Certification Authority;
- non-qualified II. certification class *Certificates* [Kxxxx] issued by e-Szignó Certification Authority;
- non-qualified *Certificates* issued not by e-Szignó Certification Authority [xxxxx].

Based on the used container in descending order by security:

- *Certificates* issued on *Qualified Electronic Signature Creation Device* [xxxBx];
- *Certificates* issued on *Hardware Security Module* [xxxHx];
- otherwise, for example *Certificates* issued by software [xxxSx], [xxxxx].

By taking into account the two points of view the *Trust Service Provider* established the following aggregated order in descending order of security:

- qualified *Certificates* issued on *Qualified Electronic Signature Creation Device* [MxxBx];
- qualified *Certificates* issued on *Hardware Security Module* [MxxHx];
- qualified otherwise, for example *Certificates* issued by software [MxxSx], [Mxxxx];



- non-qualified III. certification class *Certificates* [HxxHx] issued by e-Szignó Certification Authority on a *Hardware Security Module*;
- non-qualified otherwise, for example by software issued III. certification class *Certificates* [HxxSx][Hxxxx];
- non-qualified II. certification class *Certificates* [KxxHx] issued by e-Szignó Certification Authority on *Hardware Security Module*;
- non-qualified otherwise, for example by software issued II. certification class *Certificates* [KxxSx][Kxxxx] issued by e-Szignó Certification Authority;
- non-qualified *Certificates* issued not by e-Szignó Certification Authority [xxxxx].

During the communication with the *Clients* the *Trust Service Provider* supports the use of electronic channels and enables the use of electronic signature during the administration in most cases possible.

It is a general rule, that during the administration related to the *Certificates*, the *Client* can use its own signing *Certificate* to verify the electronic documents, if its level of security according to the aforementioned list is not lower than the relevant *Certificate*.

On an individual basis in special cases, the *Trust Service Provider* can deviate from the strict application of the above list with regard to particular tasks (for example the personal identification for III. certificate class *Certificates* in case of new qualified *Certificate* application or the modification of an existing one as a result of the same procedural identification rules it accepts the identification required for qualified *Certificate*).

### 1.3 PKI Participants

The participants applying the services provided within the framework of present *Certification Practice Statement* consist of the following:

- the Microsec e-Szignó Certification Authority,
- the *Registration Authority* in a contractual relationship with Microsec e-Szignó Certification Authority,
- the *Clients* of Microsec e-Szignó Certification Authority (*Subscribers* and *Subjects*),
- *Relying Parties*,
- other participants.

#### 1.3.1 Certification Authorities

##### Data of the *Trust Service Provider*

Name	MICROSEC Micro Software Engineering & Consulting Private Limited Company by Shares
Company registry number	01-10-047218 Company Registry Court of Budapest

Head office	1031 Budapest, Záhony street 7. D. building
Telephone number	(+36-1) 505-4444
Fax number	(+36-1) 505-4445
Internet address	<a href="https://www.microsec.hu">https://www.microsec.hu</a> , <a href="https://www.e-szigno.hu">https://www.e-szigno.hu</a>
Contact information of the customer service:	
The name of the provider unit	e-Szigno Certification Authority
Customer service	1031 Budapest, Záhony str. 7., Graphisoft Park, D building
Office hours of the customer service	on workdays between 8:30-16:30 by prior arrangement
Telephone number of the customer service	(+36-1) 505-4444
E-mail address of the customer service	<a href="mailto:info@e-szigno.hu">info@e-szigno.hu</a>
Service related information access	<a href="https://www.e-szigno.hu">https://www.e-szigno.hu</a>
Place for registering complaints	Microsec zrt. 1031 Budapest, Záhony str. 7., Graphisoft Park, D building
Relevant Consumer Protection Inspectorate	Budapest Capital Authority for Consumer Protection 1052 Budapest, Városház str. 7. 1364 Budapest, Pf. 144.

### Introduction of the *Trust Service Provider*

Microsec Ltd. is an EU qualified trust service provider according to the 910/2014/EU Regulation [1] (hereinafter: eIDAS).

Microsec Ltd. (its predecessor) started the provision of its services related to electronic signatures under the effect of Act XXXV. of 2001. [2] (hereinafter: Eat.):

- provides non-qualified electronic signature certification services, time stamping, and placement of signature-creation data on signature creation devices services according to Eat. since May 30, 2002 (registration number: MH 6834 1/2002.);
- provides qualified electronic signature certification services, time stamping, and device services according to Eat. since May 15, 2005;
- provides qualified long term preservation service according to Eat. since February 1, 2007. (reference number of the decision on the registration: HL-3549-2/2007).

On the 1st of July, 2016. the whole system of services related to electronic signatures changed uniformly on a European basis with eIDAS and its complement Act CCXXII of 2015. [5] coming into force. Microsec continuously migrates its services in accordance with the new eIDAS requirements.

From the 1st of July, 2016 :

- starts the issuance of eIDAS qualified signing certificates for natural persons;
- starts the issuance of eIDAS non-qualified signing, seal and webserver certificates;

- in accordance with the transitional provisions, it provides on a national qualified level until obtaining the final eIDAS certificate the issuance of signing certificates for organizations, time stamping and long term preservation services.

### Quality and Information Security

Microsec highlights the importance of *Client* experience. In order to maintain a high level of services, the *Trust Service Provider* has been operating a quality control system compliant with the ISO 9001 standard since January 23, 2002. Compliance with the standard has been verified by Lloyd's Register Quality Assurance.

Microsec assigns high priority to the security of the systems it operates, and has therefore been operating an information security management system that is compliant with ISO 27001 (formerly known as BS 7799) in its main areas of activity since May 19, 2003. Compliance with the standard has been verified by Lloyd's Register Quality Assurance.

### Business Providing Certification Services

Operating as an independent business unit within the organization of Microsec, the e-Szignó Certification Authority provides the *Certificate* creation and management, the *Certificate* revocation information issuance, the *Electronic Signature Creation Device* and the provision of the online certificate status service. The tasks related to the management of the regulations is provided by this unit too. The e-Szignó Certification Authority has its own *Registration Authority*, but does not exclude the cooperation with an external *Registration Authority* either.

### Services

The *Trust Service Provider* provides the following trust services defined by the eIDAS regulation [1] to the *Subscriber* within the framework of the present *Certification Practice Statement* :

- Issuance of Certificates for Website Authentication

### The Issuance of Certificates for Website Authentication Service

The *Trust Service Provider* to provide the Issuance of Certificates for Website Authentication service signs a service agreement with the *Subscriber* , within the confines of it issues a *Certificate* suitable for electronic signature generation to the *Subjects* specified by the *Subscriber*. The *Certificate* provides a certified connection between the data of the identified *Subject* and the public signature verifier data of the signature generation data that the *Subject* holds. Within the framework of a service agreement, multiple *Certificates* can be issued to the *Subject*.

In case of a *Website Authentication Certificate* the *Subject* is a webserver which is identified by the domain name or IP address indicated in the *Certificate*. The *Applicant* is that natural person, who acts during *Certificate* application.

In case of a valid a subscription, the *Applicant* may initiate the following actions:

- *Applicant* may apply for a *Certificate* from the *Trust Service Provider*, the *Certificate* issuance is performed according to a *Certificate Policy* or policies;

- the *Applicant* may request the revocation of its *Certificate*;

The *Subscriber* may also request the revocation of the belonging *Subject's Certificate*. These actions may also be requested by the organizational administrator authorized by the *Subscriber* and registered by the *Trust Service Provider*.

The *Trust Service Provider* makes the revocation lists publicly available, containing the revocation status of the issued *Certificates*. The *Trust Service Provider* also makes the *Certificate* public, according to the *Applicant's* consent. The revoked or expired *Certificate* is invalid.

The *Trust Service Provider* also issues test certificates with the purpose of testing its system. The test certificates do not have any legal effect.

### Certificate Types

The *Certificate Policies* supported by the present *Certification Practice Statement* are presented in section 1.2.1 . The ID of the applied *Certificate Policy* is always indicated in the "Certificate Policies" field of the *Certificate*.

The e-Szignó Certification Authority provides various certificate types for its *Clients*, which mainly differ concerning their properties and data authentically bound to the *Subject*.

- *Organizational Certificate* means a *Certificate* wherein the *Subject* is an *Organization*, a device under the control of the *Organization* or the *Certificate* attests the relationship of a natural person *Subject* with the *Organization*. In this case, the name of the *Organization* is indicated in the "O" field of the *Certificate*. This type of a *Certificate* can only be used as specified by the *Organization*.
- *Certificate for Automatism* means a *Certificate* wherein the denomination of the IT device (application, system) is indicated amongst the *Subject* data in the *Certificate*, by the help of the *Subject* uses the *Certificate*. In case of a *Website Authentication Certificate* the webserver domain name or IP address is indicated at the name of the *Subject*, so every *Website Authentication Certificate* is a *Certificate for Automatism*.
- *Pseudonymous Certificate* means a *Certificate* wherein not the official denomination of the *Subject* is in the *Certificate*. In the pseudonymous *Certificates* the requested name is indicated in the "Pseudonym" field, and it is stated in the "CN" field that the *Certificate* contains a pseudonym. *Website Authentication Certificate* can never be pseudonymous.
- *Personal Certificate* means a *Certificate* that does not contain either an "O" or a "Title" field. This type can only be issued to natural persons.

The e-Szignó Certification Authority issues *Certificates* for natural persons and legal persons. In case of *Certificates* issued to legal persons the authorized representative natural person or a trustee authorized by the representative need to act on behalf of the legal person.

### Test Certificates

The *Trust Service Provider* issues test certificates – firstly to test their system, on the other hand, to third parties in order to test the services. No legal effect belongs to the certificates, and

the *Trust Service Provider* does not take any responsibility for their issuance, usage and service availability.

The *Trust Service Provider* does not issue test certificates under the top level service provider (root) *Certification Unit*.

The issuance of the test certificates is done under the "Microsec e-Szigno Test Root CA 2008" root exclusively created and operating for this task.

The *Trust Service Provider* indicates the test certificates in the "Certificate Policies" field according to the following (see section 7.1.2 ):

- the 1.3.6.1.4.1.21528.2.1.1.9 OID is indicated as a *Certificate Policy* in the *Certificate*, or
- the 1.3.6.1.4.1.21528.2.1.1.100 OID is indicated as a *Certificate Policy* in the *Certificate*, or
- no *Certificate Policy* is indicated in the *Certificate*.

### Certification Units

The following contains a list of *Certification Units* appearing in the system of the e-Szignó Certification Authority under the effect of this *Certification Practice Statement*. Further information can be found in the the certificate hierarchy of the *Trust Service Provider* at the following address: <https://e-szigno.hu/en/pki-services/ca-certificates.html>

The following certification units of the *Trust Service Provider* issue *Certificates*:

- "Microsec e-Szigno Root CA 2009" – Root certification unit, that issues SHA-256 based *Certificates* for the *Certification Units* of the *Trust Service Provider*. This *Certification Unit* has a self certified (SHA-256 based) certificate.
- "e-Szigno SSL CA 2014" – This unit issues only *Website Authentication Certificates* and code signing *Certificates* exclusively according to the III. certification class. Certified by "Microsec e-Szigno Root CA 2009". This unit does not issue pseudonymous *Certificates*.
- "Class2 e-Szigno SSL CA 2016" – This unit issues only *Website Authentication Certificates* and *Certificates* for networking authentication exclusively according to the II. certification class. Certified by "Microsec e-Szigno Root CA 2009". This unit does not issue pseudonymous *Certificates*.
- OSCP responders; every *Certification Unit* with SHA-256 based *Certificate* certifies dedicated OSCP responder *Certification Unit*, which gives responses regarding the revocation status of the *Certificates* issued by the given certification unit. The OSCP responder units name contains the "OCSP Responder" text besides the given certification unit name. The "OCSPSigning" extended key usage is present in the OSCP responder *Certificates*.

The following *Certification Units* of the *Trust Service Provider* do not issue *Certificates* anymore: The aforementioned units have SHA-256 based *Certificates*, and issue SHA-256 based SHA-256 *Certificates*, and OSCP responses. Every provider and end-user RSA key is at least 2048 bit in the hierarchy above.

The *Trust Service Provider* issued SHA-1 *Certificates* based "Microsec e-Szigno Root CA" *Certification Unit* beforehand. The *Trust Service Provider* does not issue *Certificates* according to this hierarchy. The *Trust Service Provider* keeps the SHA-1 based hierarchy for the verifiability of the previously issued *Certificates*. The following *Certification Units* are in the hierarchy:

- "Microsec e-Szigno Root CA" – Root certification unit, which issued SHA-1 based *Certificates* to the *Certification Units* of the *Trust Service Provider*. This *Certification Unit* has a self-certified certificate.
- "e-Szigno SSL CA" – This unit only issued *Website Authentication Certificates* and code signing *Certificates*. Certified by "Microsec e-Szigno Root CA". This unit did not issue pseudonymous *Certificates*.
- "e-Szigno OCSP CA" (self certified) – OCSP responder certificate issuer *Certification Unit*.
- "Advanced e-Szigno OCSP Responder" – OCSP responder – certified by the "e-Szigno OCSP CA".

Intermediate *Certification Units* in the SHA-1 based hierarchy issue "closing CRLs", with a validity date (*nextUpdate*) that is equal to the expiry date of the issuing *Trust Service Provider*.

For the uninterrupted verification of issued certificates SHA-1-based revocation information was available for SHA-1-based *Certificates* until the 31st of December, 2012. Until this date, the *Trust Service Provider* used SHA-1-based OCSP responder certificates and issued SHA-1-based OCSP responses for the SHA-1-based hierarchy. Since the 1st of January, 2013, the *Trust Service Provider* uses SHA-256 based OCSP responder certificates and issues SHA-256 based OCSP responses in its SHA-1 based hierarchy.

The hash of the root *Certificates* belonging to "Microsec e-Szigno Root CA" and "e-Szigno OCSP CA" were published by the *Trust Service Provider* in the July 21, 2005 edition of Magyar Nemzet (a Hungarian daily newspaper), the *Trust Service Provider* published the hash of the "Microsec e-Szigno Root CA 2009" *Certificate* in the June 17 2010 issue of Expressz (a Hungarian daily newspaper). These root *Certificates* are available through the webpage of the e-Szignó Certification Authority.

- The SHA-1 hash of the "Microsec e-Szigno Root CA" root *Certificate*: 23 88 c9 d3 71 cc 9e 96 3d ff 7d 3c a7 ce fc d6 25 ec 19 0d,  
the SHA-256 hash of the same root *Certificate*: 32 7a 3d 76 1a ba de a0 34 eb 99 84 06 27 5c b1 a4 77 6e fd ae 2f df 6d 01 68 ea 1c 4f 55 67 d0
- The "e-Szigno OCSP CA" root *Certificate* SHA-1 hash: 56 2c 85 5b 9c d9 be 0e 64 e6 f7 95 86 24 95 a1 09 3e f1 68,  
the SHA-1 hash of the same root *Certificate*: 15 a9 45 a5 e4 92 c8 6c 3e 4e 0e a5 81 4c 9c 43 b0 4f 2e a6 83 1a 64 6c 37 8c d2 b1 82 05 aa 89
- The "Microsec e-Szigno Root CA 2009" root *Certificate* SHA-1 hash <sup>1</sup> :

<sup>1</sup>The same root (trust anchor) formerly operated with a different certificate. The SHA-1 hash of the former root *Certificate* is : a6 5c b4 73 3d 94 a5 c8 65 a8 64 64 7c 2c 01 27 2c 89 b1 43, and the SHA-256 hash is: 8e 8c 6e bf 77 dc 73 db 3e 38 e9 3f 48 03 e6 2b 6b 59 33 be b5 1e e4 15 2f 68 d7 aa 14 42 6b 31. the *Trust Service Provider* published this hash in the 22 June 2009 issue of Magyar Hírlap (a Hungarian daily newspaper). Signatures and *Certificates* which were verified with the usage of the former root *Certificate* can also be considered valid.

```
89 df 74 fe 5c f4 0f 4a 80 f9 e3 37 7d 54 da 91 e1 01 31 8e,  
the SHA-256 hash of the same root:  
3c 5f 81 fe a5 fa b8 2c 64 bf a2 ea ec af cd e8 e0 77 fc 86 20 a7 ca e5  
37 16 3d f3 6e db f3 78
```

The following trustable certificate stores contain and distribute the "Microsec e-Szigno Root CA" and the "Microsec e-Szigno Root CA 2009" root *Certificates*:

- Microsoft Windows certificate store,
- Network Security Services (NSS) certificate store,
- Google Android from the v2.3 (Gingerbread) version,

The "Microsec e-Szigno Root CA 2009" root *Certificate* is contained and distributed by the following certificate stores:

- Apple iOS from the 7.1.2 version.
- Apple Mac OS X from the 10.9.4 version.

The <https://e-szigno.hu/en/pki-services/browser-compatibility.html> webpage contains more information on other browsers and certificate stores that contain the root certificates of the *Trust Service Provider* by default.

The other *Certificates* of the *Trust Service Provider* can be verified based on the self certified root certificates, so these *Certificates* are only published by the *Trust Service Provider* on its webpage. If – law or in the framework of a contract or agreement between *Trust Service Providers* – other *Trust Service Provider* issues certificates for the *Certification Units* of the *Trust Service Provider*, the *Trust Service Provider* can publish the *Certificates* on its webpage. The *Trust Service Provider* undertakes that in case of *Certificates* issued for the *Trust Service Provider* in this manner, it complies with the cross certifying *Trust Service Provider's Certificate Policy* and considers the included information binding.

Before the expiration date of the provider *Certificates*, the *Trust Service Provider* generates new provider keys and starts new *Certification Units*, and takes all the necessary steps, so that the change of the provider *Certificates* does not endanger the continuity of the services.

### **Chained Certification Service**

The *Trust Service Provider* has the right to offer a chained certification service, where a *Certification Unit* of the *Trust Service Provider* issues a certificate to a *Certification Unit* controlled by another certification authority (hereinafter: cross-certified CA).

This cross-certification is arranged according to the following requirements:

- The *Trust Service Provider* and the cross-certified CA conclude a contract, the contract contains the exact conditions of the cross-certification. The cross-certified CA contracts the belonging *Clients* by itself, within this contract, the cross-certified CA is appointed as the certification authority.

- The *Trust Service Provider* takes full responsibility for the activities of the chained Certification Authority.
- The cross-certified certification authority can only issue *Certificates* for a well defined scope of users.
- The cross-certified certification authority shall publish its *Certificate Policy*, and it shall operate according to it.
- The *Trust Service Provider* is entitled to verify the operation of the cross-certified provider.
- The *Trust Service Provider* revokes the *Certificate* issued during the cross certification if the cross-certified certification authority does not comply with its own *Certificate Policy*, or if the cross-certified certification authority indicates that its cross certified provider key is compromised.
- If the *Trust Service Provider* issues provider *Certificate* for another Certification Authority, it announces the fact to the National Media and Infocommunications Authority. If the cross-certified CA issues *Certificates* that can be used natively and publicly, the cross-certified CA is bound to announce the cross-certification to the National Media and Infocommunications Authority, and ask for registration (except it is already registered at the National Media and Infocommunications Authority). These rules apply to other services related to electronic signatures as subordinate services (e.g. time stamp).

### 1.3.2 Registration Authorities

The *Trust Service Provider* implements registration and other tasks related to the issuing of *Certificates*, as well as further certificate management tasks centrally, within the framework of a customer service operating within its own organization.

Tasks of the office:

- registration of the *Subject* indicated on end user *Certificates*,
- administration and registration activity related to the issuing of *Certificates* and
- maintaining contact with *Clients* (reception of questions, announcements, requests and complaints, and the initiation of their processing),
- performance of certificate actions (revocation, certificate renewal, certificate modification and re-key).

The customer service operated by the *Trust Service Provider* receives requests pertaining to various certificate actions, and initiates their processing. The *Trust Service Provider* maintains a continuously available standby service for the initiation of revocation – 24 hours a day, every day of the week.

The *Registration Authority* may perform registration activities at the following locations:

- at the customer service of the *Trust Service Provider*;



- the associate of the *Registration Authority* may visit *Clients* and perform mobile registration activities on the site according to the internal statements of the *Trust Service Provider*.

The *Trust Service Provider* may also contract other organizations for the creation of external registration offices, or for the operation of mobile registration units which perform specific tasks of the central office at an external location. These external *Registration Authorities* also operate in a controlled way and in accordance with this *Certification Practice Statement*, the *Trust Service Provider* supervises the controlling system of these organisations.

### 1.3.3 Subscribers

The *Clients* of the services provided by the *Trust Service Provider*:

- *Subscriber*:
  - concludes a service agreement with the *Trust Service Provider*,
  - defines the scope of the *Applicant* ,
  - responsible for the payment of the fees arising from the usage of the service.
- *Applicant*: acts during the application for the given *Website Authentication Certificate*.

### 1.3.4 Relying Parties

The *Relying Party* is not necessarily in a contractual relationship with the *Trust Service Provider*. The *Certification Practice Statement* sections 4.5.2, 4.9.6, 9.6.4 and 9.9.3 and the other policies mentioned in it contain the recommendations related to its operation.

The *Trust Service Provider* maintains its contacts with the *Relying Parties* mainly through its website.

### 1.3.5 Other Participants

If a *Certificate* has been issued representing an *Organization* to the *Applicant* for its activity, the *Represented Organization* is the actual *Organization* also indicated within the *Certificate*.

The *Trust Service Provider* does not necessarily have a contractual relationship with the *Represented Organization*, but the *Trust Service Provider* shall not issue an *Organizational Certificate* without the approval of that *Organization*. The *Trust Service Provider* can revoke the *Certificate* at the request of the *Represented Organization*.

## 1.4 Certificate Usage

### 1.4.1 Appropriate Certificate Uses

The private keys belonging to the end-user *Certificates* issued by the *Trust Service Provider* based on the present *Certification Practice Statement* can be only used for website authentication.

### 1.4.2 Prohibited Certificate Uses

*Certificates* issued in accordance with the present *Certificate Policies*, and the private keys belonging to them

using for other purposes than website authentication is prohibited.

## 1.5 Policy Administration

### 1.5.1 Organization Administering the Document

The data of the organization administering the present *Certification Practice Statement* can be found in the following table:

Organization name	Microsec e-Szignó Certification Authority
Organization address	Hungary, H-1037 Budapest, Záhony street 7. building D
Telephone number	+36 1 505-4444
Fax number	+36 1 505-4445
E-mail address	info@e-szigno.hu

### 1.5.2 Contact Person

Questions related to the present *Certification Practice Statement* can be directly put to the following person:

Contact person	Process management department leader
Organization name	Microsec Ltd.
Organization address	Hungary, H-1037 Budapest, Záhony street 7. building D
Telephone number	+36 1 505-4444
Fax number	+36 1 505-4445
E-mail address	info@e-szigno.hu

### 1.5.3 Person or Organization Responsible for the Suitability of the Practice Statement for the *Qualified Signature Certificate Policy*

The provider that issued the *Certification Practice Statement* is responsible for its conformity with the *Qualified Signature Certificate Policy* referenced in it and for the provision of the service according to the regulations contained therein.

The *Certification Practice Statements* and the provision of the services are supervised by the National Media and Infocommunications Authority. The National Media and Infocommunications Authority maintains a register on the *Certificate Policies* and on the *Trust Service Providers* applying these policies. The National Media and Infocommunications Authority takes into account the observations of an independent conformity assessment body at the conformity assessment.

### 1.5.4 Practice Statement Approval Procedures

The writing, the acceptance and the issuance of the new or any modified versions of the *Certification Practice Statement* happens according to unified processes – as defined in detail

in section 9.12.1.

## 1.6 Definitions and Acronyms

### 1.6.1 Definitions

II. certification class	A group of <i>Certificate Policies</i> , that make possible the <i>Certificate</i> issuance based on the <i>Applicant's</i> remote registration.
III. certification class	A group of <i>Certificate Policies</i> , that bound the <i>Certificate</i> issuance to the <i>Applicant's</i> personal registration.
Data Centre	A facility designed for the placement and operation of computer systems and associated components. These components typically include telecommunications systems and communication connections, redundant power supply, data storage, air conditioning, fire protection and safety systems.
Subject	In case of a <i>Website Authentication Certificate</i> the <i>Subject</i> is the webserver, which is identified by a domain name or IP address.
Subject Unique Identifier	The globally unique identifier of the <i>Subject</i> , given by the <i>Trust Service Provider</i> . The identifier is in the "Subject DN Serial Number" field of the <i>Certificate</i> , according to the requirements of section 3.1.1.
Trust Service Supervisory Body	"The National Media and Infocommunications Authority, the supervising authority monitoring the <i>Trust Services</i> ." (Act CCXXII. of 2015. [5] 91.§ 1. paragraph)

Trust Service	<p>"Means an electronic service normally provided for remuneration which consists of:</p> <ul style="list-style-type: none"> <li>• the creation, verification, and validation of electronic signatures, electronic seals or electronic time stamps, electronic registered delivery services and certificates related to those services, or</li> <li>• the creation, verification and validation of <i>Website Authentication Certificate</i>; or</li> <li>• the preservation of electronic signatures, seals or certificates related to those services;</li> </ul> <p>" (<i>eIDAS [1] 3. article 16. point</i>)</p>
Trust Service Policy	<p>"A set of rules in which a <i>Trust Service Provider</i>, relying party or other person requires conditions for the usage of the <i>Trust Service</i> for a community of the relying parties and/or a class of applications with common safety requirements." (<i>Act CCXXII. of 2015. [5] 1. § 8. point</i>)</p>
Trust Service Provider	<p>"A natural or a legal person who provides one or more <i>Trust Services</i> either as a qualified or as a non-qualified <i>Trust Service Provider</i>." (<i>eIDAS [1] 3. article 19. point</i>)</p>
Electronic Document	<p>"Means any content stored in electronic form, in particular text or sound, visual or audiovisual recording" (<i>eIDAS [1] 3. article 35. point</i>)</p>
Electronic Time Stamp	<p>"Means data in electronic form which binds other data in electronic form to a particular time establishing evidence that the latter data existed at that time." (<i>eIDAS [1] 3. article 33. point</i>)</p>
Subscriber	<p>A person or organization signing the service agreement with the <i>Trust Service Provider</i> in order to use some of its services.</p>
Relying Party	<p>The communicating party, who identifies a webserver when accessing the website based on its <i>Website Authentication Certificate</i>, furthermore, those software vendors who produce Internet browsers or applications in which they use <i>Website Authentication Certificate</i> during its operation.</p>
Suspension	<p>The temporary termination of the <i>Certificate's</i> validity before the end of the validity period indicated on the <i>Certificate</i>. The <i>Certificate</i> suspension is not definitive; the suspended <i>Certificate's</i> validity can be restored.</p>

Root Certificate	Also known as top level certificate. Self-signed <i>Certificate</i> , which is issued by a specific <i>Certification Unit</i> for itself, which is signed with its own private key, so it can be verified with the Signature-Verification Data – indicated on the certificate.
HSM: Hardware Security Module	A hardware-based secure tool that generates, stores and protects cryptographic keys and provides a secure environment for the implementation of cryptographic functions.
Certification Authority	A <i>Trust Service Provider</i> , who/which identifies the requester within the confines of the certification service, issues <i>Certificates</i> , keeps a record, receives the <i>Certificate</i> related data changes, and publishes the regulations belonging to the <i>Certificate</i> and the information on the current state (especially on possible revocation) of the <i>Certificate</i> .
Certification Unit	A unit of the <i>Trust Service Provider's</i> system that signs the <i>Certificates</i> . Always just one Certificate-Creation Data (signing key, signature-creation data) belongs to a <i>Certification Unit</i> . It is possible that a Certification Authority simultaneously operate several <i>Certification Units</i> .
Certificate Policy	"A <i>Trust Service Policy</i> which concerns the <i>Certificate</i> issued within the framework of the <i>Trust Service</i> ." ( <i>Act CCXXII. of 2015. [5] 1. § 24. point</i> )
Applicant	That natural person who acts during the application for the given <i>Certificate</i> .
Represented Organization	If the <i>Certificate</i> is issued to the <i>Applicant</i> for the purpose of using it for its activities or for then the <i>Represented Organization</i> is the <i>Organization</i> in question, which is also specified in the <i>Certificate</i> .
Compromise	A cryptographic key is compromised, when unauthorized persons might have gained access to it.
Intermediate Certification Unit	A <i>Certification Unit</i> whose <i>Certificate</i> was issued by another <i>Certification Unit</i> .

Cryptographic Key	An individual digital signal series controlling cryptographic transformation, the knowledge of which is required for encryption, decryption, electronic signature creation and verification.
Key Management	The production of cryptographic keys, their delivery to users or its algorithmic implementation, as well as the registration, storage, archival, revocation and termination of keys which are closely linked to the used security method.
Private Key	In the public key infrastructure, the element of an asymmetric cryptographic key pair for an actor that the <i>Applicant</i> shall keep strictly secret. In case of webserver authentication the webserver shall use its private key during its authentication procedure. During the issuance of <i>Certificates</i> , the <i>Certification Authority</i> uses the private keys of the <i>Certification Unit</i> for placing an electronic signature or seal on the <i>Certificate</i> to protect it.
Public Key	In the public key infrastructure, the element of an asymmetric cryptographic key pair belonging to an actor, which should be made public. The disclosure is typically in the form of a <i>Certificate</i> , which links the name of the actor with its public key. In case of webserver authentication, the public key of the webserver is needed for the verification of its identity. The authenticity of the <i>Certificates</i> can be verified with the public key of the <i>Certification Unit</i> .
Public Key Infrastructure, PKI	An infrastructure based on asymmetric cryptography, including the cryptographic algorithms, keys, certificates, the related standards and legislation, the underlying institutional system, a variety of providers and devices.
Registration Claim	The data and statement given beforehand for the preparation of the <i>Certificate Application</i> and the provider contract to the <i>Trust Service Provider</i> by the <i>Client</i> in which the Client authorizes the <i>Trust Service Provider</i> for data management.
Registration Authority	Organization that checks the authenticity of the <i>Certificate</i> holder's data and verifies that the <i>Certificate Application</i> is authentic, and it has been submitted by an authorized person.

Extraordinary Operational Situation	An extraordinary situation causing disturbance in the course of the operation of the <i>Trust Service Provider</i> , when the continuation of the normal operation of the <i>Trust Service Provider</i> is not possible either temporarily or permanently.
Organization	Legal person.
Organizational Certificate	A <i>Certificate</i> , which was issued for a <i>Organization</i> , namely the <i>Subject</i> of which is the webserver under the control of the <i>Organization</i> . In this case the name of the <i>Organization</i> is indicated in the "O" field of the <i>Certificate</i> .
Organization Administrator	That natural person who is eligible to act during the application and revocation of the website authentication <i>Certificates</i> issued to the <i>Organization</i> and to grant the issuance of organization related personal <i>Certificates</i> and the revocation of such <i>Certificate</i> . The <i>Organization</i> administrator can be appointed by a person eligible for representing the organization. Designation of an <i>Organization Administrator</i> is not compulsory for every <i>Organization</i> , if not designated, then the person eligible to represent the <i>Organization</i> performs the tasks aforementioned.
Trust Service Practice Statement	"The statement of the <i>Trust Service Provider</i> of the detailed procedures or other operational requirements used in connection with the provision of particular <i>Trust Services</i> ." ( <i>Act CCXXII. of 2015. [5] 1. § point 41.</i> )
Service Agreement	"The contract between the <i>Trust Service Provider</i> and the <i>Trust Service</i> client, which includes the conditions for the provision of the <i>Trust Service</i> and for using the services." ( <i>Act CCXXII. of 2015. [5] 1. § point 42.</i> )
Certificate	"The electronic signature certificate, the electronic seal certificate and the <i>Website Authentication Certificate</i> , and all those electronic verifications issued within the framework of the <i>Trust Service</i> by the service provider, which includes the certificate related verification data and the certificate usage related information, and which as an electronic document is reliably protected against the available counterfeiting technologies at the time of the issuance and during its validity period." ( <i>Act CCXXII. of 2015. [5] 1. § point 44.</i> )

Certificate Application	The data and statements given by the <i>Applicant</i> to the <i>Trust Service Provider</i> for <i>Certificate</i> issuance, in which the <i>Applicant</i> reaffirms the authenticity of data to be indicated on the <i>Certificate</i> .
Certificate Repository	Data repository containing various <i>Certificates</i> . A Certification Authority has a Certificate Repository in which the issued certificates are disclosed, but the system containing Certificates available to the application on the computer of the <i>Relying Party</i> is also called Certificate Repository.
Client	The collective term for the <i>Subscriber</i> and every related <i>Applicant</i> denomination.
Revocation	The termination of the <i>Certificate's</i> validity before the end of the validity period indicated on the <i>Certificate</i> too. The <i>Certificate</i> revocation is permanent, the revoked <i>Certificate</i> cannot be reinstated any more.
Revocation Status Records	The records of the suspended and revoked <i>Certificates</i> which includes the fact of the suspension or revocation and the time of the suspension or revocation maintained by the <i>Certification Authority</i> .
Certificate for Website Authentication	"Means an attestation that makes it possible to authenticate a website and links the website to the natural or legal person to whom the certificate is issued." ( <i>eIDAS [1] article 3. point 38.</i> ) The webserver domain or IP address is indicated in the name field of a <i>Website Authentication Certificate</i> .

### 1.6.2 Acronyms

CA	Certification Authority
CP	Certificate Policy
CPS	Certification Practice Statement
CRL	Certificate Revocation List
eIDAS	electronic Identification, Authentication and Signature
LDAP	Lightweight Directory Access Protocol
NMHH	National Media and Infocommunications Authority
OCSP	Online Certificate Status Protocol
OID	Object Identifier
PKI	Public Key Infrastructure
QCP	Qualified Certificate Policy
RA	Registration Authority



TSP Trust Service Provider

## 2 Publication and Repository Responsibilities

### 2.1 Repositories

The *Certification Authority* publishes on its webpage (<https://www.e-szigno.hu>) and through LDAP protocol (<ldap://ldap.e-szigno.hu>) its provider *Certificates*, and those *Certificates* to the disclosure of which the *Applicant* consented to.

The *Trust Service Provider* publishes the *Qualified Signature Certificate Policy*, the *Certification Practice Statement* and other documents containing the terms and conditions its operation is based on.

The *Certification Authority* guarantees, that the availability of its system publishing its service *Certificates*, the *Certificate Repository* and the revocation status information on an annual basis will be at least at least 99.9% per year, while service downtimes may not exceed at most 3 hours in each case.

### 2.2 Publication of Certification Information

The *Trust Service Provider* discloses on its webpage its provider *Certificates*, and those *Certificates* for the *Relying Parties* to the disclosure of which the *Applicant* consented to.

#### Service Provider Certificates

With the following methods the *Certification Authority* discloses the *Certificates* of the certification units and the online certificate status service units it operates:

- The denomination of the root certification units, and the hash of its root certificates in the *Certification Practice Statement*. (see section: 1.3.1.) The information related to their change of status are available at the website of the *Certification Authority*.
- The status change of *Certificates* of intermediate (non-root) is disclosed on the revocation lists, its website and within the confines of the online certificate status response services.
- For the signers of the online certificate status responses the *Certification Authority* – compliant to the best international practice – issues a *Certificate* with extremely short period of validity (for 10 minutes ) thereby eliminating the need for *Certificate* revocation status verification. The revocation status of the OCSP response *Certificates* is only to be disclosed by the *Trust Service Provider* such a way that in case of key compromise, or any other problems there won't be any more new *Certificate* disclosed for the OCSP response signer old private key later. The *Trust Service Provider* discloses OCSP response *Certificates* for a new, secure private key. For the detailed description of the OCSP response validation see section 4.5.2.

## End-User Certificates

With the following methods the *Certification Authority* discloses status information related to the end-user *Certificates* which it had issued:

- on revocation lists,
- within the confines of the online certification status response service.

The end-user *Certificate* revocation is disclosed by the *Trust Service Provider*, and the *Applicant's* consent is not required for it. For status information disclosing methods, see Section 4.10.

The *Trust Service Provider* discloses the contractual conditions and policies electronically on its website.

The new documents to be introduced are disclosed on the website 30 days before coming into force.

The documents in force are available on the site in addition to all previous versions of all documents.

The actual version of policies and contractual conditions is readable in printed form at the customer service of the *Trust Service Provider*.

The *Trust Service Provider* makes available the *Qualified Signature Certificate Policy*, the *Certification Practice Statement* and the *Service Agreement* to the *Client* on a durable medium following the conclusion of the contract.

The *Trust Service Provider* notifies its *Clients* about the change of the General Terms and Conditions.

## 2.3 Time or Frequency of Publication

### 2.3.1 Frequency of the Publication of Terms and Conditions

The disclosure of the *Certification Practice Statement* related new versions is compliant with the methods described in Section 9.12.

The *Trust Service Provider* discloses other regulations, contractual conditions and their new versions if necessary.

The *Trust Service Provider* publishes extraordinary information without delay in accordance with the legal requirements and in the absence thereof when necessary.

### 2.3.2 Frequency of the Certificates Disclosure

The *Trust Service Provider* regarding the disclosure of some *Certificates* follows the practices below:

- the *Certificates* of the root certification units operated by it are disclosed before commencing the service;
- the *Certificates* of the intermediate certification units operated by it are disclosed within 5 workdays after issuance;
- the *Certification Authority* discloses in case of the *Applicant's* consent the end-user *Certificates* in its *Certificate Repository* after issuance without delay.

### 2.3.3 The Changed Revocation Status Publication Frequency

The status information related to the end-user *Certificates* issued by the *Trust Service Provider* and the provider *Certificates* are available immediately within the confines of the online certificate status service.

The information related to the status of the *Certificates* are disclosed in the Certificate Repository on the certificate revocation lists. The practices related to the issuance of the certificate revocation lists are discussed in Section 4.10.

## 2.4 Access Controls on Repositories

Access is provided to anyone for reading purposes to public information of the *Certificates* and status information disclosed by the *Certification Authority* according to the particularities of publication.

The information disclosed by the *Certification Authority* shall only be amended, deleted or modified by the *Certification Authority*. The *Certification Authority* shall prevent unauthorized changes to the information with various defence mechanisms.

## 3 Identification and Authentication

### 3.1 Naming

The section contains requirements for the data indicated in the *Certificates* issued to end-users in accordance with the applied *Certificate Policies*.

The indicated Issuer ID and the Subject ID amongst the basic fields of the *Certificate* comply with the RFC 5280 [19] and RFC 6818 [20] recommendations name-specific format requirements, in addition the *Trust Service Provider* supports the Subject Alternative Names and Issuer Alternative Names fields located amongst the extensions.

#### 3.1.1 Types of Names

##### Denomination of the *Subject*

The denomination of the *Certificate Subject* (content of the Subject field) consists of:

- Common Name (CN) – OID: 2.5.4.3 The name of the *Subject*

In case of *Website Authentication Certificates* the requested domain name or IP address.

Always filled out.

Only that domain name or IP address is indicated that exists and legally used by the Applicant. In case of *Website Authentication Certificates* the domain name or IP address can be in this or in the Subject Alternative Names field.

The *Website Authentication Certificate* shall not be pseudonymous.

Always filled out.

- Surname – OID: 2.5.4.4 – Surname of the natural person  
If behind the requested domain or IP address, there is a natural person, then his surname is in this field, where the *Trust Service Provider* generates the surname from the full name in the CN field.  
Always filled out.
- Given Name – OID: 2.5.4.42 – The first name of the natural person.  
If behind the requested domain or IP address, there is a natural person, then his given name is in this field, where the *Trust Service Provider* generates the first name from the full name in the CN field.  
Always filled out.
- Pseudonym (PSEUDO) – OID: 2.5.4.65 Pseudonym of the Subject  
It may be completed only in case of a pseudonymous Certificate.  
The *Website Authentication Certificate* shall not be pseudonymous.
- Serial Number – OID: 2.5.4.5 Unique identifier of the *Subject*.  
The indication of at least one filled out "Serial Number" field is in the *Certificate* which complies with the following requirements, so that it is able to form a part of the *Subject* permanent unique identifier in case of the usage of "Permanent Identifier" extension according to the RFC 4043 [18] recommendation:

- the identifier value belongs to the *Subject* named in the *Certificate*, identified by the *Trust Service Provider*, and it is unique within the system of the *Trust Service Provider*;
- the *Trust Service Provider* guarantees that the identifier value of any two *Certificates* it issued only matches with each other, if both of the *Certificates* belong to the same *Subject*.

The "Serial Number" value that meets the above requirements is the Subject provider unique identifier.

This field is part of the *Subject* denomination, and is not the same as the *Certificate* serial number defined by RFC 5280.

The unique identifiers issued by the *Trust Service Provider* to the *Subject* are OID formatted: "1.3.6.1.4.1.21528.2.x.y.z".

- In it, the first numbers are fixed (1.3.6.1.4.1.21528.2.2: is the unique identifier of the *Trust Service Provider*),
- "x" is the inner identifier used by the *Trust Service Provider*,
- "y" is the inner identifier used by the *Trust Service Provider*,
- "z" is an automatically issued, a unique identifier within a specific "x.y" value pair.

So the "x.y.z" value pair is the the Subject unique identifier within the system of the Certification Authority.

Because the first part of the identifier identifies the *Trust Service Provider* globally, and the rest of the identifier specifies the *Subject* within the system of the *Trust Service Provider*, so the full identifier identifies the *Subject* in a unique way globally by itself.

There can be multiple OIDs belonging to the same Subject, but only one Subject belongs to an OID. The Subject is always entitled to request a new (unassigned) OID.

The *Trust Service Provider* only issues the same OID for two *Certificates* if it made sure that the *Subject* belonging to the two *Certificate* is the same.

In case of a *Website Authentication Certificate* this OID identifies together in a unique way the owner given in the "Subject DN" field and the domain name set given in the "Subject Alternative Names" field.

The *Certificate* can contain further Serial Number fields. The identifier can be given in a format specified in the ETSI EN 319 412-1 specification, in (Name:Value) format (for example: "ID card number:AAAAAA" ), or in other format requested by the Clients.

In the Serial Number the *Trust Service Provider* – compliant with the standards – does not indicate accents.

These other fields can be considered as the *Subject's* unique identifiers, but the forefront OID formatted identifier fulfils the identifier role according to RFC 4043.

- Organization (O) – OID: 2.5.4.10 The name of the *Organization*

In case of an *Organizational Certificate* the *Organization's* full or shortened name is indicated in the "O" field according to the deed of foundation or a public register.

In case of the *Website Authentication Certificates* the legitimately used trademark, trade name or DBA by the Applicant can be indicated in this field for the request of the Applicant.

In case of an *Organizational Certificate* the field is always filled out.

In case of personal – not related to any organization – certificates this field is not filled out.

In case of a provider *Certificate* issued for a *Trust Service Provider* the "O" field the real name of the organization providing the service is indicated in it.

- Organization Identifier (OrgId) – OID: 2.5.4.97 – Identifier of the organization

In case of an organizational certificate the identifier of the *Organization* indicated in the "O" field is in this field.

Only that data can be in it, which was verified by the *Trust Service Provider*.

In case of an organizational certificate filling out the field is optional.

In case of personal – not related to any organization – certificates this field is not filled out.

- Organizational Unit (OU) – OID: 2.5.4.11 – The name of the organizational unit

In case of an organizational certificate the name of the certification unit related to the organization named in the "O" field, or the trademark, or other information is in this field.

Only that data is indicated here that the *Trust Service Provider* verified and that the *Organization* has the right to use.

The "OU" field is filled only if the "O", "L" and "C" fields are filled.

Optional field. In case of personal – not related to any organization – certificates this field is not filled out.

- Country (C) – OID: 2.5.4.6 – Identifier of the country.  
In case of an *Organizational Certificate* the two-letter country code of the place of incorporation of the *Organization* indicated in the "O" field.  
In case of a *Website Authentication Certificate* not including the name of the *Organization*, the country belonging to the domain or IP address, or if this cannot be clearly decided, then the two-letter country code of the *Applicant's* country.  
Always filled out.  
In case of Hungary, the value of the "C" field is: "HU".
- Street Address (SA) – OID: 2.5.4.9 – Address data  
Not filled.
- Locality Name(L) – OID: 2.5.4.7 – Name of settlement  
In case of an *Organizational Certificate*, the locality name of the *Organization's* place of incorporation.  
In case of a *Certificate* related to the *Organization* it is always filled, in case of a *Certificate* not related to a *Organization*, it is not filled.
- State or Province Name – OID: 2.5.4.8 – Member state, province name  
In case of *Organizational Certificate*, the state, province or county name of the *Organization's* place of incorporation.  
In case of a *Certificate* not related to an *Organization*, it is not filled.
- Postal Code – OID: 2.5.4.17 – Zip code  
In case of *Organizational Certificate*, the postal code of the *Organization's* place of incorporation. If filled, only verified information can be indicated.  
In case of a *Certificate* not related to an *Organization*, it is not filled.
- Title (T) – OID: 2.5.4.12 – Title of the subject  
Not filled.
- E-mail Address (EMAIL) – OID: 1.2.840.113549.1.9.1 – The e-mail address of the *Subject*  
Not filled.

The *Certificates* issued in accordance with the present *Certification Practice Statement* might contain further – in accordance with the referenced *Certificate Policies* – "Subject DN" fields. Only verified text values may be indicated on these fields (they shall not contain values indicating lack of data for example: ".", "-", or " ").

### **Subject Alternative Names**

A "Subject Alternative Names" field is not listed as a critical extension in the *Certificate*. The content will be filled as follows.

The "Subject Alternative Names" field always contain at least one domain name or IP address.

In this field, all domain / IP addresses are listed, even that, which is in the "CN" of the "domain" field. Only a fully qualified domain name (FQDN: Fully Qualified Domain Name) is here, and a reserved domain IP address is not included here.

The *Certificate* may only include a domain name here and in the "CN" of the "Subject" field.

### The Denomination of the Certificate Issuer Certification Unit

The identifier of the *Certificate* issuer (Issuer field) is made up as follows:

- Common Name (CN) – OID: 2.5.4.3  
The name of the *Certificate* issuer certification unit in English (see section: 1.3.1.).
- Organization (O) – OID: 2.5.4.10  
"Microsec Ltd."  
(The name of the *Trust Service Provider* in English without accents.)
- Organization Identifier (OrgId) – OID: 2.5.4.97  
"VATHU-23584497-2-41"  
Not always filled out.
- Organizational Unit (OU) – OID: 2.5.4.11  
"e-Szigno CA"  
(The name of the *Trust Service Provider* organization unit's name without accents; not filled in SHA-256 based provider *Certificates*.)
- Locality (L) – OID: 2.5.4.7  
"Budapest"  
(Domicile city of the *Trust Service Provider* without accents.))
- Country (C) – OID: 2.5.4.6  
"HU"  
(Two letter abbreviation of the domicile country of the *Trust Service Provider*))
- E-mail address (EMAIL) – OID: 1.2.840.113549.1.9.1  
"info@e-szigno.hu"  
Not always filled out.

The same data is indicated in the provider *Certificate* of the *Certificate* issuer, in the subject identifier field.

### The Alternate Names of the Certificate Issuer Certification Unit

The Issuer Alternative Names field is not filled in the end user *Certificates*.

Denominations indicated in the end user *Certificate* issuer's provider *Certificate*:

- In the SHA-1 based provider *Certificates* the signatory (namely the *Certification Unit*) alternative names field is filled as follows:

Subject Alternative Names – OID: 2.5.29.17 (not critical)

CN = (the Hungarian denomination of the certification unit, see section: 1.3.1.)

O = Microsec Kft.

OU = e-Szignó HSZ

L = Budapest

C = HU

rfc822Name = info@e-szigno.hu

- In case of provider *Certificates* based on SHA-256 only the e-mail address is indicated in the alternate names field (rfc822Name).

### 3.1.2 Need for Names to be Meaningful

The following rules are applied to the "SubjectDN" field:

- the identifier shall be meaningful;
- the personal name in the *Certificate* shall be indicated the same way as the notation in public registers ;
- the name of the *Organization* in the *Certificate* shall be indicated the same way as the notation in public registers – or in the absence thereof like in the deed of foundation.

### 3.1.3 Anonymity or Pseudonymity of Subscribers

*Website Authentication Certificate* shall not be pseudonymous.

### 3.1.4 Rules for Interpreting Various Name Forms

In order to interpret the identifiers the *Relying Parties* should act as described in this document. If the *Relying Party* is in need for help related to the interpretation of the identifier or any other data indicated in the *Certificate*, it can contact directly the *Trust Service Provider*. In such case, the *Trust Service Provider* shall not give any further information on the *Client* than indicated in the *Certificate*, – provided that the law does not require it – only provides the information to help interpret the indicated data.

### 3.1.5 Uniqueness of Names

The *Subject* has a unique name in the *Certificate Repository* of the *Trust Service Provider*. In order to ensure the uniqueness, the *Trust Service Provider* gives each *Subject* an identifier (OID), – unique in the *Trust Service Provider's* register – , which is indicated on the *Subject's* unique identifier "Subject DN Serial Number" field.

The *Subjects'* unique identifiers (OID) are distributed in accordance with the order of the received certification applications examination, ensuring the uniqueness of the "Subject" field in the *Certificate*.



## Procedures to Resolve Disputes Relating the Names

The *Trust Service Provider* makes sure of the *Client's* credentials to use the indicated names. The *Trust Service Provider* is entitled to revoke the *Certificate* in question for the illegal use of the name or data.

### 3.1.6 Recognition, Authentication, and Role of Trademarks

In the fields of the end-user *Certificate* required by the *Applicant* trademarks may occur, and the *Trust Service Provider* makes sure of their legitimate use, and in case of a complaint it is entitled to revoke the *Certificate*.

If the *Client* requests a *Certificate*, and asks for brand name or trademark indication, then the *Client* shall provide evidence of the legitimacy of its use, which the *Trust Service Provider* verifies before *Certificate* issuance.

The *Trust Service Provider* uses the e-Szignó trademark during its service provision. The trademark is the property of E-Szignó LP., for the usage of the trademark, the consent is given by the holder.

## 3.2 Initial Identity Validation

The *Trust Service Provider* can use any communication channel within the limits provided by law, for the verification of the identity of the person or organization requesting the *Certificate*, and for checking the authenticity of the data provided.

The *Trust Service Provider* may refuse the issuance of the required *Certificate* at its sole discretion, without any apparent justification.

### 3.2.1 Method to Prove Possession of Private Key

Prior to the issuance of a *Certificate* the *Trust Service Provider* ensures and makes sure that the *Certificate* requester owns and has it under his control the private key belonging to the public key of the *Certificate*.

If the *Trust Service Provider* generates within its organization the private key belonging to the *Certificate* of the *Subject* – typically on *Hardware Security Module* in case of *Certificate Policies* requiring such –, then it does not have to specially verify that the *Subject* owns the private pair of the public key to be verified.

If the *Subject* requests the *Certificate* issuance for a key provided by it – typically in case of software certificates –, then the *Trust Service Provider* accepts the *Certificate Application* in PKCS#10 format, which at the same time confirms, that the owner of the private key asked for the *Certificate* indeed.

### 3.2.2 Authentication of an Organization Identity

#### Authentication of organization identity

The identity of the *Organization* is verified in the following cases:

- if the *Subject* of the *Certificate* to be issued is the *Organization*;

- if the *Certificate* is issued to a natural person, but the name of the *Organization* is indicated on the *Certificate* as well.

Furthermore it is verified in these cases, that:

- whether the natural person acting on behalf of the *Organization* is entitled to act on behalf of the *Organization*;
- whether the *Organization* consented to the issuance of the *Certificate*.

For performing the verification, the *Client* shall give the following data:

- the official denomination and registered office of the *Organization*,
- official registration number of the *Organization* (e.g. company registration number, tax identification number), if applicable;
- the name of the organization unit within the *Organization*, if its indication in the *Certificate* is requested,

The following certificates and evidences have to be attached to the *Certificate Application*:

- the statement with the application submitter's manual signature on that the data given for the *Organization* identification is correct and comply with reality;
- a declaration of the the applicant with his signature that there is no trademark amongst the data to be indicated in the *Organization Certificate*, or if included, proof that the *Organization* is entitled to use the trademark;
- a certificate regarding that on behalf of the organization the *Certificate* application submitter natural person is entitled to submit the application <sup>2</sup>;
- the specimen signature of the person entitled to represent the *Organization* or other, official document equal to the specimen signature, which contains the name and signature of the persons entitled to represent the *Organization* <sup>3</sup>;
- the *Organization* existence, name and the legal status verification document <sup>4</sup>.

The *Trust Service Provider* is bound to verify the validity and authenticity of the presented documents in authentic databases.

The *Trust Service Provider* does not exclude the verification of *Organizations* registered abroad, as far as the data verification with adequate records of the country or obtaining a certificate issued by a trusted third party is feasible.

In respect of data verification, the *Trust Service Provider* accepts:

---

<sup>2</sup>Section 3.2.5. contains the details regarding the verification of the authorizations and privileges.

<sup>3</sup>In case of Court of Registration registered firms the above documents can be acquired by the *Trust Service Provider*.

<sup>4</sup>In case of Court of Registration registered firms the above documents can be acquired by the *Trust Service Provider*.

- certificate issued by the embassy or consulate of the foreign country in Hungary, that the organization exists and the given information is correct;
- certificate issued by a Hungarian embassy or consulate in a foreign country, that the organization exists and the given information is correct.

The *Trust Service Provider* can accept other documents and evidences too, if it makes sure that the level of security is the same as of the above. Obtaining such evidence and submitting it to the *Trust Service Provider* is the *Client's* responsibility.

The *Trust Service Provider* only accepts valid documents, and evidences not older than 3 months.

The *Trust Service Provider* does not issue the *Certificate* if it considers that based on its internal rules it can not verify with corresponding confidence the certificate, document or the data of the foreign organization.

### **Authentication of domain identity**

At least one domain name or IP address shall be in the *Website Authentication Certificates*.

Before the issuance of *Website Authentication Certificates* the *Trust Service Provider* ensures about the genuineness of the domain name or IP address to be indicated in the *Certificate*, and about the eligibility of the *Subject* to use the domain name or IP address. During the inspection a confirmation shall be obtained from authentic records or from a reliable third party, that the *Subject* is entitled to use the domain name or IP address, or the *Subject* shall demonstrate in practice that he has control over the given domain name or IP address

If more than one domain name or IP address is indicated in the *Certificate*, the aforementioned verification shall be carried out in each case.

If a domain name containing a joker "\*" character is indicated in the *Certificate* (wildcard certificate), the *Trust Service Provider* ensures that, the *Applicant* is the legal user of the full domain namespace. The *Trust Service Provider* does not issue a *Certificate*, in which the joker "\*" character stands at the place of the highest domain name that can be registered, that is located directly on the left side of the public domain endings (for example: "\*.com", "\*.co.uk").

The *Trust Service Provider* issues *Certificates* for public domain names and IP addresses used on the Internet, not for domain names and IP addresses reserved for internal use.

### **3.2.3 Authentication of an Individual Identity or e Domain**

The identity of the *Website Authentication Certificate* requester natural person shall be verified.

In case of *Certificates* belonging to the III. certification policy, the method of the identification of the natural person is:

1. During personal identification. In this case:
  - the natural person shall appear in person at the *Registration Authority* to perform the personal identification;
  - the identity of the natural person is verified during personal identification based on a suitable official proof of identity card;

- the natural person shall verify the accuracy of the data for the registration and identity verification with a statement signed with a handwritten signature;
  - The validity of the identification data used for personal identification is checked by the *Registration Authority* with the help of a trusted third party or a public register.
  - The natural person's address shall be checked against a residence card suitable for identification.
  - The *Trust Service Provider* verifies, whether any alteration or counterfeiting happened to the presented cards.
2. Remotely using an electronic identification device, with respect to that the physical presence of a natural person or a representative entitled to represent the legal person before issuing qualified certificates has been guaranteed, and which complies with the substantial or high security levels defined in Article 8 of eIDAS regulation [1]. In these cases:
- In addition, during identification besides subject's name an identification number or other data accepted on a national level that enables that natural persons can be distinguishable from others of the same name shall be supplied.
  - The identification data used for personal identification is checked by the *Registration Authority* with the help of a trusted third party or a public register.
  - The identity of the natural person shall be verified by a copy of the official card suitable for personal identification.
  - The natural person's address shall be checked against a copy of a residence card suitable for identification.
  - The *Trust Service Provider* verifies, whether any alteration or counterfeiting happened to the presented cards.
3. By identification traced back to an electronic signature certificate. In this case:
- The *Applicant* submits the *Certificate Application* in electronic format with an electronic signature based on a non-pseudonymous *Certificate* with a safety classification not lower than the requested *Certificate* (see section 1.2.3.).
  - The identification data used for personal identification is checked by the *Registration Authority* with the help of a trusted third party or a public register.
  - The identity of the natural person shall be verified by a copy of the official card suitable for personal identification.
  - The natural person address checked against a copy of a residence card suitable for identification.
  - The *Trust Service Provider* verifies, whether any alteration or counterfeiting happened to the presented cards.

In case of *Certificates* belonging to the II. certification class, there's no need for personal meeting for the identification of the person, in such cases the *Trust Service Provider* can identify the *Applicant* remotely by the following methods:

- the *Applicant* sends a copy of one of its official identity cards suitable for identity verification to the *Trust Service Provider*;

- the *Applicant* can submit a *Certificate Application* with an electronic signature if the used non-pseudonymous *Certificate* has a safety classification not lower than the requested *Certificate* (see section 1.2.3.).

The *Trust Service Provider* performs data reconciliation with public registers in case of certificates belonging to the II. certification class.

The *Registration Authority* verifies the authenticity of the presented cards in this case too. Furthermore the *Trust Service Provider* verifies that the *Certificate Application* was really sent by the identified *Applicant* through a trustable communication channel. Then the *Trust Service Provider* asks for confirmation from the *Applicant* through such a contact that was not given during the application procedure, but it originates from other sources. There is no need for confirmation through more reliable communication channel, in case of identification performed by an appropriate electronic identification device or by a *Certificate Application* submitted with an appropriate electronic signature. The *Applicant* can prove its identity at its own discretion according to the III. certification class.

The *Trust Service Provider* uses the data reconciled during a previous identification procedure, if the *Applicant* requests new *Certificate* instead of an expired or a revoked one, or if he requests a new *Certificate* besides the existing one during the validity period of the service agreement. The authenticity of the *Certificate* application, the accuracy of the data to be in the *Certificate* and the identity of the person submitting the application shall also be checked.

The *Trust Service Provider* verifies the identity of foreign citizens with the help of their passport or other, personal identification documents, in this case it performs data reconciliation with the proper records of the country, if such records are available. Additional steps are necessary for verifying the foreign document with appropriate confidence, as well as to access the foreign register. In respect of data verification, the *Trust Service Provider* accepts:

- certificate issued by the embassy or consulate of the foreign country in Hungary, that the organization exists and the given information are correct;
- certificate issued by a Hungarian embassy or consulate in a foreign country, that the organization exists and the provided information is correct.

The *Trust Service Provider* can also accept other documents and evidences, if it makes sure that the level of security is the same as of the above. Obtaining such evidence and submitting it to the *Trust Service Provider* is the *Client's* responsibility.

The *Trust Service Provider* only accepts valid documents and evidences not older than 3 months.

The *Trust Service Provider* does not issue the *Certificate* if it considers that based on its internal rules, that it can not verify with corresponding confidence the certificate, document or the data of the foreign organization.

### 3.2.4 Non-Verified Subscriber Information

Only that data can be in the *Certificate* issued by the *Trust Service Provider*, which was verified by the *Trust Service Provider* or on the authenticity of which the *Applicant* made a statement with recognition of their criminal liability.

### 3.2.5 Validation of Authority

The identity of the natural person representing the legal person is verified according to the requirements of Section 3.2.3. before issuing an *Organizational Certificate*.

The right of representation of the natural person shall be verified.

Persons entitled to act on behalf of an *Organization*:

- a person authorized to represent the given *Organization*,
- a person who is mandated for that purpose by an authorized person to represent the *Organization*,
- an *Organization* administrator appointed by an authorized person to represent the *Organization*,

An organization administrator is a person who is eligible to act during the application and revocation of the *Certificates* issued to the *Organization* .

The organization administrator can be appointed during *Certificate* application, or anytime later with the help of the corresponding form. The identifier information of the designated person(s) shall be given on the form, by which he/she can be identified in later litigation. The form shall be (manually or qualified electronically) signed by the representative of the *Organization*, which is verified by the registration associate of the *Trust Service Provider* when received. Appointing an organization administrator is not mandatory, and multiple organization administrators can be appointed too. If there is no appointed organization administrator, then the person entitled to represent the *Organization* can perform this task.

### 3.2.6 Criteria for Interoperation

The *Trust Service Provider* does not work together with other *Trust Service Provideres* during the provision of the service.

## 3.3 Identification and Authentication for Re-key Requests

Re-key is the process when the *Trust Service Provider* issues a *Certificate* to a *Subject* with a replaced public key. Re-key can only be requested during the validity period of the service agreement.

In case of a re-key request, the *Trust Service Provider* verifies the existence and validity of the affected *Certificate*.

Details related to the re-key process can be read in section 4.7.

In case of the certificates belonging to the II. certification class, the *Trust Service Provider* does not perform re-key. Issuing new key container *Certificate* only takes place within the framework of a new *Certificate* application process.

### 3.3.1 Identification and Authentication for Routine Re-key

For the submission of the re-key applications, the *Trust Service Provider* ensures the following options:

- on paper signed manually by the *Applicant* at the customer service of the *Trust Service Provider*, to the mobile registration associate of the *Trust Service Provider* or to some other *Registration Authority's* registration associate, on a date previously agreed,
- in electronic form with an electronic signature of the *Applicant* based on the non-pseudonymous *Certificate* with a safety classification not lower than the *Certificate* to be renewed (see section 1.2.3.);
- during the revocation process of the *Certificate*;
- signed manually, sent by post to the Customer service.

In case of a personal application the applicant identification takes place according to as described in section 3.2.3.

In case of a *Certificate* application according to the aforementioned, signed with an electronic signature there is no need for further verification of the applicant's identity, or the authenticity of the application.

The renewal request is submitted on paper by post, the identification of the applicant and the verification of the application is performed during a personal meeting after receiving the application. in case of the renewal of certificates belonging to the III. certification class.

In case re-key is necessary because the private key belonging to the *Certificate* became compromised, the *Trust Service Provider* ensures options for the *Subject* to indicate this fact during the revocation process. In this case the *Subject* is identified within the confines of the revocation process, and the details are in section 3.6.

### 3.3.2 Identification and Authentication for Re-key After Revocation

The *Trust Service Provider* accepts re-key requests – only during the validity period of the service agreement– in case of *Certificates* revoked . The identity of the person submitting the application is verified the same way, as in case of re-key requests for valid *Certificates* according to the process defined in section 3.2.3, except not all listed options are accessible by the *Client*.

## 3.4 Identification and Authentication in Case of Certificate Renewal Requests

*Certificate* renewal is the process when the *Trust Service Provider* issues a certificate with unchanged *Subject* identification information but for new validity period to a *Subject*. *Certificate* renewal can only be requested during the validity period of the service agreement and for valid *Certificates*.

### 3.4.1 Identification and Authentication in Case of a Valid Certificate

For submitting *Certificate* renewal requests the following options are enabled by the *Trust Service Provider*:

- on paper signed manually by the *Applicant* at the customer service of the *Trust Service Provider*, to the mobile registration associate of the *Trust Service Provider* or to some other *Registration Authority's* registration associate, on a date previously agreed,

- in electronic form with an electronic signature of the *Applicant* based on the non-pseudonymous *Certificate* with a safety classification not lower than the *Certificate* to be renewed (see section 1.2.3.);
- signed manually, sent by post to the Customer service.

In case of a personal application, then the *Applicant's* identification takes place according to as described in section 3.2.3.

In case of a *Certificate* application according to the aforementioned, signed with an electronic signature there is no need for further verification of the applicant's identity, or the authenticity of the application.

In case the renewal request is submitted on paper by post, the identification of the applicant and the verification of the application is performed during a personal meeting after receiving the application. in case of the renewal of certificates belonging to the III. certification class .

### 3.4.2 Identification and Authentication in Case of an Invalid Certificate

Invalid *Certificate* shall not be renewed.

## 3.5 Identification and Authentication for Certificate Modification requests

*Certificate* modification is the process, when the *Trust Service Provider* issues a new *Certificate* to the *Subject* with an unchanged public key, but with different *Subject* identification data.

In this case, the changed *Subject* information is verified by the *Trust Service Provider* as defined in section 3.2. before the *Certificate* issuance.

### 3.5.1 Identification and Authentication in Case of a Valid Certificate

For submitting *Certificate* modification applications the following options are enabled by the *Trust Service Provider*:

- on paper signed manually by the *Applicant* at the customer service of the *Trust Service Provider*, to the mobile registration associate of the *Trust Service Provider* or to some other *Registration Authority's* registration associate, on a date previously agreed,
- in electronic form with an electronic signature of the *Applicant* based on the non-pseudonymous *Certificate* with a safety classification not lower than the *Certificate* to be renewed (see section 1.2.3.);
- signed manually, sent by post to the Customer service.

In case of a personal application, then the *Applicant's* identification takes place according to as described in section 3.2.3.

In case of a *Certificate* application according to the aforementioned, signed with an electronic signature, there is no need for further verification of the applicant's identity, or the authenticity of the application.

In case the modification request is submitted on paper by post, the identification of the *Applicant* and the verification of the application is performed during a personal meeting after receiving the application. in case of the renewal of certificates belonging to the III. certification class.



### 3.5.2 Identification and Authentication in Case of an Invalid Certificate

Invalid *Certificate* shall not be modified.

### 3.6 Identification and Authentication for Revocation Request

The *Trust Service Provider* receives and processes the requests related to the revocation of the *Certificates*, and the announcements (for example related to the private key compromise or to the improper use of the *Certificate*) concerning the revocation of the *Certificates*.

The *Trust Service Provider* ensures that the requests only get accepted from authorized parties besides the rapid processing of the suspension and revocation requests.

The identity of the submitter persons and the authenticity of the applications are verified.

The identification and authentication aspects of such requests are described in section 4.9. .

In case of *Website Authentication Certificates*, suspension is not possible.

## 4 Certificate Life-Cycle Operational Requirements

The issuance of a new *Certificate* for a new *Subject* shall precede the transmission of the *Registration Application* required to the *Trust Service Provider* and signing of the service agreement on the *Subscriber's* part as well as signing of the *Certificate Application* of the *Applicant's* part.

Certificate replacement is the process, when previously registered (and during that, identified) *Subject* requests a new *Certificate* instead of the existing one (issued pursuant to a valid service agreement). Certificate replacement can take place for the below reasons:

- *Certificate renewal* means requesting a *Certificate* with the same data indicated in it as in the previous one by the *Subject* and both *Certificates* are issued for the same public key. The details of *Certificate renewal* are discussed in section 4.6.
- *Certificate modification* means requesting the modification of the *Subject's Certificate* considering data change. The *Trust Service Provider* receives *Certificate modification* requests during the validity period of the *Certificate*. Over the course of *Certificate* modification, the new *Certificate* is issued to the same public key. The details of *Certificate modification* are described in section 4.8.
- *Re-key* means a new *Certificate* issuance by the *Trust Service Provider* for a new public key at the request of the *Subject* during the *Certificate's* validity period or after expiration. The details of *Certificate renewal* are discussed in section 4.7.

When *Clients* – with a valid service agreement– request a new *Certificate*, then the modification of the service agreement is necessary.

The state of a *Certificate* can be valid or revoked. Regulations related to the status changes are discussed in section 4.9., and the *Certificate* status service is discussed in section 4.10.

The *Trust Service Provider* provides *Certificate* maintenance only during the force of the related service agreement. The requirements related to the termination of service agreement are discussed in section 4.11.

## 4.1 Application for a Certificate

For each new *Certificate* issuance, *Certificate Application* submission is required. Prior to submitting the first *Certificate Application*, the *Applicant* shall submit a *Registration Application* to the *Trust Service Provider*, this can be done through the website of the *Trust Service Provider*, for instance. The *Applicant* shall specify their data to be indicated in the *Certificate* and shall specify what kind of *Certificate* they request, and they shall authorize the *Trust Service Provider* for the management of their personal data in the *Registration* request.

The *Trust Service Provider* doesn't consider the data indicated in the *Registration Application* authentic until the *Applicant* confirms them in a *Certificate Application*.

In case the conclusion of a new service agreement is necessary, the *Trust Service Provider* prepares the *Subscriber's* service agreement based on the information given in the *Registration Application*.

The service agreement shall contain the types of *Certificate* available for specific *Subjects* in the frame of the services within the confines of the Agreement.

A new *Certificate* can be requested within the confines of a previously concluded service agreement. If the *Certificate* (*Certificate* replacement) is issued as a replacement of a *Certificate* indicated in the service agreement, it is not necessary to modify the service agreement. If the *Client* requests a new *Certificate* in addition to the extant ones, the service agreement shall be modified.

The *Trust Service Provider* informs the *Subscriber* about the *Certificate* usage terms and conditions prior to the conclusion of the contract.

If the *Applicant* is not the same as the *Subscriber*, then the aforementioned information is also given to the *Applicant*.

The *Trust Service Provider* publishes the documents containing this information in a comprehensible manner, made available in an electronically downloadable format as well as upon request in printed form. At the Customer service office, the *Client* has the opportunity for survey and consultation.

In the *Certificate Application* the *Subject* shall at least include the data below:

- data to be indicated in the *Certificate* (for example domain name or IP address, name of *Organization*, city, country);
- the personal identification information of the *Applicant* (full name, number of the identity document, mother's name, date and time of birth);
- the contact of the *Applicant* (telephone number, e-mail address);
- in case of *Organization Certificate* application, the data of the *Organization* (official name, domicile, optionally: identification data, denomination of the organization department);
- the *Subscriber's* data (billing information);

In conjunction with the *Certificate Application* the *Trust Service Provider* ask for and check at least the following documents, certifications, procurations and declarations (in case of remote identification the copies of these):

- documents necessary to identify the *Applicant* according to Section 3.2.3;

- in case of *Organizational Certificate* application, the documents for the identification of the *Organization* according to Section 3.2.2;
- in case of *Organizational Certificate* application, the evidence issued by the *Organization* that the *Applicant* is entitled for representing the *Organization* according to section 3.2.5.;
- if the *Certificate* requested contains a trademark or a brand name, then a certification about the usage rights of the *Applicant* according to section 3.1.6.

#### 4.1.1 Who May Submit a Certificate Application

*Certificate Application* may only be submitted by natural persons, to request a *Certificate* for themselves or for the organization represented. The precondition of *Certificate* issuance is a valid service agreement (signed by the *Subscriber* and the *Trust Service Provider*) concerning *Certificate* issuance and maintenance.

The *Applicant* may submit the *Certificate Application* in the following ways:

- on paper signed manually during the personal identification performed at the customer service of the *Trust Service Provider*, by the mobile registration associate of the *Trust Service Provider* or by some other *Registration Authority's* registration associate,
- on paper sent by post to the postal address of the *Trust Service Provider* (then, in case of *Certificates* belonging to the III. certification class the personal identification will take place later ),
- in electronic form with an electronic signature based on a non-pseudonymous *Certificate* with a security classification not lower than the requested *Certificate*, sent to the *Trust Service Provider's* e-mail address (see section 1.2.3.);

The *Trust Service Provider* verifies that the *Certificate Application* was really sent by that person whose data (documents) is in the application through a different – trustable – communication channel.

The *Subscriber* and the *Applicant* shall provide their contact information during the *Registration Application*.

#### 4.1.2 Enrolment Process and Responsibilities

During the process of the application the *Trust Service Provider* (or the *Registration Authority*) ascertains the identity of the person submitting the *Certificate Application* (see section 3.2.3.).

In case of *Organizational Certificate* application the *Trust Service Provider* (or the *Registration Authority*) identifies the *Organization* (see section: 3.2.2.) and it ensures, that the *Applicant* is entitled to represent the *Organization* (see section: 3.2.5.) and to request a *Certificate* related to the *Organization* (see section: 3.2.2.).

The *Applicant* shall provide all the necessary information for the conduct of the identification processes.

The *Trust Service Provider* performs data reconciliation with public registers (such as the personal data and address register or the company register). In case of a database if it can be arranged, the *Trust Service Provider* performs the data reconciliation electronically.

During the process the *Trust Service Provider* specifies the unique name of the *Subject* and assigns a globally unique ID (OID) to the *Subject*. This happens as defined in section 3.1..

The *Trust Service Provider* registers all the necessary information on the identity of the *Applicant* and the *Organization* for the provision of service and for keeping contact.

The *Trust Service Provider* registers the service agreement signed beforehand by the *Subscriber* that shall contain the *Subscriber's* statement that the *Subscriber* is aware of its obligations and undertakes the compliance.

The *Trust Service Provider* registers the *Certificate Application* signed by the *Applicant* which shall contain the following:

- a confirmation, that the data provided in the *Certificate Application* are accurate;
- a consent, that the *Trust Service Provider* records and processes the data provided in the application;
- the decision about the disclosure of the *Certificate*;
- a statement that there's no brand name or trademark indicated in the requested *Certificate*, or it is indicated and the applicant is entitled to use that.

The *Trust Service Provider* keeps the aforementioned records for the time period required by law.

The *Trust Service Provider* archives the contracts, the *Certificate* application form and every attestation that the *Represented Organization*, the *Applicant* or the *Subscriber* handed in.

If the identity of the *Applicant* or in case of an *Organizational Certificate* the identity of the *Organization* can not be verified without a doubt or any of the indicated data on the *Certificate* application form is incorrect, then the *Trust Service Provider* can, according to its inner regulations give the *Client* the opportunity to correct the missing or incorrect data, and to the hand over the missing attestations within 3 months from the submission of the *Certificate Application*.

## 4.2 Certificate Application Processing

### 4.2.1 Performing Identification and Authentication Functions

The *Trust Service Provider* identifies the *Applicant* according to Section 3.2 ., and it verifies the authenticity of the request.

In case of requesting an organization *Certificate*, the *Organization* is going to be identified too, and the verification of the privileges takes place according to section 3.2. The *Trust Service Provider* registers all the information used by the *Subject* or in case of an *Organizational Certificate* the *Organization* to certify its identity, including the registration number of the documentation used for the certification and the incidental limitations related to its validity.

### 4.2.2 Approval or Rejection of Certificate Applications

To avoid any conflicts of interests, the *Trust Service Provider* ensures its personal and operational independence contrary to the *Subscribers*. It does not constitute a breach of conflicts of interests, if the *Trust Service Provider* issues *Certificates* for its associates.

The *Trust Service Provider* verifies the authenticity of all the information given in the *Certificate Application* to be indicated on the *Certificate* before issuing the *Certificate*.

The *Trust Service Provider* accepts or refuses to fulfil the *Certificate Application* after processing it.

If the identity of the natural person or the organization which is to be identified, or in case of a personal *Certificate*, or any of the indicated data on the *Certificate Application* form is incorrect, and is not corrected by the *Client* upon request of the *Trust Service Provider*, then the *Trust Service Provider* rejects the application.

In case of *Certificate Application* refusal the *Trust Service Provider* informs the *Applicant* and the *Subscriber*, but the *Trust Service Provider* does not have to justify its decision.

### 4.2.3 Time to Process Certificate Applications

The *Trust Service Provider* undertakes the processing of the *Certificate Application* within 5 workdays if all the necessary data and document is available.

## 4.3 Certificate Issuance

The *Trust Service Provider* only issues the *Certificate* to the *Subject* in case of certificates belonging to the III. certification class, in case of the acceptance of the *Certificate Application*.

The issued *Certificate* only contains the data that was indicated in the *Certificate Application* and that was verified by the *Trust Service Provider* during the evaluation process.

In case of *Certificates* belonging to the II. certification class the *Trust Service Provider* only issues the certificate to the *Subject* after verifying the data given in the *Registration Application* and receiving the signed service agreement. The issued *Certificate* only contains that *Subject* data , that was given in the *Registration Application*, and that the *Trust Service Provider* verified during the evaluation.

### 4.3.1 CA Actions During Certificate Issuance

The *Certificate* issuance happens according to strictly regulated and controlled processes, the details are stated by the *Trust Service Provider's* inner regulations and requirements.

### 4.3.2 Notification of the Subscriber about the Issuance of the Certificate

The Certification Authority informs the *Applicant* and the *Subscriber* on the issuance of the *Certificate* and enables the *Applicant* to receive the *Certificate*.

## 4.4 Certificate Acceptance

### 4.4.1 Conduct Constituting Certificate Acceptance

In case of *Certificates* belonging to the III. certification class *Applicant* shall verify the accuracy of the data indicated in the *Certificate* during the takeover of the *Certificate* and shall make a written statement on that. In the statement the *Applicant* verifies the reception of the *Certificate*.

In case of Certificates belonging to the II. certification class, the *Applicant* (or its representative) do not have to separately state the takeover of the issued *Certificate*. By signing the *Certificate Application* the *Subscriber*, and by signing the *Certificate Application* the *Applicant* verifies at the same time its acceptance of the *Certificate Policy* the *Certification Practice Statement* and the other documents containing the contractual conditions.

#### 4.4.2 Publication of the Certificate by the CA

After the *Certificate* receipt – if the *Applicant* consents – the *Trust Service Provider* discloses the *Certificate* in its *Certificate* store.

#### 4.4.3 Notification of Certificate Issuance by the CA to Other Entities

In case of an Organizational *Certificate* the contact of the *Represented Organization* is notified by the *Trust Service Provider* on the *Certificate* issuance without delay.

### 4.5 Key Pair and Certificate Usage

#### 4.5.1 Subscriber Private Key and Certificate Usage

The private key belonging to the *Certificate* shall only be used for website authentication, and any other usage is prohibited.

A private key corresponding to an expired or revoked *Certificate* can not be used.

The *Subject* is bound to ensure the adequate protection of the private key and the activation data (password or PIN code).

The limitations determined in Section 1.4. have to be followed during the usage.

#### 4.5.2 Relying Party Public Key and Certificate Usage

To retain the level of security guaranteed by the *Trust Service Provider*, in the course of performing the webserver authentication the *Relying Party* proceeds prudentially, particularly regarding to the following:

- the *Relying Party* shall verify the validity and revocation status of the *Certificate*;
- the public keys belonging to the *Website Authentication Certificates* shall only be used for website authentication;
- the verifications related to the *Certificate* should be carried out for the entire certificate chain;
- it is recommended to verify that the *Certificate* was issued according to the appropriate Certificate Policy;
- the *Relying Party* shall consider any restrictions indicated in the *Certificate* or in the regulations referenced in the *Certificate*.

If the *Relying Party* does not act in accordance with the proceedings described the *Trust Service Provider* may not be held responsible for the resulting damage.

The *Trust Service Provider* makes available a service for its *Clients* and *Relying Parties* that they can use to verify the issued *Certificates*.

## 4.6 Certificate Renewal

The process when the *Trust Service Provider* issues a new *Certificate* for a new validity period for the same public key with unchanged *Subject* identity information is called *Certificate* renewal.

If the *Subject* would like to use the *Certificate* after the expiration, then it shall initiate the *Certificate* renewal. The *Certificate* renewal technically means the issuance of a new *Certificate*, with the same *Subject* identification data, but new validity period. Other data can change in the *Certificate*, like the CRL, OCSP references or the provider key used for signing the *Certificate*.

### 4.6.1 Circumstances for Certificate Renewal

*Certificate renewal* is only permitted when all of the following conditions are met:

- the *Certificate* renewal request was submitted within the validity period of the *Certificate*;
- the *Certificate* to be renewed is not revoked;
- the private key corresponding to the *Certificate* is not compromised;
- the *Subject* identity information indicated in the *Certificate* is still valid.

The *Trust Service Provider* shall only accept a *Certificate* renewal application within the effect of the service agreement.

If a previous *Certificate* of the *Subject* is revoked or expired, then new *Certificate* can only be requested in the frame of *Re-key* (see section: 4.7. ) or new *Certificate* application (see section: 4.6.).

If any of the *Subject* data indicated in the *Certificate* changed, then new *Certificate* shall be requested within the framework of *Certificate* modification (see section 4.8.).

During the *Certificate renewal*, the *Applicant* is informed if the terms and conditions have changed since the previous *Certificate* issuance.

If the *Applicant* is not the same as the *Subscriber*, then the information aforementioned is also provided to the *Subscriber*.

The *Certificate* renewal is performed within the framework of a valid service agreement, there is no need for its modification.

### 4.6.2 Who May Request Renewal

The *Certificate* renewal shall be initiated by a person who is entitled to submit an application for a new *Certificate* of the same type at the time of the submission of renewal application.

The applicant shall state in the *Certificate* renewal application, that the *Subject* identification data indicated in the *Certificate* are still valid.

The *Trust Service Provider* is entitled to initiate the renewal of the *Certificate* if the service signatory key used for the issuance of the *Certificate* shall be replaced out of turn.

The *Trust Service Provider* provides the following possibilities for *Certificate* renewal application submissions:

- on paper signed manually at the customer service of the *Trust Service Provider*, by the mobile registration associate of the *Trust Service Provider* or by some other *Registration Authority's* registration associate, on a date previously agreed,
- in an electronic form with an electronic signature based on the non-pseudonymous *Certificate* with a safety classification not lower than the *Certificate* to be renewed (see section 1.2.3.);
- signed manually, sent by post to the Customer service.

#### 4.6.3 Processing Certificate Renewal Requests

During the evaluation of the *Certificate* renewal application, the *Trust Service Provider* verifies that:

- the submitted *Certificate* renewal application is authentic;
- the submitter of the *Certificate* renewal application has the appropriate entitlement and authorization;
- the submitter of the *Certificate* renewal application stated that the data of the *Subject* to be indicated in the *Certificate* are unchanged and accurate;
- the *Certificate* renewal application was submitted during the *Certificate's* validity period;
- the *Certificate* to be renewed is not revoked;
- based on currently available information about the cryptographic algorithms used, they still will be applicable even during the planned validity period of the *Certificate* to be issued.

The method used for identification and authentication during the *Certificate* renewal is stated in Section 3.4.

#### 4.6.4 Notification of the Client about the New Certificate Issuance

The *Trust Service Provider* informs the *Applicant* and the *Subscriber* about the *Certificate* issuance.

#### 4.6.5 Conduct Constituting Acceptance of a Renewed Certificate

During the *Certificate* renewal process, there is no key generation, thus there is no need to handover key to the *Subject*. The renewed *Certificate* can be received (downloaded) without personal encounter.

The subject accepts the *Certificate* by its usage without additional declaration.



#### 4.6.6 Publication of the Renewed Certificate by the CA

The *Trust Service Provider* discloses the renewed *Certificate* the same method as the original *Certificate*.

#### 4.6.7 Notification of Other Entities about the Certificate Issuance

In case of an *Organizational Certificate* the contact of the *Represented Organization* is notified by the *Trust Service Provider* on the *Certificate* issuance without delay.

### 4.7 Certificate Re-Key

*Re-key* means the process when the *Trust Service Provider* issues a new *Certificate* for the *Subject* in a way that the public key is to be changed.

Further data may be optionally changed in the new *Certificate* issued during the *Re-key* process, for example validity period, the CRL and OCSP links or the provider key used to sign the *Certificate*. In case of keys belonging to the II. certification class, the Certification Authority does not perform *Re-key*. The issuance of a *Certificate* with a new key is exclusively performed within the framework of new *Certificate* application.

#### 4.7.1 Circumstances for Certificate Re-Key

The validity of the previous *Certificate* is not required for *Re-key*, but the *Trust Service Provider* shall only accept *Re-key* applications within the scope of the service agreement.

During the *Certificate Re-key*, the *Applicant* is informed by the *Trust Service Provider* if the terms and conditions have changed since the previous *Certificate* issuance. If the *Applicant* is not the same as the *Subscriber*, then the information aforementioned is also given to the *Subscriber*. *Certificate Re-key* is performed within the framework of a valid service agreement, there is no need for its modification.

#### 4.7.2 Who May Request Certification of a New Public Key

The *Certificate Re-key* shall be initiated by a person who would be entitled to submit a new *Certificate Application* at the time of the submission of the *Re-key* application.

The applicant shall state in the *Certificate Re-key* application, that the *Subject* identification data indicated in the *Certificate* are still valid, or they shall give the new data and make a statement of its validity.

The *Trust Service Provider* ensures the following possibilities to submit *Certificate* renewal application:

- on paper signed manually at the customer service of the *Trust Service Provider*, to the mobile registration associate of the *Trust Service Provider* or to some other *Registration Authority's* registration associate, on a date previously agreed,
- in an electronic form with an electronic signature based on the non-pseudonymous *Certificate* with a safety classification not lower than the *Certificate* to be renewed (see section 1.2.3.);

- during the revocation process of the *Certificate*;
- signed manually, sent by post to the Customer service.

#### 4.7.3 Processing Certificate Re-Key Requests

During the evaluation of the *Certificate Re-key* application the *Trust Service Provider* verifies that:

- the submitted application is authentic;
- the submitter of the application has the appropriate entitlement and authorization;
- the data indicated in the application are accurate;
- based on the currently available information about the cryptographic algorithms used, they still will be applicable even during the planned validity of the *Certificate* to be issued.

Before processing the *Re-key* request the identity of the person submitting the *Certificate Re-key* application shall be verified according to section 3.3.

#### 4.7.4 Notification of the Client about the New Certificate Issuance

The *Trust Service Provider* informs the *Applicant* and the *Subscriber* about the *Certificate* issuance.

#### 4.7.5 Conduct Constituting Acceptance of a Re-Keyed Certificate

#### 4.7.6 Publication of the Re-Keyed Certificate

The *Trust Service Provider* discloses the renewed *Certificate* the same way as the original *Certificate*.

#### 4.7.7 Notification of Other Entities about the Certificate Issuance

In case of an *Organizational Certificate* the contact of the *Represented Organization* is notified by the *Trust Service Provider* on the *Certificate* issuance without delay.

### 4.8 Certificate Modification

*Certificate modification* means the process when the *Trust Service Provider* issues a new *Certificate* for the *Subject* with changed *Subject* identity information but with unchanged public key.

The *Certificate* modification technically means new *Certificate* issuance. The *Trust Service Provider* is bound to revoke the previous *Certificate*, that contains invalid data. (see section: 4.9.) .

Previous data can change in the new *Certificate* issued during the *Certificate* modification, such as the validity period, the CRL and OCSP references or the *Trust Service Provider* key used for *Certificate* signing.

#### 4.8.1 Circumstances for Certificate Modification

*Certificate modification* becomes necessary in the following cases:

- change of data indicated in the *Subject's Certificate*;
- in the *Certificate* issuing system of the *Trust Service Provider* any data of the *Certificate* issuer CA indicated in the "Subject DN" is changed, or its public key is changed and as a result of it, its provider *Certificate* is changed;
- the *Certificate* profile determined by the *Trust Service Provider* is changed.

Requirements of *Certificate* modification:

- the *Certificate* modification application was submitted during the *Certificate's* validity period;
- the *Certificate* to be modified is not revoked;
- the private key corresponding to the *Certificate* is not compromised.

The *Trust Service Provider* only accepts *Certificate* modification application in the scope of the Service Agreement.

If the previous *Certificate* of the *Subject* is revoked or expired, then the new *Certificate* can be requested within the framework of *Re-key* (see section: 4.7.) or new *Certificate* application (see section: 4.6.).

During the *Certificate* modification, the *Applicant* is informed if the terms and conditions have changed since the previous *Certificate* issuance.

If the *Applicant* is not the same as the *Subscriber*, then the information aforementioned is also given to the *Subscriber*. The *Certificate* modification is performed within the framework of a valid service agreement, there is no need for its modification.

#### 4.8.2 Who May Request Certificate Modification

The *Certificate* modification shall be initiated by a person who is entitled to submit a new *Certificate* application at the time of the submission of the modification application.

In the *Certificate* modification request, the applicant shall give the new data and shall make a statement of their accuracy.

The *Trust Service Provider* initiates the *Certificate* modification if it becomes aware of that the *Subject's* data indicated in the *Certificate* is changed.

The *Trust Service Provider* ensures the following possibilities to submit *Certificate* renewal application:

- on paper signed manually at the customer service of the *Trust Service Provider*, to the mobile registration associate of the *Trust Service Provider* or to some other *Registration Authority's* registration associate, on a date previously agreed;
- in an electronic form with an electronic signature based on the non-pseudonymous *Certificate* with a safety classification not lower than the *Certificate* to be renewed (see section 1.2.3.);

- during the revocation process of the *Certificate*;
- signed manually, sent by post to the Customer service.

#### 4.8.3 Processing Certificate Modification Requests

During the evaluation of the submitted *Certificate* modification application, the *Trust Service Provider* verifies that:

- the submitted *Certificate* renewal application is authentic;
- the submitter of the *Certificate* renewal application has the appropriate entitlement and authorization;
- the data given in the application are accurate;
- the *Certificate* renewal application was submitted during the *Certificate*'s validity period;
- based on the currently available information about the cryptographic algorithms used, they still will be applicable even during the planned validity period of the *Certificate* to be issued.

The *Trust Service Provider* verifying the validity of the *Subject*'s data proceeds the same as the initial verification performed before a new *Certificate* issuance.

Before the execution of the *Certificate* modification application, the applicant shall be identified according to section 3.5.

#### 4.8.4 Notification of the Client about the New Certificate Issuance

The *Trust Service Provider* informs the *Applicant* and the *Subscriber* about the *Certificate* issuance.

#### 4.8.5 Conduct Constituting Acceptance of Modified Certificate

During *Certificate* modification, there is no new key generation, thus there is no need to handover key to the *Subject*. The modified *Certificate* can be received (downloadable) without personal encounter.

The *Subject* accepts the *Certificate* by its usage, and there is no need for further statement.

#### 4.8.6 Publication of the Modified Certificate by the CA

The *Trust Service Provider* discloses the modified *Certificate* the same way as the original *Certificate*.

#### 4.8.7 Notification of Certificate Issuance by the CA to Other Entities

In case of an *Organizational Certificate* the contact of the *Represented Organization* is notified by the *Trust Service Provider* on the *Certificate* issuance without delay.

## 4.9 Certificate Revocation and Suspension

The process when the *Trust Service Provider* terminates the validity of the *Certificate* before expiration is called *Certificate* revocation. The *Certificate* revocation is a permanent and irreversible status change; the revoked certificate will never be valid again.

The *Website Authentication Certificate* shall not be suspended.

The usage of the private key belonging to the revoked *Certificate* shall be eliminated immediately. If possible, the private key belonging to the revoked *Certificate* shall be destroyed immediately after revocation.

Responsibility regulations related to revocation:

- Before the arriving of the revocation request to the *Trust Service Provider*, the *Applicant*, and the *Subscriber* is responsible for the damages arising.
- After that moment when, the *Trust Service Provider* accepts the revocation notification, the *Trust Service Provider* is responsible for the damages arising. The *Trust Service Provider* forthwith publishes the changed revocation state of the *Certificate* after accepting the request.
- If the *Trust Service Provider* has already published the invalid revocation state of the *Certificate*, the *Trust Service Provider* does not take any responsibility, if the *Relying Party* considers the *Certificate* valid.

### 4.9.1 Circumstances for Revocation

*Certification Authority* takes action on the revocation of the end-user *Certificate* in the following cases:

- *Certificate* modification because of data change referring to the *Subject*;
- the *Trust Service Provider* becomes aware that the data in the *Certificate* do not correspond to reality;
- the *Applicant* or the *Subscriber* notifies the *Trust Service Provider* that the *Certificate Application* is not approved and subsequently the approval is not given;
- if the *Trust Service Provider* issued the *Certificate* based on a document from a third party, and it withdraws that document in writing;
- the *Applicant* or the *Subscriber* requests the revocation of the *Certificate* in writing;
- the *Trust Service Provider* becomes aware that the private key is not in the exclusive possession of the *Applicant* ;
- the *Trust Service Provider* becomes aware that the certificate was used illegally;
- the *Trust Service Provider* becomes aware that the *Subscriber* failed to fulfil any of its financial obligations according to the service agreement;
- the termination of service agreement;

- the *Trust Service Provider* becomes aware that the usage of the domain name or IP address indicated in the *Certificate* is no longer eligible (e.g court withdrew the right to use the domain, or the owner does not renew the domain registration);
- the *Trust Service Provider* becomes aware that the wildcard certificate was used for deceptive domain name authentication;
- the *Trust Service Provider* becomes aware that the public key in the *Certificate* does not comply with the requirements defined in Section 6.1.5. and 6.1.6.;
- the *Trust Service Provider* becomes aware that the *Certificate* was not issued according to the related *Qualified Signature Certificate Policy* and the *Certification Practice Statement*;
- the *Trust Service Provider* becomes aware that the private key of the *Certificate* issuer certification unit might be compromised;
- the format and technical content of the *Certificate* presents an unacceptable risk to the *Relying Parties* (for example, if the used cryptographic algorithm or key size is no longer secure);
- the *Trust Service Provider* is no longer entitled to issue *Certificates*, and maintenance is not provided for the existing CRL and OCSP services;
- the *Trust Service Provider* has terminated its activities;
- the law makes revocation mandatory;

The *Trust Service Provider* shall revoke is bound to take action on the revocation of the *Certificate* of the intermediate certification unit in the following cases:

- *Certificate* modification because of data change relating to the certification unit or the *Trust Service Provider*;
- the *Trust Service Provider* becomes aware that it is not in the exclusive possession of the private key;
- the *Trust Service Provider* becomes aware that the *Certificate* is used illegally;
- the *Trust Service Provider* becomes aware that the public key in the *Certificate* does not comply with the requirements defined in Section 6.1.5 and 6.1.6. ;
- the format and technical content of the *Certificate* presents an unacceptable risk to the *Relying Parties* (for example, if the used cryptographic algorithm or key size is no longer secure);
- the *Certificate* was not issued according to the relevant *Qualified Signature Certificate Policy* and the *Certification Practice Statement* or the operation of the intermediate certification unit does not comply with the relevant *Qualified Signature Certificate Policy* or *Certification Practice Statement*;
- the *Trust Service Provider* is no longer entitled to issue *Certificates*, and maintenance is not provided for the CRL and OCSP services related to the *Certificates* ;

- the *Trust Service Provider* has ended its activities;
- the law makes the revocation mandatory.

*Certification Authority* is bound to take action on the revocation of the *Certificate* of the intermediate certification unit operated by other *Certification Authority* in the following cases:

- *Certificate* modification because of data change relating to the certification unit or the other *Certification Authority*;
- the issuer *Certification Authority* becomes aware that the data indicated in the *Certificates* do not correspond with reality;
- *Certification Authority* operating the intermediate certification unit notifies the issuer *Certification Authority* that the *Certificate Application* is not approved and its consent is not given afterwards either;
- if *Certification Authority* issued the *Certificate* based on a document from a third party, and that third party withdraws the document in writing;
- the operator of the intermediate certification unit requests the revocation of the *Certificate* in writing;
- the issuer *Certification Authority* becomes aware that the operator of the intermediate certification unit is not in the exclusive possession of the private key;
- the issuer *Certification Authority* becomes aware that the *Certificate* is used illegally;
- the issuer *Certification Authority* becomes aware that the public key in the *Certificate* does not anymore comply with the requirements defined in Section 6.1.5 and 6.1.6. ;
- the format and technical content of the *Certificate* presents an unacceptable risk to the Relying parties (for example, if the used cryptographic algorithm and key size is no longer safe);
- the issuer *Certification Authority* becomes aware that the *Certificate* is not issued according to the related *Qualified Signature Certificate Policy* and the *Certification Practice Statement* or the operation of the intermediate certification unit operator does not comply with the relevant *Qualified Signature Certificate Policy* or *Certification Practice Statement*;
- the *Certification Authority* is no longer entitled to issue *Certificates*, and maintenance of the CRL and OCSP services for the existing *Certificates* is not provided;
- the *Certification Authority* operating the certification unit or the issuer *Certification Authority* of its *Certificate* has ended its activities;
- the law makes the revocation mandatory.

#### 4.9.2 Who Can Request Revocation

The revocation of the *Certificate* may be initiated by:

- the *Subscriber*;
- the *Applicant*;
- in case of *Organizational Certificate*, the *Organization's* authorized representative;
- the contact person specified in the service agreement;
- the *Trust Service Provider*.

#### 4.9.3 Procedure for Revocation Request

The *Trust Service Provider* ensures the following possibilities to submit a revocation request:

- on paper signed manually at the customer service of the *Trust Service Provider* during office hours in person;
- in an electronic form with an electronic signature based on a non-pseudonymous *Certificate* with a security classification not lower than the *Certificate* to be revoked (see section 1.2.3.);
- signed manually, sent by post to the customer service.
- Through the website of the *Trust Service Provider* 24 hours a day. The IT system of the *Trust Service Provider* shall process immediately the applications submitted through its website, the site shall inform the application submitter about the results of the evaluation.
- Through a telephone hotline of the *Trust Service Provider* 24 hours a day. The administrator of the *Trust Service Provider* shall review the applications received on the *Trust Service Provider* hotline telephone within the duration of the call, and he shall notify the applicant about his decision.

The *Trust Service Provider* verifies the authenticity of the request, and the submitter's eligibility during the evaluation of the request.

In case of submitting a personal request, the identification of the requester takes place according to section 3.2.3.

In case of *Certificate* application signed with a valid electronic signature, there is no need for further verification of the identity of the applicant and the authenticity of the application.

In case of submitting revocation application on paper, via mail the *Trust Service Provider* verifies the manual signature on the application, and gets in touch with the applicant on one of its contacts provided at the registration, in order to reinforce the application.

The reason for revocation shall be stated. If the revocation was requested by the *Client*, and it does not state the reason for revocation, then the *Trust Service Provider* considers that the reason for revocation is that the *Subject* does not want to use the *Certificate* anymore.

If the *Client* asks for revocation due to key compromise, the *Trust Service Provider* ensures a possibility during the revocation process, to request a new *Certificate* in the framework of *Re-key* to replace the *Certificate* to be revoked. The rules for *Re-key* are in section 4.7.



#### 4.9.4 Revocation Request Grace Period

The *Trust Service Provider* does not apply grace period during the fulfilment of revocation requests.

#### 4.9.5 Time Within Which CA Must Process the Revocation Request

In case of applications submitted in person, the time of arrival is when the *Client* provides all the necessary data for revocation. In case of applications sent by post or electronic mail, the time of arrival is when the mail arrives to the Customer Service office of the *Trust Service Provider* at office hours, or when it arrives to the mailbox on the server of the *Trust Service Provider*. Letters arriving out of office hours are considered as arrived at the beginning of the next office hours. The *Trust Service Provider* only undertakes the requirements for requests sent for addresses stated in section 1.2., in case of statements sent to other addresses – specially directly sent to specific associate of the *Trust Service Provider* – or via other channels, the *Trust Service Provider* does not offer any availability.

The *Trust Service Provider* investigates the *Website Authentication Certificate* related reported problems and decides about further steps within 24 hours.

The *Trust Service Provider* revokes the *Website Authentication Certificates* within 24 hours after the conditions defined in section 4.9.1 are met.

The *Trust Service Provider* revokes the *Website Authentication Certificate* issuer intermediate certification units' *Certificates* within 7 days after the conditions defined in section 4.9.1 are met.

#### 4.9.6 Revocation Checking Requirement for Relying Parties

To maintain the level of security guaranteed by the *Trust Service Provider*, prior to the adoption and use of the information indicated in the *Certificate*, it is necessary for *Relying Parties* to act with proper carefulness. It is particularly recommended for them to verify all of the *Certificates* located in the *Certificate* chain according to the relevant technical standards. The verification should cover the verification of the *Certificates*' validity, the policy requirements and key usage, and the checking of the referenced CRL or OCSP based revocation information.

#### 4.9.7 CRL Issuance Frequency (If Applicable)

The *Trust Service Provider* issues a new *Certificate* revocation list at least once a day, but in case of revocation immediately after the acceptance of the notification for its end user *Certificates*.

The validity of these certificate revocation lists is to a maximum of 25 hours.

The *Trust Service Provider* issues a new *Certificate* revocation list at least once a year or in case of a revocation within 24 hours for its intermediate certification units. The validity of these issued *Certificate* revocation lists is to a maximum of 12 months.

#### 4.9.8 Maximum Latency for CRLs (If Applicable)

At most 5 minutes elapse between the generation and disclosure of the revocation list (CRL).

#### 4.9.9 Online Revocation/Status Checking Availability

The *Trust Service Provider* provides online *Certificate* status (OCSP) service.

#### 4.9.10 Online Revocation Checking Requirements

The online *Certificate* status service complies with the requirements of Section 4.10 .  
*Certification Authority* provides OCSP service through GET method.

#### 4.9.11 Other Forms of Revocation Advertisements Available

The *Trust Service Provider* makes available in its public *Certificate* Repository – with their status – the revoked *Certificates*. Thus by searching in the *Certificate* Repository the *Clients* and the *Relying Parties* can personally (without the help of an application) verify the revocation status of a *Certificate*.

#### 4.9.12 Special Requirements for Key Compromise

In case of any certification unit's private key is compromised, the *Trust Service Provider* makes every reasonable effort in order to notify the *Relying Parties* about the incident. It publishes any status change on the provider *Certificates* on its webpage. In case of compromised *Certificates* issued by the *Trust Service Provider*, the *Trust Service Provider* is able to revoke the end-user *Certificate* belonging to the compromised private key. The revocation reason information (reasonCode) in this case is set to keyCompromise (1) value.

#### 4.9.13 Circumstances for Suspension

The validity of the *Website Authentication Certificates* shall not be suspended.

#### 4.9.14 Who Can Request Suspension

Not applicable.

#### 4.9.15 Procedure for Suspension Request

Not applicable.

#### 4.9.16 Limits on Suspension Period

Not applicable.

### 4.10 Certificate Status Services

The *Trust Service Provider* provides the following possibilities for the *Certificate* status query:

- OCSP – online *Certificate* revocation status query service,

- CRL – certificate revocation lists.

The revoked *Certificates* are listed in the revocation lists.

The new status of the *Certificate* – see section: 4.9. – appears instantly in the revocation records of *Trust Service Provider* in case of revocation after the successful completion of the process. From that moment, the OCSP responses provided by the *Trust Service Provider* shall contain the new revocation status of the certificate.

In case of revocation the *Trust Service Provider* issues a new CRL without delay – see section: 4.9.

The *Trust Service Provider* issues an extraordinary revocation list in case of *Certificate* revocation due to key compromise instantly after recording the event.

OCSP response issued by the *Trust Service Provider* shall not contain "good" status information for *Certificates* that were not issued by the given certification unit (positive OCSP).

#### 4.10.1 Operational Characteristics

Each certification unit of the *Trust Service Provider* issues revocation list with the frequency below:

- The productive (not root) SHA-256 based certification units operated within the system of the *Trust Service Provider* issue CRL once in at the most of 24 hours.
- The "Microsec e-Szigno Root CA 2009" root certification unit issues a CRL once in at the most of 24 hours.
- The SHA-1 based intermediate units within the system of the *Trust Service Provider* issue closing CRL, with the same validity period "nextUpdate" as the validity period of the *Certificate* of the unit.
- The "Microsec e-Szigno Root CA" root certification unit issues a CRL at most per month.
- The "e-Szigno OCSP CA" root certification unit issues a CRL once at the most of 24 hours.<sup>5</sup>

The all-time current revocation lists for the specific *Certificates* can be reached at the following address: <https://e-szigno.hu/en/pki-services/ca-certificates.html>

The effective date of the revocation lists "thisUpdate" marks also the time when the certification unit assembled and started signing the revocation list. After that, in case of long revocation lists the publication of the revocation list may even take 1 or 2 minutes. The appearance of the next revocation list ("nextUpdate") marks the next time, from what the list is publicly available. Accordingly, the time interval between the date of the revocation list entering into force, and the date of publication of the next revocation list can be longer than the time intervals above, but this does not affect the time interval between the appearance of the CRLs is at most 24 hours, and (in case of a CRL related to Certification Authority Certificates) 1 month.

Regarding, that amongst the provided services, the validity of the *Certificate* can be determined the fastest and the easiest with OCSP, the *Certification Authority* recommends the use of OCSP to its *Clients*.

---

<sup>5</sup>The CRL issued by the "e-Szigno OCSP CA" does not apply to any *Certificate*, it is always empty, because the OCSP responder *Certificates* issued by this unit includes an "ocspNoCheck" extension.

### Online Certificate Status Protocol (OCSP)

The *Trust Service Provider* publishes the revocation status of the *Certificates* with the OCSP service too. Via this service, the same status is available as by the newest CRL.

In respect of the *Certificate* based on SHA-256, the *Trust Service Provider* provides OCSP service according to the RFC 2560 "authorized responder" principle, so its every certification unit certifies separately an OCSP responder, which provides information on the revocation status of the *Certificates* issued by the certification unit (section 1.3.1.).

The *Trust Service Provider* provides OCSP services two different ways, below the characteristics of the two versions are shown.

#### OCSP Service Provided for Clients

- Only those *Clients* use of this version of the OCSP service, that have a valid service agreement for the maintenance of that *Certificate*. The *Trust Service Provider* can identify the *Client* by the *Certificate* or by a username password pair at the query.
- This version of the OCSP service is available for all *Certificates*, the responses always contain the current information listed in the registry of the *Trust Service Provider*.
- The issued OCSP response is always made at the time of the query. The "thisUpdate" and "producedAt" time values in the OCSP response match with the time of the query.
- The "nextUpdate" indicated in the response is either not filled, or contains a time value not later than the responder certification expiration time.
- With the help of the OCSP service provided to *Clients*, an evidence always can be acquired that later verifies towards third parties the revocation status of the *Certificate* indicated in the registry of the *Trust Service Provider* for the query date.

#### Public and Free OCSP Service

- This version of OCSP service is publicly and freely available, any *Relying Party* can avail itself of it same as the revocation lists. There is no need for authentication at query.
- This version of OCSP service can be reached through the URLs indicated on the *Certificates*.
- Based on the RFC 6960 "Response Pre-production" process, the issued OCSP response can be created before the query and does not necessarily contain the nonce element. The *Trust Service Provider* can give the same response for multiple queries. The "thisUpdate" and "producedAt" time values are identical, but these can precede the time of the query.
- The "nextUpdate" indicated in the response is either not filled, or contains a time value not later than the responder certification expiration time.
- The OCSP responses always contain the current information listed in the revocation registry of the *Trust Service Provider*, but if the "thisUpdate" time of the OCSP response is earlier than the time for which the verification is carried out – which is either earlier or coincides with the time of the query –, then the OCSP response is not clear evidence for a third party regarding the revocation status of the *Certificate*.

Due to the indicated differences of the aforementioned two versions of the OCSP services, the public and free service can be considered equivalent to the service provided to the *Clients* in the following cases:

- If there is no need for OCSP response storage, rather it is used for prompt, immediate decision making. In this case, it is acceptable, that the OCSP response does not verify the validity of the *Certificate* clearly for third parties at a definite time subsequently.
- If the time span between the time of the OCSP query and the time, regarding when the verification is made, is bigger, than the difference of the "nextUpdate" and "thisUpdate" values of the stored OCSP response (which can be at most the validity period of the responder certificate used for signing the OCSP response). In this case, the OCSP responses provided by the public and free service can be accepted as a clear evidence for the third party, because the thisUpdate field in them is guaranteed to be later than the time, regarding when the verification is made.
- If the verifier party does not query the OCSP response itself (but for example uses an OCSP response attached to an archive signature), then it is not necessary to check, which sources the OCSP response came from originally. It is sufficient to verify only that the "thisUpdate" value in the OCSP response is later, than the time regarding which the verification is made.

The *Trust Service Provider* ensures the aforementioned two versions of the OCSP services with the same availability.

#### 4.10.2 Service Availability

The *Trust Service Provider* ensures that the availability of the *Certificate Repository* and the terms and conditions pertaining to the *Certificates* issued by the *Trust Service Provider* is at least 99.9% per year, and the length of downtime shall not exceed at most 3 hours.

The *Trust Service Provider* ensures that the availability of the revocation status information and the revocation management service is at least at least 99.9% per year, and the length of downtimes shall not exceed at most 3 hours on any occasion.

The response time of the revocation status service in case of normal operation is less than 10 seconds.

#### 4.10.3 Optional Features

The *Trust Service Provider* provides various (CRL and two types of OCSP) services according to the descriptions in this section, in the framework of *Clients* and *Relying Parties* can verify the revocation status of the *Certificates* issued by the *Trust Service Provider*. Besides these, the *Trust Service Provider* makes available in its public *Certificate Repository* – with their status indicated – the revoked *Certificates*, so while searching in the *Certificate Repository* the *Clients* and *Relying Parties* can (without the help of an application) verify the revocation status of the *Certificate*.

### 4.11 End of Subscription

The *Trust Service Provider* revokes the end-user *Certificates* in case of the termination of the contract concluded with the *Subscriber*.

## 4.12 Key Escrow and Recovery

The *Trust Service Provider* does not provide key escrow service for a private key belonging to a *Website Authentication Certificate*.

### 4.12.1 Key Escrow and Recovery Policy and Practices

The private key belonging to the *Website Authentication Certificate* shall not be escrowed.

### 4.12.2 Symmetric Encryption Key Encapsulation and Recovery Policy and Practices

The private key belonging to the webserver *Certificate* shall not be escrowed, so regarding that the symmetric encryption keys do not have to be managed.

## 5 Facility, Management, and Operational Controls

The *Trust Service Provider* applies physical, procedural, and personnel security precautions that comply with acknowledged standards, along with the administrative and governance related procedures that enforce these.

The *Trust Service Provider* keeps a record of the system units and resources related to the service provision, and conducts a risk assessment on these. It uses protective measures proportional to the risks related to the individual elements.

The *Trust Service Provider* monitors the capacity demands and ensures that the adequate processing power and storage are available for the provision of the service.

### 5.1 Physical Controls

The *Trust Service Provider* takes care that physical access to critical services is controlled, and keeps physical risk of the assets related to critical services at a minimum.

The purpose of physical precautions is to prevent illegitimate access, damage, and unauthorized access to the *Trust Service Provider's* information, and physical zones.

Services that process critical and sensitive information are implemented at secure locations in the system of the *Trust Service Provider*.

The provided protection is proportional to the identified threats of the risk analysis that the *Trust Service Provider* has performed.

In order to provide adequate security:

- The *Trust Service Provider* implements the strongly protected services in its protected computer room. This computer room has been designed and constructed specifically for this purpose, by its design uniform enforcement of various aspects of protection (the placement and structure of the site, physical access (access control and supervision), power supply, air conditioning, protection against water leakage and flooding, fire prevention and protection, media storage etc.) took place.

- The Customer Service office of the *Trust Service Provider* was designed, to be able to meet the requirements for registration services under realistic costs.
- The *Trust Service Provider* constructed its mobile registration units, so that they comply with the requirements imposed on the registration service.
- The *Trust Service Provider* requires its external offices and mobile units to have the same security level as the security of the *Trust Service Provider* registration office and mobile units. The conditions and the expectations of the *Trust Service Provider* are recorded in a contract with the external *Registration Authority*.
- The *Trust Service Provider* implements every critical service and every necessary tool in a separate security zone. All the devices necessary for this are placed in a protected computer room – forming part of the security zone.

### 5.1.1 Site Location and Construction

The IT system of the *Trust Service Provider* is located and operated within a properly secured *Data Centre* with physical and logical protection that prevents illegitimate access. Defensive solutions – as for example guarding, security locks, intrusion detection systems, video surveillance system, access control system – are applied over the course of locating and establishing the *Data Centre* that are built on each other and interdependent and together they provide a powerful protection system for the IT systems participating in service provision, and for the preservation of the confidential data stored by the provider.

### 5.1.2 Physical Access

The *Trust Service Provider* protects devices and equipment that take part in the service provision from unauthorized physical access in order to prevent tampering with the devices.

*Trust Service Provider* ensures that:

- each entry to the *Data Centre* is registered;
- only authorized staff members with trusted roles with the right permissions can entry to the computer room individually;
- persons without independent authorization can only stay in the *Data Centre* in justified cases, for the time required and accompanied by personnel with appropriate rights;
- the entry logs shall be archived continuously and evaluated weekly.

The activation data (passwords, PIN codes) of the devices shall not be stored openly even in the *Data Centre*.

In the presence of unauthorized persons:

- data media containing sensitive information are physically out of reach;
- the logged-in terminals are not left without supervision;
- no work process is carried out during which confidential information may be revealed.

When leaving the computer room the administrator shall verify that:

- every equipment of the *Data Centre* is in an adequately secure operation state;
- there's no terminal left logged-in;
- physical storage devices are locked properly;
- systems, devices providing physical protection operate properly;
- the alarm system has been activated.

There are appointed responsible people to carry out regular physical security assessments. The results of the examinations are recorded in the appropriate log entries.

### 5.1.3 Power and Air Conditioning

The *Trust Service Provider* applies an uninterruptible power supply unit in the *Data Centre* that:

- has adequate capacity to ensure power supply for the *Data Centre's* IT and subsidiary facility systems;
- protects IT equipment from voltage fluctuations in the external network, power outages, spikes and other;
- in case of lasting power outage has its own power generation equipment, which – by allowing refueling – is able to provide the necessary energy for any period of time.

The air of the outer environment shall not get into the *Data Centre* directly. The *Data Centre* air purity is ensured with adequate filter system to detect a variety of contaminants from the air (dust, pollutants, and corrosive materials, toxic or flammable substances). The ventilation system provides the necessary amount of fresh air with adequate filtration for the safe working conditions of the operators.

The humidity is reduced to the level required by the IT systems.

The *Trust Service Provider* uses cooling systems with proper performance to provide the necessary operating temperature, to prevent overheating of IT devices.

### 5.1.4 Water Exposures

The *Data Centre* of the *Trust Service Provider* is adequately protected from water intrusion and flooding. The total area of the security zone is free from sanitary facilities, there is not any drain or water pipe close to it. In the protected computer room security is further increased by the use of a raised floor.

### 5.1.5 Fire Prevention and Protection

In the *Data Centre* of the *Trust Service Provider*, a fire protection system approved by the competent fire headquarters operates.

There is the type and quantity of manual fire extinguishers in accordance with the relevant regulations at clearly visible locations in each room.



### 5.1.6 Media Storage

The *Trust Service Provider* protects its media storages from unauthorized access and accidental damage. All audit and archive data is created in duplicate. The two copies are stored separately from each other physically, at locations in a safe distance from each other. The stored media storages are protected from damaging environmental influences such as low or high temperatures, dirt, moisture, sunlight, strong magnetic fields, strong radiation.

The *Trust Service Provider* stores the primary media storages in the operational room of the certification organization, a code locked fireproof vault, the secondary copies in a vault in the customer service office.

### 5.1.7 Waste Disposal

The *Trust Service Provider* ensures the environmental standards compliant disposal of the superfluous assets, and media.

The *Trust Service Provider* does not use the electronic storage media containing information classified as confidential even for storing data classified as not confidential after deleting their content and devices like that shall not be taken outside of the premises of the *Trust Service Provider*. The *Trust Service Provider* physically destroys – according to the rules of disposal – the defective for any other reason unusable, redundant media storages containing confidential classified information:

- chops paper documents up in a shredder machine;
- disassembles the hard drives and smashes the critical components;
- destroys the optical disc with a suitable shredder machine.

### 5.1.8 Off-Site Backup

The *Trust Service Provider* creates a backup weekly from which the whole service could be restored in case of a fatal error. The backups – at least including the last full backup – are stored at an external location that's physical and operational protection is identical to the primary site. The secure data transmission from the primary to the reserve locations is resolved.

## 5.2 Procedural Controls

The *Trust Service Provider* takes care that its systems are operated securely, according to the rules, and with a minimal risk of defects.

Procedural precautions have the objective of supplementing, and at the same time intensifying the effectiveness of physical safeguards, along with those applicable to personnel, by means of appointing and isolating trusted roles, documenting the responsibilities of various roles, as well as specifying the personnel headcounts and exclusion roles necessary for the various tasks, moreover identification and authentication expected in the various roles.

The *Trust Service Provider's* internal governance system ensures that its operation complies with legal, as well as its internal regulations. In its system a responsible person shall be clearly assigned for every given system unit and process.

Individuals responsible for a given system element or process are assigned unambiguously to every system element and every process in its system. Development and operations related tasks are sharply segregated in the *Trust Service Provider's* system. The auditing activity of the independent system auditor and the *Trust Service Provider's* internal auditor ensures the system's appropriate operation.

### 5.2.1 Trusted Roles

The *Trust Service Provider* creates trusted roles (in the wording of the regulation, scope of activities) according to the requirements of decree 24/2016. [6] for the performance of its tasks. The rights and functions are shared among the various trusted roles in such a way that one user alone shall not be able to bypass the security protection measures.

The *Trust Service Provider* defines the following trusted roles, with the following responsibilities:

**Manager with overall responsibility for the IT system of the *Trust Service Provider*:**

The individual responsible for the IT system.

**Security officer:** Senior security associate, the individual with overall responsibility for the security of the service.

**System administrator:** Infrastructure administrator. The individual with the task to install, configure and maintain the systems of the *Trust Service Provider*. Responsible, for the reliable and continuous operation of the assigned system units, and for monitoring the development of technology, and for the detection and proposing of development solutions of the vulnerabilities of each system component.

**Operator:** System operator, individual performing the IT system's continuous operation, backup and restore.

**Independent system auditor:** Individual who audits the logged, as well as archived dataset of the *Trust Service Provider*, responsible for verifying the enforcement of control measures the service provider implements in the interest of operation that complies with regulations, moreover for the continuous auditing and monitoring of existing procedures.

**Registration officer:** Individual responsible for the approval of production, issuance, revocation of end-user certificates.

**Official active in the field of personalization:** The individual, whose task is the Certificate application compilation;

**Official on duty:** The individual with the task to provide 24 hour duty. Responsible for the provision of the 24 hour duty, and for the processing of received applications without delay according to the security rules of the *Trust Service Provider*.

For the provision of trusted roles the manager responsible for the security of the *Trust Service Provider* formally appoints the *Trust Service Provider's* employees.

Only those persons may hold a trusted role who are in employment relationship with the *Trust Service Provider*. Trusted roles shall not be hold in the context of a commission contract.

Up to date records are kept of the trusted roles and in case of any change, the National Media and Infocommunications Authority is notified without delay.

### 5.2.2 Number of Persons Required per Task

The security and operational regulations of the *Trust Service Provider* define that the following tasks can be only performed in protected environment, with the contemporaneous presence of two employees holding trusted roles:

- the generation of the *Trust Service Provider's* own service key pair;
- the backup of the provider's private key;
- the activation of the provider's private key;
- the destruction of the provider's private key.

At least one of the persons performing the procedures listed above shall be a system administrator, and the other person shall not be the independent system auditor.

During the implementation of the operations listed, unauthorized person shall not be present in the room.

### 5.2.3 Identification and Authentication for Each Role

The users managing the IT system of the *Trust Service Provider* have unique identification data, enabling secure identification and authentication of the users.

The users can only access the IT systems critical from the aspect of the provision of the certification service after identification and authentication.

The identification and authentication data are revoked without delay in case of the cessation of user rights.

Every user of the IT system and every actor in the administrative process is identified individually. For the verification of the physical access, the *Trust Service Provider* uses an RFID card based access control system, and for the logical access control, it uses VPN Certificates issued on a Secure Signature-Creation Device. Before successful authorization, not even a single safety-critical task can be performed. Every employee of the *Trust Service Provider* has exactly as many access rights, as it is absolutely necessary for the assigned role.

### 5.2.4 Roles Requiring Separation of Duties

Employees of the *Trust Service Provider* can hold multiple trusted roles at the same time, but the *Trust Service Provider* ensures that:

- the security officer and the registration officer shall not hold the independent system auditor role;
- the system administrator shall not hold the security officer and the independent system auditor role;
- the manager with overall responsibility for the IT system shall not hold the security officer and the independent system auditor role.

In addition to the aforementioned, the *Trust Service Provider* seeks the complete separation of trusted roles.

### 5.3 Personnel Controls

The *Trust Service Provider* takes care that its personnel policy, and its practices applicable to employing staff members intensify and support the reliability of the *Trust Service Provider's* operation. The objective of precautions applicable to personnel is to reduce the risk of human errors, theft, fraud and cases of misuse.

The *Trust Service Provider* addresses personnel security already during the hiring stage, including the conclusion of contracts, as well as their validation when they are being employed. In the case of all trusted roles, applicants have valid certificate of no criminal record at the time of the application. Every employee in a trusted role and external parties – who get in contact with the *Trust Service Provider's* services – shall sign a non-disclosure agreement.

At the same time, the *Trust Service Provider* ensures for its employees obtaining as well as further developing of common, general know-how along with the specialized professional knowledge necessary for performing the various jobs.

#### 5.3.1 Qualifications, Experience, and Clearance Requirements

As a hiring requirement, the *Trust Service Provider* requires at least intermediate education degree, but the *Trust Service Provider* continues to take care that employees receive appropriate training. Immediately after recruitment, the *Trust Service Provider* grants a training for its new employees, under the course of which they acquire the knowledge necessary to carry out the job. Registration officer can only be an employee, who finished a training course during which, he/she acquired the ability to recognize the ID cards acceptable by the *Trust Service Provider* (ID card, passport and driver's license). The *Trust Service Provider* usually supports the professional development of the employees, but it also expects employees to independently develop their skills in their respective fields. Some of the employees of the *Trust Service Provider* have the role to detect and gather the technical and business innovations and to organize, and share this knowledge with their colleagues.

Trusted roles can be held at the *Trust Service Provider* only by persons, who have no external influence and possess the necessary expertise validated by the *Trust Service Provider*.

The manager with overall responsibility for the IT system can only be a person who has:

- specialized degree (mathematics, physics college or university degree or a college/university degree acquired at an engineering department belonging to the technical field of science);
- at least three years of expertise in professional working experience related to information security.

#### 5.3.2 Background Check Procedures

The *Trust Service Provider* only hires employees for trusted or leading roles, who

- have a clean record and there's no proceeding in progress against them that may affect the impunity.
- are not subject to professional disqualifications prohibiting to exercise electronic signatures related services.

At the time of the appointment, shall the leading role holder *Trust Service Provider* employee with a statement, a trusted role holder employee with a certificate of good conduct less than 3 months old justify the clean criminal record.

The *Trust Service Provider* verifies the authenticity of the relevant information given in the applicant's CV during the hiring process.

### 5.3.3 Training Requirements

The *Trust Service Provider* trains the newly recruited employees, over the course of which they acquire

- basic PKI knowledge;
- the specifics and the way of handling the *Trust Service Provider's* IT system;
- the necessary special knowledge for fulfilling their scope of activities;
- processes and procedures defined in the public and inner regulations of the *Trust Service Provider*;
- the legal consequences of the individual activities;
- the applicable IT security regulations to the extent necessary to the specific scope of activities;
- the data protection rules.

The *Trust Service Provider* trains the employees concerned with registration about the dangers and risks related to the verification of the data to be indicated on the Certificate.

The employees concerned with registration take and pass an exam on the knowledge of the related requirements and procedures for data verification before their appointment, and this fact is documented by the *Trust Service Provider*.

Only employees having passed the training shall gain access to the he production IT system of the *Trust Service Provider*.

### 5.3.4 Retraining Frequency and Requirements

The *Trust Service Provider* ensures that the employees have the necessary knowledge continuously, so if needed, further or repeater type of training is held.

Further training is held if there's a change within the processes or the IT system of the *Trust Service Provider*.

The training is adequately documented, from what the syllabus and the scope of the participator employees can be clearly determined.

### 5.3.5 Job Rotation Frequency and Sequence

The *Trust Service Provider* does not apply mandatory rotation between individual work schedules.

### 5.3.6 Sanctions for Unauthorized Actions

The *Trust Service Provider* regulates the prosecution possibilities of the employees in an employment contract in case of failures, errors, accidental or intentional damage. If the employee – due to negligence or intentionally – violates their obligations, sanctions could be taken against him by the *Trust Service Provider*, which it sets out having regard to the offense and the consequences. The sanctions may include disciplinary proceedings, dismissal, revocation of appointment, criminal liability. Upon appointment every trusted role employee as part of the employment documents:

- gets written information about legal liabilities, rights, certification and management standards for the treatment of personal data,
- gets a job description that includes the concerning security tasks,
- signs a confidentiality agreement in which the related consequences non-compliant with safety measures, (criminal sanctions) can be found too.

All of these include the labor legislation or criminal consequences, that sanction the different discipline – job obligations – violation or breaking the law.

### 5.3.7 Independent Contractor Requirements

The *Trust Service Provider* only assigns trusted roles to its employees.

The *Trust Service Provider* chooses persons employed with engagement contract or subcontract to perform the other tasks, chosen if possible, from the list of previously qualified suppliers. The *Trust Service Provider* concludes a written contract before working with suppliers.

Each contracting party – before the start of the active work – signs a confidentiality statement in which he agrees that the business / corporate secrets learned later on will not be covered up to unauthorized persons, and will not be exploited in any other way. The confidentiality statement includes sanctions in case of violation. External employees employed under the contract are expected to have appropriate technical skills, and the *Trust Service Provider* does not hold any trainings for them.

### 5.3.8 Documentation Supplied to Personnel

The *Trust Service Provider* continuously provides for the employees the availability of the current documentation and regulations necessary to perform their roles.

Each employee in trusted role receives the following documents in writing:

- the organizational security regulations of the *Trust Service Provider*,
- the signed confidentiality agreement,
- personal job description,
- educational materials on the occasion of the planned or special training for the specific form of education.

All employees are informed in a written notice about any changes in the organizational safety regulations.

## 5.4 Audit Logging Procedures

In order to maintain a secure IT environment the *Trust Service Provider* implements and operates an event logger and control system covering its full IT system.

### 5.4.1 Types of Events Recorded

The *Trust Service Provider* logs every security-related event that can provide information on events, changes happened in the IT system or in its physical environment according to the generally accepted information security practice. In case of every log entry, it stores the following data:

- the time of the event;
- the type of the event;
- the success or failure of the implementation;
- the identification of the user or the system who/what triggered the event.

All of the essential event logs are available to the independent system auditors, who examine the compliance of the *Trust Service Provider's* operation.

The *Trust Service Provider* logs The following events at minimum:

- LOGGING:
  - the shutdown, restart of the logging system or some of its components;
  - the modification of any parameter of the logging settings, for example the frequency, alert threshold, and the event to be examined;
  - the modification or deletion of the stored logging data;
  - the activities performed because of the logging system's failure.
- SYSTEM LOGINS:
  - successful logins, unsuccessful login attempts for trusted roles;
  - in case of password based authentication:
    - \* the change of the number of permitted unsuccessful attempts;
    - \* reaching the limit of the permitted number of the unsuccessful login attempts in case of user login;
    - \* readmission of the user blocked because of the unsuccessful login attempts;
  - changing the authentication technique ( for example from password based to PKI based).
- KEY MANAGEMENT:
  - all events for the entire life cycle of service keys (key generation, loading, saving, etc.);
  - events related to generating, managing the user keys;
  - all events related to the management of private keys stored for any purpose by the *Trust Service Provider*.

- CERTIFICATE MANAGEMENT:
  - every event related to the issuance and the status change of the provider *Certificates*.
  - every request including *Certificate* issuance, re-key, key renewal and revocation;
  - events related to the request processing;
  - all control activities undertaken in relation to the issuance of *Certificates*, including the time of the telephone conversations related to the verification, the telephone number, the name of the called person and the acquired information;
  - refusal of the certificate applications;
  - *Certificate* issuance or status change.
- DATA FLOWS:
  - any kind of safety-critical data manually entered into the system;
  - safety-relevant data, messages received by the system;
- CA CONFIGURATION:
  - re-parameterization , any change of the settings of any component, of the CA;
  - user admission, deletion;
  - changing the user roles, rights;
  - changing the Certificate profile;
  - changing the CRL profile;
  - generation of a new CRL list;
  - generation of an OCSP response;
  - *Time Stamp* generation;
  - exceeding the required time accuracy threshold.
- HSM:
  - installing an HSM;
  - removing an HSM;
  - disposing, destructing an HSM;
  - delivering HSM;
  - clearing (resetting) an HSM;
  - uploading keys, certificates to the HSM.
- CONFIGURATION CHANGE:
  - hardware;
  - software;
  - operating system;
  - patch;



- PHYSICAL ACCESS, LOCATION SECURITY:
  - person entry to and exit from the security zone holding the CA components;
  - access to a CA system component;
  - a known or suspected breach of physical security;
  - firewall or router traffic.
- OPERATIONAL ANOMALIES:
  - system crash, hardware failure;
  - software failures;
  - software integrity validation error;
  - incorrect or wrongly addressed messages;
  - network attacks, attack attempts;
  - equipment failure;
  - electric power malfunctions;
  - uninterruptible power supply error;
  - an essential network service access error;
  - violation of the *Qualified Signature Certificate Policy* or the *Certification Practice Statement*;
  - deletion of the operating system clock.
- OTHER EVENTS:
  - appointment of a person to a security role;
  - operating system installation;
  - PKI application installation;
  - initiation of a system;
  - entry attempt to the PKI application;
  - password modification, setting attempt;
  - saving the inner database, and restore from a backup;
  - file operations ( for example creating, renaming, moving);
  - database access.

#### 5.4.2 Frequency of Audit Log Processing

The independent system auditors of the *Trust Service Provider* evaluates the generated log files every working day.

During the evaluation, the authenticity and integrity of the examined logs is ensured, the error messages in the logs are checked and if needed, document the differences and take measures to eliminate the cause of the deviation.

For the IT system evaluation, the *Trust Service Provider* uses automated evaluation tools too, that are used to monitor the resulting log entries according to preset criteria and, where necessary, alert the operational staff.

The fact of the investigation, the results of the investigation and the measures undertaken to avert deficiencies found are properly documented.

#### 5.4.3 Retention Period for Audit Log

Before the deletion from the on-line system, the logs are archived and their secure preservation is ensured by the *Trust Service Provider* for the amount of time defined in Section 5.5.2.

For that time period, the *Trust Service Provider* ensures the readability of archived data, and maintains the necessary software and hardware tools necessary for that.

#### 5.4.4 Protection of Audit Log

The *Trust Service Provider* protects the created logs for the required preservation time. During the whole preservation time, the following properties of the logs' data is ensured:

- protection against unauthorized disclosure: only authorized persons – primarily the independent system auditors – access the logs;
- availability: authorized persons are granted access to the logs;
- integrity: any data alteration, deletion in the log files and change in the order of the entries, etc. is prevented.

The *Trust Service Provider* provides the log records with qualified *Time Stamps*, and they are stored in a way excluding the seamless insertion and deletion of the log entries.

The log files are protected against accidental and malicious damage by backups. In case of log entries containing personal data, the *Trust Service Provider* makes sure of the confidential storage of the data. Only those individuals are entitled to access to the log entries, who absolutely need it for their work. The *Trust Service Provider* verifies the accesses in a secure way. The *Trust Service Provider* preserves the log files in a secure environment. Keeps copies of the files at the second operation site.

#### 5.4.5 Audit Log Backup Procedures

Daily log files are created from the continuously generated log entries during the operation in each system.

The daily log files are archived in two copies after the evaluation and stored physically apart from each other, at separate sites for the required time.

The exact process of backups shall be defined in the backup regulations of the *Trust Service Provider*.

#### 5.4.6 Audit Collection System (Internal vs External)

Each application automatically collects and sends the records to the logging system.

The logging functions start automatically at the time of the system launch and they are run continuously during the entire period of system operation.

In case of any anomaly in the automatic examiner and logging systems, the operation of the related areas are suspended by the *Trust Service Provider* until the incident is resolved.

#### 5.4.7 Notification to Event-causing Subject

The persons, organizations and applications that caused the error event are not always notified, but if necessary the *Trust Service Provider* involves them in the investigation of the event. The Clients affected by triggering the event has the duty to cooperate with the *Trust Service Provider* to explore the event.

#### 5.4.8 Vulnerability Assessments

Besides processing daily the log entries, the experts of the *Trust Service Provider* monthly review extraordinary events and perform analysis of vulnerability, based on which the *Trust Service Provider* if necessary, takes measures to increase the security of the system.

Every major event of significant deficiencies detected or in case of external threat, but at least once a year the experts of the *Trust Service Provider* perform a comprehensive vulnerability analysis using a mapping of potential internal and external threats that may result in unauthorized access, and may affect the *Certificate* issuing process, or allow modification of the data stored in the *Certificate*. Based on the results of the analysis, the Certification Authority if necessary, will further develop its processes and systems in order to increase the overall security of the service.

### 5.5 Records Archival

#### 5.5.1 Types of Records Archived

The *Trust Service Provider* is prepared to the proper secure long-term archiving of electronic and paper documents.

The *Trust Service Provider* archives the following types of information:

- every document related to the accreditation of the *Trust Service Provider*;
- all issued versions of the *Certificate Policies* and *Certification Practice Statements*;
- all issued versions of the Terms and Conditions;
- contracts related to the operation of the *Trust Service Provider*;
- all information related to the registration, including:
  - every document handed in with the *Certificate* application;
  - the identification data of the document(s) presented during the personal identification;

- service agreement(s);
- other subscriber disclaimers;
- the ID of the administrator assessing the registration application;
- conditions and the results of the examination of the application;
- all information related to the Certificate for the whole life-cycle;
- every electronic and paper based log entry.

### 5.5.2 Retention Period for Archive

The *Trust Service Provider* preserves the archived data for the time periods below:

- *Certification Practice Statement*: 10 years after the repeal;
- All electronic and / or paper-based information relating to Certificates for at least:
  - 10 years after the validity expiration of the Certificate;

### 5.5.3 Protection of Archive

The *Trust Service Provider* stores all archived data in two copies at locations physically apart from each other. Authentic paper or electronic copy is made in accordance with the applicable law from the only authentic paper based copy of the document available.

Each of the two locations fulfils the requirements for archiving security and other requirements.

During the preservation of the archived data, it is ensured that:

- their integrity is preserved;
- they are protected against unauthorized access ;
- they are available;
- they preserve authenticity.

The archived electronic data is provided with at least an advanced electronic signature or seal and a qualified *Time Stamp*.

### 5.5.4 Archive Backup Procedures

The *Trust Service Provider* stores the paper documents in a single original copy and makes an authentic electronic copy of the original in accordance with the relevant legislation. Electronic copies are stored according to the same rules as other protected electronic documents.

### 5.5.5 Requirements for Time-stamping of Records

Every electronic log entry is provided with a time sign, on which the system provided time is indicated at least to one second precision.

The *Trust Service Provider* ensures that in its service provider systems, the system clock is at maximum different from the reference time with 1 second.

The *Trust Service Provider* provides the daily log files with a qualified *Time Stamp*.

During the preservation of the archived data, if necessary (for example algorithm change expiration of the original *Time Stamp*) the authenticity of the data is ensured.

### 5.5.6 Archive Collection System (Internal or External)

The log entries are generated in the *Trust Service Provider's* protected computer system, and only the log files that are electronically signed and protected with qualified timestamps can leave it.

One original copy of the documents created during the service provision is stored and protected by the *Trust Service Provider* in an inner data storage operated by it.

### 5.5.7 Procedures to Obtain and Verify Archive Information

The *Trust Service Provider* creates the log files manually or automatically. In case of an automatic logging system, the certified log files are generated daily.

The archived files are protected from unauthorized access.

Controlled access to the archived data is only available to the eligible persons:

- *Clients* are eligible to see the data stored about them;
- in legal litigation in order to provide evidence the necessary data shall be provided.

## 5.6 CA Key Changeover

The *Trust Service Provider* ensures that the used *Certification Units* are continuously possessing a valid key and Certificate for their operation. For that purpose, sufficient time before the expiration of their Certificates, and the usage expiration of the keys related to them, it generates a new key pair for the *Certification Units* and inform its Clients in time. The new provider key is generated and managed according to this regulation.

If the *Trust Service Provider* changes any of its end-user *Certificates* issuer provider Certificate keys, it complies with the following requirements:

- it discloses the affected Certificates and public keys in accordance with the requirements defined in section 2.2 ;
- after the provider re-key the end-user *Certificates* to be issued will only be signed with the new provider keys;
- it preserves its old Certificates and public keys, and makes available the seal verification until all of the with the old provider key validity time expire.

## 5.7 Compromise and Disaster Recovery

In case of a disaster, the *Trust Service Provider* takes all necessary measures in order to minimize the damage resulting from the shortfall of the service, and it restores the services as quickly as possible.

Based on the assessment of the incident that occurred, it takes the necessary amendments, corrective measures to prevent future occurrence of the incident.

Once the problem resolved, the event is reported to the National Media and Infocommunications Authority, as the supervisory authority.

### 5.7.1 Incident and Compromise Handling Procedures

The *Trust Service Provider* has a business continuity plan.

The *Trust Service Provider* established and maintains a fully functional reserve system, which is at a safe distance from the primary location, geographically located at a different place and is independently capable of supplying the full range of services.

The *Trust Service Provider* annually tests the changeover to a reserve system and reviews its business continuity plans.

The *Trust Service Provider* has increased security tools and systems in order to minimize the software and hardware failures and data corruptions. The recoverability of services is guaranteed by the underpinning contracts and own backup tools of the *Trust Service Provider*.

### 5.7.2 Computing Resources, Software, and/or Data are Corrupted

The IT systems of the *Trust Service Provider* are built of reliable hardware and software components. The critical functions are implemented using redundant system elements so that in the event of an item failure they are able to operate further.

The *Trust Service Provider* makes a full daily backup of its databases and the generated log events.

The *Trust Service Provider* makes full system backups as frequently as necessary to be able to restore the full service in case of a disaster.

The business continuity plan of the *Trust Service Provider* includes accurate requirements for the tasks to be performed in case of critical system component failure.

Once the problem resolved and the integrity restored, the *Trust Service Provider* restarts its services as soon as possible.

During the restoration of services, the certificate status information service systems are top priority.

### 5.7.3 Entity Private Key Compromise Procedures

The emergency response plan of the *Trust Service Provider* has an action plan in place in case the provider private keys compromise. The action plan reveals the circumstances of the compromise besides the revocation of the provider public key and the Certificate accompanying, arranges the notification of all concerned parties, takes the necessary steps against the recurrence of the compromise and, if necessary, provides new key to the service unit and the compromise affected

end users. The *Trust Service Provider* immediately ceases to use that particular key in case of authentication unit key compromise.

In case another certificate authority also issued certificate for the given authentication unit - by law, contract or agreement between CAs based - and over or cross certified this certification unit of the *Trust Service Provider*, the *Trust Service Provider* promptly informs that other Certification Authority for that given key compromise and initiates the certificate revocation belonging to the key in question.

The *Trust Service Provider* publishes a notice about the provider public key revocation.

#### **5.7.4 Business Continuity Capabilities After a Disaster**

The tasks to be performed in case of service failure due to natural or other disaster, are defined in the *Trust Service Provider's* business continuity plan.

In the event of disaster, the regulations come into force, the damage control and the restoration of the services begins.

The secondary services site is placed so far away from the primary site that a probable disaster cannot reach both locations simultaneously.

The *Trust Service Provider* is obliged to notify the affected users as quickly as possible in the event of the disaster.

After the restoration of the services, the *Trust Service Provider* restores its devices damaged during the disaster and the original service security level as quickly as possible

#### **5.8 CA or RA Termination**

The *Trust Service Provider* notifies the end users and the National Media and Infocommunications Authority at least 60 days before the shutdown in case of the planned discontinuance of any of its services.

##### **The Certification Service and Certificate Status Service Shutdown**

At the same time with the notification about the service shutdown, the *Trust Service Provider* shuts down the following services:

- registration,
- Certificate creation,
- Certificate issuance,
- Certificate renewal,
- Certificate modification
- re-key.

The *Trust Service Provider* at least 20 days before the planned termination shuts down the following services:

- managing the Certificate revocation ,

At the same time of the termination, the *Trust Service Provider* shuts down the following services:

- information provision,
- *Certificate* publishing,
- *Certificate* revocation status publishing,
- Online Certificate Status Protocol.

Before a planned discontinuation, the *Trust Service Provider* engages in negotiations about the taking over of its services with other Certification Authorities whose rating is identical to its own. Under section 9.3 , it will hand over its records, including confidential user data, to such a Certification Authority or to the National Media and Infocommunications Authority come what may, along with its other services, depending on the outcome of the negotiations or terminates without handover.

The *Trust Service Provider* takes measures concerning the revocation of provider *Certificates* (and destroying private keys) during the 60 day period – depending on the outcome of the negotiations.

The *Trust Service Provider* informs the National Media and Infocommunications Authority about the final outcome of the negotiations. The *Trust Service Provider* is to inform its *Clients* by electronic mail, and *Relying Parties* by means of a publication on its website.

Pursuant to section 2.2., the *Trust Service Provider* will publish an announcement 5 days before its "Microsec e-Szigno Root CA", "Microsec e-Szigno Root CA 2009" and "e-Szigno OCSP CA" *Certificate* is revoked.

Upon terminating a service, the *Trust Service Provider* produces a full scope backup of its data contained in its IT system, affixing a qualified *Time Stamp* to it.

The *Trust Service Provider* provides for authorised *Relying Parties* the possibility to interpret the data appearing in its revoked and suspended *Certificates* records if necessary.

In order to make the handing over of its data to another service provider possible, the *Trust Service Provider* places data on media and in a format which the new service provider can receive or provides the new service provider with the opportunity to process data in the original format, and hands over the appropriate tools, documentation and know-how for this.

## 6 Technical Security Controls

The *Trust Service Provider* uses systems consisting of reliable, and safety technically assessed equipment for the provision of its services. The *Trust Service Provider* manages the cryptographic provider keys during their whole life-cycle within a *Hardware Security Module* that has appropriate Certification.

Both the *Trust Service Provider* and the system supplier and execution contractors have significant experience with certification service deployment and they use internationally recognized technology.



The *Trust Service Provider* continuously monitors the capacity needs, and with setting the trends it estimates the expected future capacity demands. It can arrange if needed an extension of the limited capacity, thereby providing the necessary processing and continuous availability of storage capacities.

## 6.1 Key Pair Generation and Installation

The *Trust Service Provider* makes sure that the generation and management of all the private keys generated by it – for itself, for some of its departments (for example *Certificate Repository, Registration Authority*) and for the *Subjects* – is secure and complies with the regulatory requirements in force and with industry standards.

### 6.1.1 Key Pair Generation

The *Trust Service Provider* uses key generation algorithms for the key-pair generation, which comply with the requirements set out in the following normatives:

- ETSI TS 119 312 [13];
- the current National Media and Infocommunications Authority algorithmic regulation issued pursuant to the authorization of the year 2015. Act CCXXII [5] 92. § (1) b) .

The *Trust Service Provider* in case of the generation of a key pair of its own ensures:

- The creation of the private key of the provider shall be carried out in a protected environment (see section 5.1 ), with two trusted role holder (see section 5.2.1) authorized person simultaneously, excluding the presence of other unauthorized persons.
- The creation of the provider private key is carried out in a device, that:
  - meets the requirements of ISO/IEC 19790 [15] , or
  - meets the requirements of FIPS 140-2 [24] level 3 or higher, or
  - meets the requirements of CEN 14167-2 [25] workshop agreement,
  - is a reliable system that is evaluated in accordance with MSZ/ISO/IEC 15408 [14] or equal security criteria valued to level 4 or higher guarantee level. The assessment shall be based on a security system design or on safety appropriations meeting the requirements of this document.
- The production of provider private key is performed based on a key generation script.
- For the generation of the provider root certification unit private key, an independent auditor is present or video recording is made of the event. The independent auditor certifies that the key generation occurred according to the script.

In case of the generation of the key pair generated for other parties (for example for its trusted role holder employees and for the *Subjects*) by the *Trust Service Provider*, it ensures that:

- The creation of the keys is carried out in a protected environment with exclusively trusted role holder persons present.

- In case of *Certificate Policies* requiring the use of a *Hardware Security Module* the *Trust Service Provider* generates the private key on the user's *Hardware Security Module* which makes the disclosure of the private key impossible.
- After the documented handover of the private key to the *Applicant* the *Trust Service Provider* destroys every copy of the handed over private key stored by it, in such a way that its restoration and usage becomes impossible. The *Trust Service Provider* ensures that the generated key pair is compliant with the requirements defined in Sections 6.1.5 and 6.1.6 , and the private key is not one of a known weak key pair.

In case of an *Applicant* generated key pair:

- the production of keys shall be done in a properly secure environment that is under the supervision of the *Applicant*;
- the *Applicant* shall ensure the proper protection of the generated private key;
- the *Trust Service Provider* shall ensure that the generated key pair is compliant with the requirements defined in Sections 6.1.5 and 6.1.6, and the public key is not one of a known weak key pair.

In case of provider root and intermediate *Certificate* creation the *Trust Service Provider* should make a key generation record demonstrating that the process has been conducted in accordance with the predetermined workflow that ensures the confidentiality and integrity of the generated keys. The record shall be signed by:

- in case of the generation of the provider root certification unit private key the trusted officer of the *Trust Service Provider* responsible for key management and as a witness a trusted person independent from the operation of the *Trust Service Provider* (eg. notary, auditor) who verify that the record corresponds to the performed process;
- in case of the generation of the provider intermediate certification unit private key the trusted officer of the *Trust Service Provider* responsible for key management who verifies that the record corresponds to the performed process.

### 6.1.2 Private Key Delivery to Subscriber

If the *Trust Service Provider* generated the the private key intended to be used during the website authentication, then the following requirements are met:

- Until the key handover, the *Trust Service Provider* stores the private keys generated by it for the *Subjects* and the activation data securely to prevent the key disclosure, copy, modification, damage and the usage by unauthorized persons.
- The *Trust Service Provider* shall ensure that the private keys and their activation data can only be taken over by the *Applicant*.
- The *Trust Service Provider* shall gain sufficient evidence of the handover of the private key to the *Applicant*, and the exact time of the handover.

- After the handover of the signer private key to *Applicant*, the *Trust Service Provider* shall not reserve any copy of the signer private key.

In case of *Certificate Policies* not requiring the use of a *Hardware Security Module*, in all cases the *Client* generates the private key, so it does not have to be delivered to the *Client*.

### 6.1.3 Public Key Delivery to Certificate Issuer

If the key pair is generated by the *Applicant*, the following provisions shall be complied with:

- the public key shall be sent to the *Trust Service Provider* in a manner that it can be unambiguously assigned to the *Applicant*;
- the *Certificate Application* process shall prove that the *Applicant* really owns the private key corresponding to the public key.

In case of end user keys generated by the *Applicant*, the *Applicant* sends the *Trust Service Provider* a PKCS#10 formatted request which he or she certifies with the private key belonging to the public key to be indicated on the *Certificate*. The PKCS#10 formatted request contains the public key generated by the *Applicant* and the *Subject* data to be indicated on the *Certificate*, so both requirements are met.

### 6.1.4 CA Public Key Delivery to Relying Parties

The *Trust Service Provider* discloses the status information related to the provider *Certificates* for the Relying Parties by the following methods:

- The *Trust Service Provider* publishes the full provider certificate hierarchy containing every root and intermediate provider certificate from which every current provider *Certificate* is downloadable (see at the Provider certificates point at the <https://e-szigno.hu/en/pki-services/ca-certificates.html> url ).
- The denomination of the root and intermediate certification units and the root *Certificates'* hash is in the 1.3.1 section of the *Certification Practice Statement*.
- The *Certificates* of the intermediate certification units are published on the certified Hungarian provider list [27] maintained and published by the National Media and Infocommunications Authority within the framework of the European common regulations [26]. The list contains every provider certificate (even the expired and revoked ones).
- For the online certificate status response signer responders the *Trust Service Provider* – according to the best international practice – issues *Certificates* with very short validity periods, thus eliminating the necessity of checking the revocation status of the *Certificates*. The current status of the *Certificates* is continuously available at the webpage of the *Trust Service Provider* at the <https://e-szigno.hu/en/pki-services/ca-certificates.html> address.

The *Trust Service Provider* discloses for the *Relying Parties* the status information related to the *Certificate* of the certification units operated by it, and of the units that take part in the online certificate status service by the following methods:

- The status information related to the *Certificate* of the root certification units is available on the webpage of the *Trust Service Provider*.
- The status change information of the intermediate (not root) certification units' certificates is disclosed on the revocation lists, on its webpage and within the confines of the online certificate status response service.
- For the responders signing the online certificate status responses the *Trust Service Provider* – according to the best international practices – issues a *Certificate* with very short validity period to eliminate the necessity of checking the *Certificate* revocation status. The *Trust Service Provider* guarantees that in case of key compromise or other problem no new *Certificate* will be issued for the old private key signing the OCSP responses. The *Trust Service Provider* issues the OCSP response *Certificates* for new, secure private keys.

Regarding the disclosure methods of the status information, also see Section 4.10.

### 6.1.5 Key Sizes

The *Trust Service Provider* uses algorithms and minimum key sizes, which comply with the requirements set out in the following norms:

- ETSI TS 119 312 [13];
- CABF Baseline Requirements recommendation [23];
- the current National Media and Infocommunications Authority algorithmic regulation issued pursuant to the authorization of the year 2015. Act CCXXII [5] 92. § (1) b).

The *Trust Service Provider* uses 2048 bit RSA keys in every currently active root and intermediate provider *Certificate* and even in the *Certificates* of the *Time-Stamping Units* and the OCSP responders.

### 6.1.6 Public Key Parameters Generation and Quality Checking

The *Trust Service Provider* generates the keys according to the description of the section 6.1.1.

#### Hardware/Software Key Generation

The generation of the *Trust Service Provider* keys used for *Certificate* issuance is done with a *Hardware Security Module*, which has FIPS 140-2 Level 3 certifications. The denomination of each device is in the 8. section.

The other keys – necessary for the internal operation of the certification Authority – keys are generated by the *Trust Service Provider* on a *Hardware Security Module* or on a computer operating in a secure environment.

### Verification of Compliance of Parameters

The compliance of the key generation parameters is verified by the system from two points of view:

- checking the conformity of the random number generation used for the parameters (whether the generation is sufficiently statistically random),
- checking the fulfilment of the requirements for parameters.

Every *Hardware Security Module* used in the system is able to statistically test the uniformity and independence of the bit sequence it generated. The modules enable the invocation of the tests through a standard interface.

#### 6.1.7 Key Usage Purposes (as per X.509 v3 Key Usage Field)

The *Trust Service Provider* root certification unit private key may only be used for the following purposes:

- issuance of the self-signed *Certificate* of the root certification unit itself ,
- to sign the intermediate certification units' *Certificates*,
- to sign the OCSP responder *Certificate*,
- to sign the *Time-Stamping Unit Certificate*,
- to sign CRLs.

The private key of the *Trust Service Provider's* intermediate certification units – as well as the private key issued to the intermediate certification unit of other organizations – can only be used for the following purposes:

- to sign the intermediate certification units' *Certificates*,
- to sign the end user *Certificate*,
- to sign the *Time-Stamping Unit Certificate*,
- to sign the OCSP responder *Certificate*,
- to sign CRLs.

The *Trust Service Provider* includes the Key Usage extensions in the end-user certificates that define the scope of the Certificate usage and in the X.509v3 [22] compatible applications technically restrict the usage of the Certificates. The requirements set out for the value of the field are in Section 7.1.2.

The private key of the *Applicant* belonging to its *Certificate* may only be used for webserver authentication, and any other usage is not permitted.

## 6.2 Private Key Protection and Cryptographic Module Engineering Controls

The *Trust Service Provider* ensures the secure management of the private keys held by it and prevents the private key disclosure, copy, deletion, modification and unauthorized usage. The *Trust Service Provider* may only preserve the private keys as long as the provision of the service definitely requires.

The *Trust Service Provider* private keys used for the certification organization *Certificate* and issuance are stored at a physically secure location, in a secure *Hardware Security Module*.

In case of *Certificates* issued according to *Certificate Policies* not requiring the use of a *Qualified Electronic Signature Creation Device* the *Trust Service Provider* does not issue private keys to the *Subject* beforehand, eliminating the need to ensure the preservation of the end-user private keys.

The *Trust Service Provider* deletes the signing private keys stored on the *Hardware Security Modules* which are out of order in as defined in the device's manual so that it is virtually impossible to restore the keys.

### 6.2.1 Cryptographic Module Standards and Controls

The systems of the *Trust Service Provider* issuing *Certificate*, signing OCSF responses and CRL lists store the private keys used for the electronic signature creation in such secure hardware devices that are compliant with the following:

- the requirements of ISO/IEC 19790 [15], or
- the requirements of FIPS 140-2 [24] 3, or the requirements of a higher level, or
- the requirements of CEN 14167-2 [25] task force agreement, or
- they are such reliable systems that are evaluated at a guarantee level 4 or higher according to MSZ/ISO/IEC 15408 [14] or an equivalent security criteria system. The assessment either shall be based on the appropriate security system plan that meets the requirements of the present document, or on security appropriations.

The denomination of the used *Hardware Security Module* is described in section 8.

The *Trust Service Provider* provider keys are only stored in coded forms outside of the *Hardware Security Module*. For coding only those algorithms and key parameters are used by the current order of the National Media and Infocommunications Authority that was issued according to the year 2015. Act CCXXII [5] 92. § (1) b) that are expected to be able to withstand the cryptographic attacks during the entire lifetime of the keys.

The *Trust Service Provider* provider private keys are stored in a physically secure site even in an encrypted form, in the safe of the *Data Centre*, where they are only accessible to authorized people.

In case of the weakening of cryptographic algorithms and key parameters, the *Trust Service Provider* destroys the coded keys or recodes them again using algorithm and key parameters that ensure higher protection.

### 6.2.2 Private Key (N out of M) Multi-Person Control

The *Trust Service Provider* implements the "n out of m" at the activation of the private key related key management functions. The parameters are determined so that the simultaneous presence of at least two; trusted role holder employees is needed for the critical operations carried out with its provider private keys.

### 6.2.3 Private Key Escrow

The *Trust Service Provider* does not escrow its own provider private key.

The *Trust Service Provider* does not provide for the website authentication private keys any escrow service, under no circumstance does it store their copy, multiple usage.

### 6.2.4 Private Key Backup

The *Trust Service Provider* makes security copies of its provider private keys, before putting the private key into service as described in section 6.2.1. in a protected environment, in the simultaneous presence of at least two people holding trusted roles, with the exclusion of other people. During the backup, the private key leaves the module in an encrypted form, and this encrypted key can be loaded into another module. Both the backup and the restore can only be performed by protection mechanisms described in section 6.2.2..

The *Trust Service Provider* stores the backup copy in duplicate, and at least one copy of those is stored at a different place from the service provider location.

The same strict safety standards are applied to the management and preservation of backups as for the operation of the production system.

The *Trust Service Provider* does not make any copy of the website authentication private keys.

### 6.2.5 Private Key Archival

The *Trust Service Provider* does not archive its private keys and the end-user private keys.

### 6.2.6 Private Key Transfer Into or From a Cryptographic Module

All of the provider private keys of the *Trust Service Provider* is created in a *Hardware Security Module* that meets the requirements.

The private keys do not exist in an open form outside of the *Hardware Security Module*.

The *Trust Service Provider* only exports the private key from the *Hardware Security Module* for the purpose of making a secure copy.

The export and loading of the provider private keys is performed according to section 6.2.2.

### 6.2.7 Private Key Storage on Cryptographic Module

The *Trust Service Provider* keeps its private keys used for service provision in *Hardware Security Modules* according to section 6.2.1.

Private keys are stored and used in the *Hardware Security Module* as specified in the certification of the device with full compliance with the related operating instructions.

### 6.2.8 Method of Activating Private Key

The *Trust Service Provider* keeps its provider private keys in a secure *Hardware Security Module* and complies with its user guide and the requirements outlined in the certification documents. The *Hardware Security Module* can only be activated by the corresponding operator cards and the private keys within the *Hardware Security Module* can not be used before activating the module. The *Trust Service Provider* keeps the operator cards in a safe environment and those cards can be only reached by entitled employees of the *Trust Service Provider*.

The *Trust Service Provider* ensures that signatures can only be created with the private key of the root unit certificate in case of commands issued directly by the trust official duly authorized to do so.

In case of the end-user private keys generated by the *Trust Service Provider* it ensures that the private keys and the private key activation data are generated and managed in a properly secure way that excludes the possibility of the unauthorized usage of the private key.

In case of *Applicant* generated private key the protection of the private key is the *Applicant's* full responsibility.

### 6.2.9 Method of Deactivating Private Key

#### Provider Private Keys

The private key used by the *Trust Service Provider*, and managed by the cryptographic devices becomes deactivated if (in a regular or irregular way) the device is removed from active status. This can happen in the following cases:

- the user deactivates the key,
- the power supply of the device is interrupted (switched off or power supply problem),
- the device enters an error state.

The private key deactivated like this can not be used until the module is in active state again.

#### End-User Private Keys

In case of *Certificate Policies* not requiring the use of a *Hardware Security Module* the proper usage of the private keys is the responsibility of the *Applicant*.

### 6.2.10 Method of Destroying Private Key

#### Provider Private Keys

The discarded, expired or compromised *Trust Service Provider's* private keys are destroyed in a way that makes further use of the private keys impossible.



The *Trust Service Provider* destroys the provider private keys stored in the secure *Hardware Security Module* of the certification organization according to the procedures, requirements defined in the user guide and in the certification documents of the used *Hardware Security Module*, in the simultaneous presence of two *Trust Service Provider* employees (an infrastructure administrator and a security officer) with the exclusion of other persons.

### **End-User Private Keys**

In case of *Certificate Policies* not requiring the use of a *Hardware Security Module* the proper destruction of the private keys is the responsibility of the *Applicant*.

The discarded website authentication private keys of the end-users are recommended to be destroyed.

#### **6.2.11 Cryptographic Module Rating**

According to the requirements of Section 6.2.1 every provider private key of the *Trust Service Provider* is stored in a cryptographic module that

- has a certification according to ISO/IEC 19790 [15], or
- has a certification according to FIPS 140-2 Level 3 [24], or
- has a Common Criteria based certificate attesting compliance with the requirements of the CEN 14167-2 [25] workshop agreement, or
- has a verification issued for this purpose by an independent certification body eligible for evaluating electronic signature products, registered by the National Media and Infocommunications Authority, or in a member state of the European Union

### **6.3 Other Aspects of Key Pair Management**

#### **6.3.1 Public Key Archival**

The *Trust Service Provider* archives every *Certificate* its certification organization issued for ten years after the end of the validity period or until until the completion of the incurred dispute related to the *Certificate*.

For the same time period, the *Trust Service Provider* preserves devices, with which the content of the *Certificate* can be established.

#### **6.3.2 Certificate Operational Periods and Key Pair Usage Periods**

##### **The Keys and Certificates of the Root Certification Units**

The validity period of the *Trust Service Provider* root certification unit certificates and the private keys belonging to them shall not exceed the amount of time until which the used cryptographic algorithms can be used safely according to the algorithmic decision of the National Media and Infocommunications Authority.

The validity period of the *Trust Service Provider* root certification unit certificates and the private keys:

- the key of the "Microsec e-Szigno Root CA" root certification unit is valid until 2017.04.06;
- the key of the "e-Szigno OCSP CA" root certification unit is valid until 2017.04.26;
- the key of the "Microsec e-Szigno Root CA 2009" root certification unit is valid until 2029.12.30.

### **The Keys and Certificates of the Intermediate Certification Units**

The validity period of the *Trust Service Provider* intermediate certification unit certificates and the private keys belonging to them are:

- shall not exceed the amount of time until which the used cryptographic algorithms can be used safely according to the algorithmic decision of the National Media and Infocommunications Authority;
- shall not exceed the validity period of the issuer root or intermediate provider *Certificate* that issued the intermediate provider *Certificate*.

The intermediate (not root) certification unit keys of the *Trust Service Provider* are valid until the expiration date of the *Certificates* belonging to them.

### **End-User Certificates**

The validity period of the end user *Certificates* issued by the *Trust Service Provider*

- is maximum 3 years from issuance;
- shall not exceed the amount of time until which the used cryptographic algorithms can be used safely according to the algorithmic decision of the National Media and Infocommunications Authority;
- shall not exceed the expiration date of the provider *Certificate* that issued the *Certificate*.

During the Certificate renewal the *Trust Service Provider* may issue the new *Certificate* for the same end-user private key.

Both the service provider and the end-user key validity period is affected, if the National Media and Infocommunications Authority issues a new algorithm decree, according to which the used cryptographic algorithm or key parameter is not secure to the end of the planned usage period. If this happens, the *Trust Service Provider* revokes the related *Certificates*.

## **6.4 Activation Data**

### **6.4.1 Activation Data Generation and Installation**

The *Trust Service Provider's* private keys are protected in accordance with the procedures, requirements defined in the used *Hardware Security Module* user guide and the certification documents.

In case of password based activation data usage, the passwords are sufficiently complex in order to ensure the required level of protection.

In case of private keys created for and handed over to the *Applicant* via software by the *Trust Service Provider* the *Trust Service Provider* creates the activation data and assigns them to the private key in a physically secure environment, with an adequate quality random number generator;

The creation and installation of the activation data of the *Applicant* created private keys is the duty of the *Applicant*.

#### 6.4.2 Activation Data Protection

The employees of the *Trust Service Provider* manage the private key activation devices and the activation data securely, protect them using technical and organizational measures and passwords are stored in encrypted form only.

In case of software private keys generated for the *Applicant*:

- the *Trust Service Provider* only records the activation data for the purpose of delivering them to the *Applicant*;
- the *Trust Service Provider* distributes the activation data to the *Applicant* using a secure method.

The protection of the activation data of the private keys created by the *Applicant*, is the duty and responsibility of the *Applicant*.

#### 6.4.3 Other Aspects of Activation Data

No stipulation.

### 6.5 Computer Security Controls

#### 6.5.1 Specific Computer Security Technical Requirements

During the configuration and operation of its IT system of the *Trust Service Provider* ensures the compliance with the following requirements:

- the user identity is verified with two-factor authentication controls by using VPN certificates stored on the card before granting access to the system or the application;
- roles are assigned to users and it ensures that all users only have permissions appropriate for his or her roles;
- a log entry is created for every transaction, and the log entries are archived;
- for the security-critical processes it is ensured that the internal network domains of the *Trust Service Provider* are sufficiently protected from unauthorized access;
- proper procedures are implemented to ensure service recovery after loss of key or system failure.

### 6.5.2 Computer Security Rating

Microsec lays much emphasis on customer complacency. In order to keep up the high quality services, the *Trust Service Provider* operates a quality management system according to the ISO 9001 standard since 23. January 2002. Compliance with this standard is certified by Lloyd's Register Quality Assurance.

Microsec pays close attention to the security of the systems it operates, therefore, in the main areas of its activity it operates a ISO/IEC 27001 compliant information security management system (previously BS 7799) since 19. may 2003. Compliance with this standard is certified by Lloyd's Register Quality Assurance.

## 6.6 Life Cycle Technical Controls

### 6.6.1 System Development Controls

The *Trust Service Provider* only uses applications and devices in its production IT system that:

- are commercial boxed software, designed and developed by a documented design methodology, or;
- custom hardware and software solutions developed by a reliable party for the *Trust Service Provider* during which design structured development methods and controlled development environment were used, or;
- open source software which comply with the security requirements and their adequacy is ensured by software verification and structured development and life-cycle management.

Procurement of IT tools is performed in a way that excludes changes to the hardware and software components using reliable, regularly qualified suppliers.

The hardware and software components applied for the provision of services are not used for other purposes by the *Trust Service Provider*.

The *Trust Service Provider* prevents the malicious software from entering into the devices used for certification services with appropriate security measures.

The hardware and software components are checked regularly for malicious software prior the first usage, and subsequently.

The *Trust Service Provider* acts with the same carefulness in case of program update purchases as at the acquisition of the first version.

The *Trust Service Provider* employs reliable, adequately trained staff over the course of installing software and hardware.

The *Trust Service Provider* only installs softwares to its service provider IT equipment necessary for the purpose of service provision.

The *Trust Service Provider* has a version control system where every change of the IT system is documented.

The *Trust Service Provider* operates automatic monitoring system to record all unauthorized changes, which records all changes in every file and in case of changes in the monitored files it generates a log entry or sends an alert to the system operators.

### 6.6.2 Security Management Controls

The *Trust Service Provider* implements processes for documenting, operating, verifying, monitoring and maintaining the systems used in the service including their modification and further development. The version control system detects any kind of unauthorized changes, data entry that affects the system, the firewall, the routers, programs and other components used in the service. Installing the program used in the service the *Trust Service Provider* ensures that the program to be installed is the proper version and that it is free from any unauthorized modification. The *Trust Service Provider* regularly checks the integrity of the software in its system used in the service.

Each *Hardware Security Module* applied by the *Trust Service Provider* has been verified, tested and evaluated. The *Trust Service Provider* verifies the integrity of the modules:

- following the acquisition of the devices during the takeover,
- immediately before the first usage,
- regularly during operation.

The *Trust Service Provider* deletes the provider keys from the *Hardware Security Modules* permanently or temporarily withdrawn from use.

The *Trust Service Provider* stores the unused *Hardware Security Modules* at a physically protected location.

### 6.6.3 Life Cycle Security Controls

The *Trust Service Provider* ensures the protection of the used *Hardware Security Modules* during their whole life cycle.

During the operation of the IT services, devices and operating systems used for the provision of the services the *Trust Service Provider* taking into account the safety aspects of the equipment life cycle.

- it uses in its system a *Hardware Security Module* which has the right certification;
- at the reception of the *Hardware Security Module*, during the qualitative takeover it verifies that the protection of the *Hardware Security Modules* against tampering was ensured during transportation;
- it stores the *Hardware Security Module* at a secure location, and the protection of the *Hardware Security Module* against tampering is ensured during storage;
- during the operation it continuously complies with the requirements of the *Hardware Security Module* appropriation of security, user guide and the certification report;
- it deletes the private keys stored in the discarded *Hardware Security Modules* in a way that it is virtually impossible to restore the keys.

## 6.7 Network Security Controls

The *Trust Service Provider* keeps its IT system configuration under strict control, and it documents every change including the smallest modification, development, software update too. The *Trust Service Provider* implements proper procedures for the detection of any hardware or software change, system installation, and maintenance occurred on the IT system. The *Trust Service Provider* checks the authenticity and integrity of every software component at their first loading. The *Trust Service Provider* applies proper network security measures for example:

- disables unused network ports and services ;
- only runs network applications unconditionally necessary for the proper operation of the IT system .

## 6.8 Time-stamping

For the protection of the integrity of the log files and other electronic files to be archived the *Trust Service Provider* uses qualified electronic *Time Stamps* issued by the e-Szignó Certification Authority.

# 7 Certificate, CRL, and OCSP Profiles

## 7.1 Certificate Profile

The end-user *Certificates* issued by the *Trust Service Provider* and the provider certification unit (root and intermediate) *Certificates* used during the service comply with the following recommendations and requirements:

- ITU X.509 Information technology - Open Systems Interconnection - The Directory: Public-key and attribute certificate frameworks [22]
- RFC 5280 [19]
- RFC 6818 [20]
- ETSI EN 319 412-1 [9]
- ETSI EN 319 412-2 [10] in case of *Certificates* issued to natural persons
- ETSI EN 319 412-3 [11] in case of *Certificates* issued to legal persons
- ETSI EN 319 412-4 [12]

### 7.1.1 Version Number(s)

The provider certification unit (root and intermediate) *Certificates* used by the *Trust Service Provider* and the end-user *Certificates* issued by the *Trust Service Provider* are "v3" *Certificates* according to the X.509 specification [22].

The provider certification unit (root and intermediate) *Certificates* used by the *Trust Service Provider* and the end-user *Certificates* issued by the *Trust Service Provider* have the following basic fields:

- **Version**  
The *Certificate* complies with "v3" *Certificates* according to the X.509 specification, so the value "2" is in this field. [19]
- **Serial Number**  
The unique identifier generated by the *Certificate* issuer certification unit.  
In case of the end-user *Certificates* the "Serial Number" field contains a random number with at least 8 byte entropy.
- **Algorithm Identifier**  
The identifier (OID) of the algorithm set used for the creation of the electronic seal certifying the *Certificate*.  
The *Trust Service Provider* uses the following algorithm:
  - "sha256WithRSAEncryption" (1.2.840.113549.1.1.11),
- **Signature**  
Electronic seal made by the *Trust Service Provider* certifying the *Certificate*, that has been created with an Algorithm set defined in the "Algorithm Identifier" field.
- **Issuer**  
The unique name of the *Certificate* issuer *Certification Unit* according to the X.501 name format.
- **Valid From & Valid To**  
The beginning and the end of the validity period of the *Certificate*. The time is recorded according to UTC and compliant with RFC 5280 encoding.
- **Subject**  
The unique name of the *Subject* according to the X.501 name format. Always filled out.
- **Subject Public Key Algorithm Identifier**

The *Trust Service Provider* supports the RSA algorithm in the end-user *Certificates*. The length of the public key is at least 1024 bit.

The value to be included in this field:

- "rsaEncryption" (1.2.840.113549.1.1.1)

- **Subject Public Key Value**  
The public key of the *Subject*.
- **Issuer Unique Identifier**  
Not filled out.
- **Subject Unique Identifier**  
Not filled out.

### 7.1.2 Certificate Extensions

the *Trust Service Provider* only uses the following certificate extensions according to the X.509 specification [22]:

#### Certificate of the Root Certification Unit

- Certificate Policies – not critical  
OID: 2.5.29.32  
This field is not indicated.
- Authority Key Identifier – not critical  
OID: 2.5.29.35  
The 40 character long unique identifier of the provider key used for the electronic seal certifying the *Certificate*.  
The field value: the SHA-1 hash of the provider public key.  
In case of the self-signed root certification unit certificate the value is identical with the value of the *Subject* key identifier field.
- Subject Key Identifier – not critical  
OID: 2.5.29.14  
The 40 character long unique identifier of the *Subject* public key. The field value: the SHA-1 hash of the public key.
- Subject Alternative Names – not critical  
OID: 2.5.29.17  
See Section: 3.1.1.  
The central e-mail address of the *Trust Service Provider* can be in this field in the *Certificate* of the root certification unit.
- Basic Constraints – critical  
OID: 2.5.29.19  
The specification whether the *Certificate* has been issued to a certification unit.  
The extension is required and its value is: CA = "TRUE".  
The "pathLenConstraint" field can be present in the *Certificate*.
- Key Usage – critical  
OID: 2.5.29.15  
The scope definition of the approved key usage.  
The field is mandatory and the value shall be: "keyCertSign", "cRLSign".
- Extended Key Usage – not critical  
The further scope definition of the approved key usage. It is not present.

The above fields are always filled out. There is not any more *Certificate* extensions.



### Certificate of the Intermediate Certification Unit

- Certificate Policies – not critical  
OID: 2.5.29.32  
This field contains the identifier of the valid certification policy (see section 1.2.1.) at the time of the intermediate certification unit *Certificate* issuance and usage, and other information on the other uses of the *Certificate*.  
Filling in is mandatory for this field, and it shall not be critical.  
In case of *Certificates* issued to the intermediate certification units of the *Trust Service Provider*, the "anyPolicy" Identifier can be present in this field.  
The reference to the related *Certification Practice Statement* can be given in this field. In case of certification unit *Certificates* issued to other *Certification Authority*, only that identifier can be in this field, which relates to a *Certificate Policy* which complies to the *Certificate Policy* implemented by the issuer *Certification Authority*, and there can be no "anyPolicy" Identifier.
- Authority Key Identifier – not critical  
OID: 2.5.29.35  
The 40 character long unique identifier of the provider key used for the electronic seal certifying the *Certificate*.  
The field value: the SHA-1 hash of the provider public key.
- Subject Key Identifier – not critical  
OID: 2.5.29.14  
The 40 character long unique identifier of the *Subject* public key. The field value: the SHA-1 hash of the public key.
- Subject Alternative Names – not critical  
OID: 2.5.29.17  
The central e-mail address of the *Trust Service Provider* can be in this field in the *Certificate* of the intermediate certification unit.
- Basic Constraints – critical  
OID: 2.5.29.19  
The specification whether the *Certificate* has been issued to a certification unit.  
The extension is required and its value is: CA = "TRUE".  
The "pathLenConstraint" field may be present in the *Certificate*.
- Key Usage – critical  
OID: 2.5.29.15  
The scope definition of the approved key usage.  
The field is mandatory and the value shall be: "keyCertSign", "cRLSign".
- Extended Key Usage – not critical  
The further scope definition of the approved key usage. It is not present.

- CRL Distribution Points – not critical  
OID: 2.5.29.31  
The field contains the CRL availability through http and/or ldap protocol. Mandatory to fill.
- Authority Information Access – not critical  
OID: 1.3.6.1.5.5.7.1.1  
The definition of the other services related to the usage of the *Certificate* provided by the *Trust Service Provider*.  
Mandatory, and the field contains the following data:
  - For the purpose of the fast and reliable verification of the current *Certificate* revocation status, the *Trust Service Provider* provides online certificate status service. The availability of this service is indicated here.
  - To facilitate the certificate chain building the *Trust Service Provider* gives the access path through http or ldap protocol of the *Certificate* of the *Certificate* issuer certification unit.

The above fields are always filled out. There is not any more *Certificate* extensions.

### End-User Certificate

- *Certificate Policies* – not critical  
OID: 2.5.29.32  
This field contains the denomination of the valid certification policy (see Section 1.2.1) at the time of the *Certificate* issuance and other information on the other uses of the *Certificate*.  
In case of end-user certificates, the *Trust Service Provider* fills in this field in all cases by providing the following data:
  - the identifier of the *Certificate Policy* (OID);
  - the availability of the *Certification Practice Statement*;
  - the textual warning in English and Hungarian from which it can be concluded that it is a II. or III. certification class certificate, namely personal appearance did or did not happen at the registration, and the Subject of the *Certificate* is a natural person .
  - The identifier specified by ETSI EN 319 411-1 (OID); the policy with which the *Certificate* complies with.

In all cases of end-user certificates at least one *Certificate Policy* is indicated according to what the *Trust Service Provider* issued the *Certificate* and according to what it later acts on. At least one such *Certificate Policy* identifier (OID) and the related *Certification Practice Statement* availability (URL) is indicated on the *Certificates* issued by the *Trust Service Provider*.

The end-user *Certificates* that do not contain the "Certificate Policies" field shall be considered test certificates. The test *Certificate* can only be used for testing purposes, and they shall be declined in case of real transactions.

The reference to the related Certification Practice Statement may be given in this field.

- Authority Key Identifier – not critical  
OID: 2.5.29.35  
The 40 character long unique identifier of the provider key used for the electronic seal certifying the *Certificate*.  
The field value: the SHA-1 hash of the provider public key.
- Subject Key Identifier – not critical  
OID: 2.5.29.14  
The 40 character long unique identifier of the *Subject* public key. The field value: the SHA-1 hash of the public key.
- Subject Alternative Names – not critical  
OID: 2.5.29.17  
See section: 3.1.1.
- Basic Constraints – critical  
OID: 2.5.29.19  
The specification whether the *Certificate* has been issued to a certification unit.  
The default value of the extension is: CA = "FALSE", so this field is not present in the end-user *Certificates*.  
The "pathLenConstraint" field is not present in the end-user *Certificates*.
- Key Usage – critical  
OID: 2.5.29.15  
The scope definition of the approved key usage.  
In the webserver *Certificates* the mandatory and exclusively admissible values: "digitalSignature", "keyEncipherment", "keyAgreement".
- Extended Key Usage – not critical  
The further scope definition of the approved key usage.  
In the *Website Authentication Certificates* the set value is: "serverAuth (1.3.6.1.5.5.7.3.1)"
- CRL Distribution Points – not critical  
OID: 2.5.29.31  
The field contains the CRL availability relevant to the Certificate through http and/or ldap protocol. The CRL availability related to the *Certificate* is present here (url).
- Authority Information Access – not critical  
OID: 1.3.6.1.5.5.7.1.1  
The definition of the other services related to the usage of the *Certificate* provided by the *Trust Service Provider*.  
In case of end-user certificate certificates the field contains the following data:
  - For the purpose of the fast and reliable verification of the current *Certificate* revocation status, the *Trust Service Provider* provides online certificate status service. The availability of this service is indicated here.
  - To facilitate the certificate chain building the *Trust Service Provider* gives the access path through http protocol of the *Certificate* of the *Certificate* issuer certification unit.

- Qualified *Certificate* Statements – not critical

OID: 1.3.6.1.5.5.7.1.3

The field is intended for the indication of statements related to the qualified *Certificates*, but it has a field, that can be used in case of a non-qualified *Certificate* too.

The QCType field may be filled according to the usage purpose. It is indicated in the field that the *Certificate* was issued for website authentication purposes (the value of the field is 'id-etsi-qct-web').

The above fields are always filled out according to the given rules. There is no more filled out *Certificate* extensions.

### 7.1.3 Algorithm Object Identifiers

The denomination of the algorithm that has been used to certify the *Certificate*. The following algorithms are used by the *Certification Authority* for sealing the end-user *Certificates*:

- "sha256WithRSAEncryption" (1.2.840.113549.1.1.11)

### 7.1.4 Name Forms

The *Trust Service Provider* uses a distinctive name – composed of attributes defined in the standards RFC 5280 [19], ETSI EN 319 412-2 [10], ETSI EN 319 412-3 [11] and ETSI EN 319 412-4 [12] – for the Subject identification in the *Certificates* issued based on this *Certification Practice Statement*.

The *Certificate* contains the globally unique identifier of the *Subject* (OID), filled out as defined in Section 3.1.1.

The value in the "Issuer DN" field of the *Certificate* is identical to the value in the "Subject DN" field of the issuer *Certificate*.

### 7.1.5 Name Constraints

The *Trust Service Provider* does not use name constraints with the use of the "nameConstraints" field.

### 7.1.6 Certificate Policy Object Identifier

The *Trust Service Provider* includes the not critical (*Certificate Policy*) extension in the *Certificates* according to the requirements of the Section 7.1.2..

### 7.1.7 Usage of Policy Constraints Extension

No stipulation.

### 7.1.8 Policy Qualifiers Syntax and Semantics

The *Trust Service Provider* can put short information related to the *Certificate* usage into the *Certificate Policy* extension Policy Qualifier field. The field contains the on-line availability of the *Certification Practice Statement* (URI).

### 7.1.9 Processing Semantics for Critical Certificate Policy Extension

No stipulation.

## 7.2 CRL Profile

### 7.2.1 Version Number(s)

The *Certification Authority* issues version "v2" certificate revocation lists according to the RFC 5280 [19] specification.

### 7.2.2 CRL and CRL Entry Extensions

The revocation lists issued by the *Certification Authority* shall compulsorily include the following fields:

- Version  
The value of the field is compulsorily "1".
- Signature Algorithm Identifier  
The identifier (OID) of the algorithm set used for creating the electronic seal certifying the revocation list. The name and ID of the algorithm sets used by the *Trust Service Provider*:
  - "sha256WithRSAEncryption" (1.2.840.113549.1.1.11).
- Signature  
The electronic seal of *Certification Authority* certifying the revocation list. The given certification unit certifies the revocation list with its key used for signing the *Certificates*.
- Issuer  
The unique identifier of the revocation list issuer certification unit.
- This Update  
The date of the entry into force of the revocation list. Value according to UTC with encoding according to RFC 5280 [19]. In case of the revocation lists issued by the *Certification Authority* this is the same as the issuance time.
- Next Update  
The issuance time of the next revocation list (see Section 4.10.). Value according to UTC with encoding according to RFC 5280 [19].
- Revoked *Certificates*  
The list of revoked *Certificates* with the serial number of the *Certificate* and with the revocation time.

The revocation list extensions to be filled in by *Certification Authority* as mandatory:

- CRL number – not critical  
The consecutive serial numbers of the revocation lists are in this field.

This extension may be used by the *Certification Authority*:

- expiredCertsOnCRL – not critical  
The *Certification Authority* indicates with a standard notation according to the X.509 specification that it does not remove the expired *Certificates* from the CRL. (See Section 4.10.)

The certificate revocation list entry extensions that may be used by the *Certification Authority*:

- Reason Code – not critical  
The reason of the revocation is in this field.
- Invalidity Date – not critical  
The time when the private key became compromised can be in this field.  
The *Certification Authority* need not fill this field.
- Hold Instruction – not critical  
The management of the suspended certificate can be in this field.  
The *Certification Authority* need not fill this field.

The *Certification Authority* is not obliged to fill out the extensions.

### 7.3 OCSP Profile

The *Trust Service Provider* operates an online certificate status service according to the RFC 2560 [16] and RFC 6960 [21] standard.

#### 7.3.1 Version Number(s)

The *Trust Service Provider* supports the online certificate status requests and responses conforming to the “v1” version according to the standards RFC 2560 [16] and RFC 6960 [21].

#### 7.3.2 OCSP Extensions

The *Trust Service Provider* may optionally include the above OCSP extension:

- expiredCertsOnCRL – not critical  
The *Certification Authority* indicates with a standard notation according to the X.509 specification that it does not remove the expired *Certificates* from the CRL. (See Section 4.10.)

The *Trust Service Provider* may include the above OCSP registration extension:

- Reason Code – not critical  
The reason of the revocation is in this field.

## 8 Compliance Audit and Other Assessments

The *Trust Service Provider* shall have its operation periodically examined by independent external auditor. During the audit it shall be examined that the operation of the *Trust Service Provider* complies with the following normative documents:

- REGULATION (EU) No 910/2014 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 23 July 2014 on electronic identification and trust services for electronic transactions in the internal market and repealing Directive 1999/93/EC [1];
- ETSI EN 319 401 V2.1.1 (2016-02); Electronic Signatures and Infrastructures (ESI); General Policy Requirements for Trust Service Providers [7]
- ETSI EN 319 411-1 V1.1.1 (2016-02); Electronic Signatures and Infrastructures (ESI); Policy and security requirements for Trust Service Providers issuing certificates; Part 1: General requirements [8]

The *Trust Service Provider* applies verified and certified elements (electronic signature production IT system elements) in connection with the service.

The *Trust Service Provider* uses the following cryptographic modules for the certification of the *Certificates*, and for the provider private key storage:

- nCipher nShield F3 PCI nC4032P-150, firmware version: 2.22.6-3;
- nCipher nShield F3 SCSI nC4032W-150, firmware version: 2.18.15-3;
- nCipher nShield F3 500e PCIe nC4033E-500, firmware versions: 2.50.16-3 and 2.51.10-3.

The above devices have FIPS 140-2 [24] Level 3 certification.

The *Trust Service Provider* has rated every one of the system elements used for providing the services into security classes on the basis of its risk assessment system. The *Trust Service Provider* keeps records about these system elements and the security ratings associated with them in the scope of its risk management system.

In addition to the external audit, the *Trust Service Provider* also has its proprietary internal auditing system, which regularly examines compliance with previous audits, and takes the necessary steps in case of deviations.

The *Trust Service Provider* has an ISO 9001 standard compliant quality management system since 2002, moreover an ISO 27001 (formerly BS 7799) compliant information security management system since 2003, which are continuously audited and reviewed by an external auditing organisation. (see section: 1.3.1.)

### 8.1 Frequency or Circumstances of Assessment

The *Trust Service Provider* has the conformance assessment carried out annually on its IT system performing the provision of the services .

If the *Trust Service Provider* cooperates with an external *Registration Authority*, then its processes are audited annually.

In case of a provider *Certificate* issued to a certification unit operated by another organization, the operation of the external certification unit is audited annually.

## 8.2 Identity/Qualifications of Assessor

The *Trust Service Provider* performs the internal audits with the help of its employees who hold the independent system auditor role.

The eIDAS and ETSI conformity assessment can be performed by an organization, which has a qualifying mandate issued by the national accreditation organization of an EU Member State.

## 8.3 Assessor's Relationship to Assessed Entity

External audit is performed by a person who:

- is independent from the owners, management and operations of the examined *Trust Service Provider*;
- is independent from the examined organization, namely neither himself or herself nor his or her immediate relatives have any employment or business relationship with the *Trust Service Provider*.
- remuneration is not dependent on the findings of the activities carried out during the audit.

## 8.4 Topics Covered by Assessment

The review covers the following areas:

- compliance with the legislation currently in force;
- compliance with technical standards;
- compliance with the Certification Policy and the *Certification Practice Statement*;
- adequacy of the employed processes;
- documentation;
- physical security;
- adequacy of the personnel;
- IT security;
- compliance with the data protection rules.

If the *Trust Service Provider* cooperates with an external *Registration Authority*, and it issued a provider *Certificate* for the certification unit of another organization then the listed areas are examined at these external organizations as well.



## 8.5 Actions Taken as a Result of Deficiency

The independent auditor summarizes the result of the screening in a detailed screening report that covers the tested system components, processes, and contains the evidence used in the screening and the auditor statements. The discrepancies revealed during the examination and the deadlines set for correcting them are recorded in a separate chapter of the report.

The independent auditor may record based on their severity the differences and discrepancies revealed during the examination:

- modification suggestions to be optionally taken into consideration;
- derogations to be averted mandatorily.

## 8.6 Communication of Results

The *Trust Service Provider* publishes the summary report on the assessment. It does not publish the discrepancies revealed during the independent system assessment, they are treated as confidential information.

# 9 Other Business and Legal Matters

## 9.1 Fees

The *Trust Service Provider* publishes fees and prices on its webpage, and makes them available for reading at its customer service.

The *Trust Service Provider* may unilaterally change the price list. The *Trust Service Provider* publishes any modification to the price list 15 days before it becomes effective. Modifications will not affect the price of services paid in advance.

Provisions associated with the payment and refunding of fees are contained in the service contract and its annexes – the general terms of contract in particular.

### 9.1.1 Certificate Issuance or Renewal Fees

See section: 9.1.

### 9.1.2 Certificate Access Fees

The *Trust Service Provider* grants free of charge on-line access to its *Certificate Repository* for the *Relying Parties*.

### 9.1.3 Revocation or Status Information Access Fees

The *Trust Service Provider* provides free of charge on-line CRL and OCSP service for the *Relying Parties* on the status of all end-user and intermediate *Certificates* it issued.

#### **9.1.4 Fees for Other Services**

See section: 9.1.

#### **9.1.5 Refund Policy**

See section: 9.1.

### **9.2 Financial Responsibility**

In order to facilitate trust the *Trust Service Provider* takes financial responsibility to fulfil all its obligations defined in the present *Certification Practice Statement*, the related *Certificate Policy* and the service agreement concluded with the *Client*.

#### **9.2.1 Insurance Coverage**

The *Trust Service Provider* has sufficient financial resources for its responsibilities related to the provision of services and for providing the costs related to its termination.

#### **9.2.2 Other Assets**

No stipulation.

#### **9.2.3 Insurance or Warranty Coverage for End-entities**

The *Trust Service Provider* does not have liability insurance. The *Trust Service Provider* indemnification is described in section 9.6.1.

### **9.3 Confidentiality of Business Information**

The *Trust Service Provider* manages clients' data according to legal regulations. The *Trust Service Provider* has a data processing regulation (see section 9.4), which addresses the processing of personal data in particular.

By applying for a *Certificate*, and signing the service agreement, *Clients* consent to the *Trust Service Provider* retaining and processing their personal data (in a manner that complies with the data processing regulations). Such consent applies to the forwarding of information specified by law and entered in records to third parties in case the *Trust Service Provider's* services go offline; moreover to forwarding such information to the *Trust Service Provider's* subcontractors – solely for the purpose of performing tasks associated with providing the service.

*Applicants* shall make a declaration as to their consent to the disclosure of a *Certificate* on the certificate application form that is linked to the service agreement.

The *Trust Service Provider* uses clients' data solely in connection with the provision of its services. The *Trust Service Provider* discloses *Subjects'* and *Represented Organizations'* data appearing in a *Certificate* together with the *Certificate* in case a *Applicant* consents to this. The *Trust Service Provider* stores their data that are not entered in a *Certificate* in a secured manner, for the purpose of providing evidence about the *Subjects'* identity, *Represented Organizations'*

organisational identity, and that of its miscellaneous data provision related obligations. The *Trust Service Provider* retains data of which it becomes aware in accordance with statutory requirements, and for the stipulated period of time. In the course of retaining data, the *Trust Service Provider* sees to the intactness, confidentiality, and secure storage of information. It only permits accessing information to individuals whose tasks justify this.

The *Trust Service Provider* provides for the confidentiality and intactness of information that is not public during the forwarding of *Clients'* data.

### 9.3.1 Scope of Confidential Information

The *Trust Service Provider* treats as confidential:

- all *Client* data, with the exception of those that qualify as information not considered confidential in section 9.3.2;
- besides the *Client* data:
  - private keys and activation codes,
  - certificate applications and Service Contracts,
  - transaction related data and log data,
  - non-public regulations,
  - all data whose public disclosure would have an adverse effect on the security of the service.

### 9.3.2 Information Not Within the Scope of Confidential Information

The *Trust Service Provider* considers all data public that can be obtained from a public source, or to the disclosure of which the *Subscriber* gave its consent in writing beforehand.

In case the *Applicant* grants consent, the *Trust Service Provider* treats all of the data it indicates in a *Certificate* as non-confidential information. Such data appear in the *Certificate* application form linked to the service agreement in a clearly marked way.

The *Trust Service Provider* manages the revocation status of the end-user and intermediate provider *Certificates* as public information and makes it available without restriction to the *Relying Parties* by publishing a revocation list (CRL) and by providing on-line Certificate Status Protocol (OCSP) service. The disclosed information contains the serial number of the Certificate, the time of the revocation and the reason for revocation. For more information, see section 7.2. and 7.3.

### 9.3.3 Responsibility to Protect Confidential Information

The *Trust Service Provider* is responsible for the protection of the confidential data it manages.

The *Trust Service Provider* shall oblige its employees, subcontractors, affiliated partners to protect all confidential data by signing declaration of confidentiality or by contract.

The *Trust Service Provider* processes confidential information it comes to possess according to the provisions of Act CXII of 2011. on the Right to Freedom Of Information, and only discloses it to persons/organizations in the following cases:

- **Information provision for authorities**

For the purpose of investigating or preventing acts of crime committed using the trusted services it provides, as well as in the case of national security related interests, the *Trust Service Provider* – if the statutory criteria applicable to data requests are met – discloses the related identity information and the information verified by the *Trust Service Provider* according to the section (1) of the Eüt. [5] 90. § to investigating authorities and national security services free of charge.

The *Trust Service Provider* records the fact of data transfers, but does not inform involved clients about it.

- **Provision of information in the scope of litigation**

In the course of litigation and non-litigious actions under common law, the *Trust Service Provider* may hand over – in case their being affected is certified – *Subject* identity information and the information verified by the *Trust Service Provider*, to an adverse party or its representative, as well as it may disclose them to the inquiring court.

The *Trust Service Provider* records the fact of data transfers and informs impacted clients about it.

- **Disclosure upon owner's request**

Upon a *Client's* personal request to do so or on the basis of its authorisation granted officially, in writing, the *Trust Service Provider* reveals confidential user information pertaining to the *Client* to third parties.

- **Miscellaneous circumstances resulting in the disclosure of information**

Upon termination of its activity the *Trust Service Provider* is bound to hand over its records subject to the access obligations together with confidential user data to the trusted service provider that takes it over according to section (6) of 88. § Eüt. [5].

## 9.4 Privacy of Personal Information

The *Trust Service Provider* takes care of the protection of the personal data it manages, the operation and regulations of the *Trust Service Provider* comply with the requirements of the Act CXII of 2011. on the Right to Freedom Of Information [3].

The *Trust Service Provider*:

- preserves,
- upon expiry of the obligation to retain – unless the *Client* otherwise indicates – deletes from the client database

the registered personal data and information on the *Client* in accordance with the legal requirements.

The *Trust Service Provider* stores identification data, data about the *Subject* appearing in the *Certificate*, data about the *Subscriber* associated with contact details and data connected to the provision of the service in its records.

The *Trust Service Provider* hands over *Client* data to third parties solely in cases where this is stipulated by a legal regulation or if the *Client* has granted its consent to this in writing.

#### **9.4.1 Privacy Plan**

The *Trust Service Provider* has a Privacy Policy for data processing that contains detailed requirements for the personal data management. The Privacy Policy for data processing is published on the webpage of the e-Szignó Certification Authority on the following URL: <https://e-szigno.hu/letoltesek/dokumentumok-es-szabalyzatok/>

#### **9.4.2 Information Treated as Private**

The *Trust Service Provider* protects all personal data related to the data subject or containing conclusions on the data subject that cannot be accessed publicly from the *Certificate* or other public data source.

#### **9.4.3 Information Not Deemed Private**

The *Trust Service Provider* may disclose the data of the *Subjects* indicated in the *Certificate* based on the written consent of the *Applicant*.

The *Trust Service Provider* may indicate the unique provider identifier assigned to the *Subject* in the *Certificate*.

#### **9.4.4 Responsibility to Protect Private Information**

The *Trust Service Provider* stores securely and protects the personal data related to the *Certificate* issuance and not indicated in the *Certificate*. The data is protected by appropriate measures in particular against unauthorized access, alteration, and against disclosure.

#### **9.4.5 Notice and Consent to Use Private Information**

The *Trust Service Provider* only discloses personal data indicated in the *Certificates* with the written consent of the *Client*.

#### **9.4.6 Disclosure Pursuant to Judicial or Administrative Process**

In cases defined in the relevant legislation the *Trust Service Provider* may disclose the stored personal data about the *Client* without notifying the *Client*.

#### 9.4.7 Other Information Disclosure Circumstances

No stipulation.

### 9.5 Intellectual Property Rights

During its business operation, the *Trust Service Provider* shall not harm any intellectual property rights of a third person.

The owner of the private and public key issued by the *Trust Service Provider* to clients is the *Subscriber* and the full user is the *Applicant* regardless of the physical media that contains and protects the keys.

The owner of the *Certificate* issued by the *Trust Service Provider* to its clients is the *Trust Service Provider* and its full user is the *Subscriber*.

The *Trust Service Provider* may publish, reproduce, revoke and manage the issued end-user *Certificates*, with the public key contained in them in the manner described in the terms and conditions.

The certificate revocation status information is the property of the *Trust Service Provider* which is disclosed as defined in sections 7.2. and 7.3.

The unique provider identifier issued to the *Clients* by the *Trust Service Provider* is the property of the *Trust Service Provider* which

is disclosed as a part of the *Certificate* by the *Trust Service Provider* in the *Certificate Repository*.

The *Client* is entitled to the use of the identification in the certificate (which identifies the *Certificate* subject).

The present *Certification Practice Statement* is the exclusive property of the *Trust Service Provider*. The *Clients*, *Applicants* and other *Relying Parties* are only entitled to use the document according to the requirements of the present *Certification Practice Statement* and any other use for commercial or other purposes is strictly prohibited.

The present *Certification Practice Statement* may be freely distributed in unchanged form, in full length and with the indication of origin.

The rules of the application of the software provided for the use of the service by the *Trust Service Provider* is accessible in the description of the software and it is included in the user's guide referenced in the description.

### 9.6 Representations and Warranties

#### 9.6.1 CA Representations and Warranties

##### Certification Authority's Responsibility

The responsibility of the *Trust Service Provider* is in the *Certification Practice Statement*, the related *Certificate Policies*, and the service agreement with the *Client* and its attachments.

- The *Trust Service Provider* assumes responsibility for compliance with the procedures described in *Certificate Policies* it supports;

- The *Trust Service Provider* assumes responsibility as its own for the damages caused during the provision of the service by its subcontractors;
- The *Trust Service Provider* is liable under the rules of liability for breach of contract in the Civil Code of the Republic of Hungary [4] in relation to the *Clients* which are in a contractual relationship with it.
- The *Trust Service Provider* is liable under the rules of causing damage outside of contract in the Civil Code of the Republic of Hungary [4] in relation to third parties (such as the *Relying Party*) that are not in a contractual relationship with it.
- The *Trust Service Provider* will pay compensation for damages with the limitations specified in its regulations, and the service contracts concluded with Clients for proven damages that occur in the scope of its responsibility (see the section Limitation of Liability 9.8.).
- If the valid claim of several entitled parties related to an insurance event exceeds the amount defined for an insurance event in the liability insurance for the damages, then the compensation of the claims takes place in a relative ratio to the amount determined in the liability contract.

The *Trust Service Provider* is not responsible:

- for the *Subject* activities related to the private key;
- for the certificate verification and usage activities of the *Relying Parties*;
- for the regulations issued by the *Relying Parties* or others.

### **Certification Authority Obligations**

The *Trust Service Provider's* basic obligations is that it shall provide the services in line with the *Qualified Signature Certificate Policy*, this *Certification Practice Statement* and other regulations in the public domain, the contractual terms and conditions, furthermore corporate and security related internal regulations. These basic obligations are as follows:

- to establish the legal, regulatory, material, contractual, etc. framework appropriate for the service;
- to provide high standard and secure services in accordance with the applicable regulations;
- to continuously operate and audit organisations associated with the services (certification body, customer service, etc.);
- to abide by the procedures prescribed in the regulations, and to avoid or eliminate any potentially occurring incorrect operation;
- to ensure the Services to every applicant who accepts the terms and conditions specified in the regulations;
- to maintain public and proprietary records, as well as to make them continuously available to anybody over the internet.

### Certification Organization Obligations

The certification organization has the task of setting up and operating the certification units (see section: 1.3.1), as well as units necessary for the online certificate status service, to take care of the certificate repository and revocation status related information moreover to manage regulations. The *Trust Service Provider's* internal, operative regulations specify how a certification organization shall be operated. Certification Authority's certificates issued by certification units are managed (for registration staff members, on-call duty staff, etc.) in accordance with the stipulations of operative regulations. This statement only includes stipulations in connection with the public provider and end-user certificates.

Tasks to be performed in the scope of managing regulations:

- the specification, approval, and maintenance of certificate types that are used;
- preparing the public regulations of the services and internal (not public) stipulations, their reconciliation with legal regulations and internal (not public) regulations, furthermore carrying out any updates;
- the recording of observations associated with regulations applicable to the services, and to evaluate recommendations.

The e-Szignó Certification Authority is responsible:

- for the authenticity and accuracy of the *Certificates* it issued;
- for the regulations it has issued, and for their the conformity and compliance with statutory regulations;
- for the compliance of the key pairs it generated, and for the relationship between the private-public key and the *Certificate*;
- in general for the compliance with its obligations.

### 9.6.2 RA Representations and Warranties

The customer service has the task of representing the *Trust Service Provider* at end-users in connection with the services. It performs the following tasks in the scope thereof:

- participates in selling the services;
- performs the registration of *Subjects*;
- receives requests pertaining to various certificate operations ( revocation, reinstation, certificate replacement);
- receives and handles data modification related filings;
- participates in revocation status publication;
- offers information provision activity to *Clients* and *Relying Parties* in connection with its activities associated with the services provided by the *Trust Service Provider*;



The *Registration Authority* is responsible:

- for establishing the personal identity of *Applicants*;
- for establishing the organisational identity of *Represented Organizations*, and in this latter case for establishing the right of representation of an individual acting in the name of a *Represented Organization*;
- for the genuineness of recorded registration data;
- for providing information to those using the services as to the contents and availability of the *Qualified Signature Certificate Policy* and the *Certification Practice Statement*, as well as the terms and conditions of using the service prior to concluding the service agreement;
- in general to fully comply with its obligations.

### 9.6.3 Subscriber Representations and Warranties

#### **Subscriber Responsibility**

The responsibility of the *Subscriber* is set by the service agreement and its attachments (including the terms and conditions).

#### **Subscriber Obligations**

The responsibility of the *Subscriber* is to act in accordance with the contractual terms and regulations of the *Trust Service Provider* while using the service including requesting and applying the *Certificates* and private keys.

The obligations of the *Subscriber* are determined by this *Certification Practice Statement*, the service agreement and the standard policy conditions and other documents forming an integral part with it, as well as the relevant *Qualified Signature Certificate Policies*.

#### **Subscriber Rights**

- *Subscribers* have the right to use the services in accordance with this *Certification Practice Statement*.
- *Subscribers* are entitled to specify which *Subjects* should be allowed to receive certificates, in writing, and *Subscribers* have the right to request the suspension and revocation of such certificates.
- *Subscribers* have the right to request the revocation of certificates.
- *Subscribers* are entitled to appoint an organisational administrator.

***Applicant Responsibility***

The *Applicant* is responsible for:

- the authentication, accuracy and validity of the data provided during registration;
- the verification of the data indicated in the requested *Certificate*;
- to provide immediate information on the changes of its data and the data indicated in the *Certificate*;
- using its private key and *Certificate* according the regulations;
- the secure management of its private key and activation code;
- for the immediate notification and for full information of the *Trust Service Provider* in cases of dispute;
- to generally comply with its obligations.

***Applicant obligations***

The *Applicant* shall:

- read carefully this *Certification Practice Statement* before using the service;
- completely provide the data required by the *Trust Service Provider* necessary for using the service, and to provide truthful data;
- if the *Applicant* becomes aware of the fact that the necessary data supplied for using the service – especially data indicated in the certificate – have changed, it is obliged to immediately:
  - notify the *Trust Service Provider* in writing,
  - request the suspension or revocation of the *Certificate* and
  - terminate the usage of the *Certificate*;
- use the service solely for the purposes allowed or not proscribed by legal regulations, according to the cited regulations and documents;
- to install the *Website Authentication Certificate* only to that server which is accessible on the domain name or IP address in the *Certificate*;
- ensure that no unauthorized individuals have access to data and tools (passwords, secret codes, signature-creation devices) necessary for using the service;
- notify the *Trust Service Provider* in writing and without delay in case a legal dispute starts in connection with the *Certificates* associated with the service;
- cooperate with the *Trust Service Provider* in order to validate the data necessary for issuing certificates, and to do everything they can to allow the soonest possible completion of such verification;

- the *Applicant* shall answer to the requests of the *Trust Service Provider* within the period of time determined by the *Trust Service Provider* in case of key compromise or the suspicion of illegal use arises;
- acknowledge that the *Subscribers* entitled to request the revocation and/or suspension of the *Certificate*;
- acknowledge that the *Trust Service Provider* issues *Certificates* in the manner specified in the *Certification Practice Statement*, upon the completion of the validation steps described therein;
- acknowledge that the *Trust Service Provider* only displays data that are corresponding to reality in issued *Certificates*. Accordingly, the *Trust Service Provider* validates data to be entered in *Certificates* according to the *Certification Practice Statement*;
- acknowledge that the *Trust Service Provider* revokes the issued *Certificate* in case it becomes aware that the data indicated in the *Certificate* do not correspond to the reality or the private key is not in the sole possession or usage of the *Applicant* and in this case, the *Applicant* is bound to terminate the usage of the *Certificate*;
- acknowledge that the *Trust Service Provider* has the right to suspend, and revoke *Certificates* if the *Subscriber* fails to pay the fees of the services by the deadline;
- in case of requesting an *Organizational Certificate*, acknowledge that the *Trust Service Provider* will issue the *Certificate* solely in the case of the consent of the *Represented Organization*;
- in case of requesting an *Organizational Certificate*, acknowledge that the *Represented Organization* has the right to request the revocation of the *Certificate*;
- for the issuance of a *Website Authentication Certificate* the *Applicant* is bound to hand over the declaration of consent of the given domain owner to the *Trust Service Provider*;
- acknowledge that the *Trust Service Provider* has the right to suspend, and revoke *Certificate* if the *Subscriber* violates the service agreement or the *Trust Service Provider* becomes aware that the *Certificate* was used for an illegal activity.

### **Applicant Rights**

- *Applicants* have the right to apply for *Certificates* in accordance with the *Certification Practice Statement*.
- In case this is allowed by the applicable *Certificate Policy*, *Applicants* are entitled to request the suspension or the revocation of their *Certificates*, according to this *Certification Practice Statement*.

#### 9.6.4 Relying Party Representations and Warranties

The *Relying Parties* decide based on their discretion and/or their policies about the way of accepting and using the *Certificate*. During the verification of the validity for keeping the security level guaranteed by the *Trust Service Provider* it is necessary for the *Relying Party* to act with caution, so it is particularly recommended to:

- comply with the requirements, regulations defined in the present *Qualified Signature Certificate Policy* and the corresponding *Certification Practice Statement*;
- use reliable IT environment and applications;
- verify the the *Certificate* revocation status based on the current CRL or OCSP response;
- take into consideration every restriction in relation to the *Certificate* usage which is included in the *Certificate*, in the *Qualified Signature Certificate Policy* and the *Certification Practice Statement*.

#### 9.6.5 Representations and Warranties of Other Participants

##### Represented Organisation responsibility

The *Represented Organization* is solely responsible for the documents it issues. In particular for document in which it attests that a *Applicant* is a staff member of the *Trust Service Provider*, moreover is entitled to appear in the *Represented Organization's Certificate*. In case the information appearing in any certification made out by the *Represented Organization* is changed, reporting this to the *Trust Service Provider* without delay is the *Represented Organization's* responsibility.

##### Represented Organisation rights

- The *Trust Service Provider* only issues *Certificates* in which the *Represented Organization's* name is indicated in possession of the *Represented Organization's* consent.
- The *Represented Organization* is entitled to suspend and revoke *Certificates* in which the *Represented Organization's* name was also indicated.

#### 9.7 Disclaimers of Warranties

The *Trust Service Provider* excludes its liability if:

- the *Relying Party* does not act with caution during the usage or verification of the *Certificates* namely it does not act according to the present *Certification Practice Statement*, the *Qualified Signature Certificate Policy* or the existing legislation;
- *Applicant* do not follow the requirements related to the management of the private key;
- regulations issued by the *Relying Parties* or by others do not comply with the present *Certification Practice Statement* or the *Qualified Signature Certificate Policy*;

- it is unable to provide information or fulfil communication obligations due to the problems of the Internet, or part of it;
- the damage comes from a vulnerability or error of the cryptographic algorithms accepted by the National Media and Infocommunications Authority algorithmic decree.

## 9.8 Limitations of Liability

Conditions of liability of the *Trust Service Provider*:

- The *Trust Service Provider* is not responsible for damages that arise from the *Relying Party* failing to proceed according to effective legal regulations and the *Trust Service Provider*'s regulations in the course of validating and using certificates, moreover its failing to proceed as may be expected in the given situation.
- The *Trust Service Provider* shall only be liable for contractual and non-contractual damages connected to its services in relation to third parties with respect to provable damages that occur solely on account of the chargeable violation of its obligations.
- The *Trust Service Provider* is not liable for damages that result from its inability to tend to its information provision and other communication related obligations due to the operational malfunction of the Internet or one of its components because of some kind of external incident beyond its control.
- The *Trust Service Provider* engages in data comparison with an authentic database, before issuing a *Subject's Certificate*. The *Trust Service Provider* will not assume any liability for damages arising out of the inaccuracy of information provided by such authentic databases.
- The *Trust Service Provider* assumes liability solely for providing the services in accordance with the provisions of this *Certification Practice Statement*, as well as the documents to which reference is cited herein (Certification Policies, standards, recommendations), moreover with its proprietary internal regulations.

### Administrative Processes

The *Trust Service Provider* logs its activities, protects the intactness and authenticity of log entries, moreover retains (archives) log data over the long term in the interest of allowing for the establishing, documenting, and evidencing of financial accountability, its proprietary liability related to damage it causes, as well as that of damage compensation due to it for damage it suffers.

### Financial Liability

The *Trust Service Provider* has appropriate deposit according to the relevant legal requirements for its financial liability and to guarantee costs related to its termination and for reliability.

In addition, the *Trust Service Provider* also has the legal regulations required liability insurance in order to ensure the reliability.

## **Limitation of Financial Liability**

The *Trust Service Provider* limits the obligation for compensation related to services, the extent of this limitation is 100 000 HUF per damage event.

If the valid claim of several entitled parties related to a damage event exceeds the limitation defined for a damage event, then the compensation of the claims takes place in a relative ratio to the limitation.

## **9.9 Indemnities**

### **9.9.1 Indemnification by the *Trust Service Provider***

The detailed rules of the indemnities of the *Trust Service Provider* are specified in this regulation (see section: 9.8. ), the service agreement and the contracts concluded with the *Clients*.

### **9.9.2 Indemnification by Subscribers**

The *Subscriber* and the Subject are liable for damages to the *Trust Service Provider* for the loss or damage caused by non-compliance with their obligations and the relevant recommendations.

### **9.9.3 Indemnification by Relying Parties**

See section: 9.8.

## **9.10 Term and Termination**

### **9.10.1 Term**

The effective date of the specific *Certification Practice Statement* is specified on the cover of the document.

### **9.10.2 Termination**

The *Certification Practice Statement* is valid without a time limit until withdrawal.

Section 9. of the *Certification Practice Statement* shall remain effective even after the termination of the *Certification Practice Statement*'s effect (regardless of the manner in which effectiveness is terminated) in connection with any and all *Certificates* which the *Trust Service Provider* will have issued while the *Certification Practice Statement* was effective.

### **9.10.3 Effect of Termination and Survival**

In case of the withdrawal of the *Certification Practice Statement* the *Trust Service Provider* publishes the detailed rules of the withdrawal and the rights and obligations persisting after withdrawal on its webpage.

The *Trust Service Provider* guarantees that in case of a the *Certification Practice Statement* withdrawal, requirements for the protection of the confidential data remain in effect.

### 9.11 Individual Notices and Communications with Participants

The *Trust Service Provider* maintains a customer service in order to contact with its *Clients*.

The *Clients* may make their legal declarations to the *Trust Service Provider* solely in writing, and in executed form. Executing in representation of an organisation shall only be valid together with certification of such right of representation.

Issued *Certificates* may also be suspended by telephone. Notifications of other nature may also be given in writing, in the form of electronic mail or fax.

The e-Szignó Certification Authority informs its *Clients* by means of publication on its webpage or in electronic mail.

### 9.12 Amendments

The *Trust Service Provider* reserves the right to change the *Certification Practice Statement* in a controlled way in case of the change of normative rules, safety requirements, market conditions or other circumstances.

In exceptional cases (for example the need for taking critical security measures) the changes can be put into force with immediate effect.

#### 9.12.1 Procedure for Amendment

The *Trust Service Provider* only discloses those of its procedures in its public domain regulations whose knowledge does not jeopardize the security of the services. The *Trust Service Provider* has a number of internal security and other regulations, as well as operative level stipulations which it treats in confidence (this certificate practice statement mentions several such). The procedures described in section 8.4. audit these documents as well.

A team responsible for maintaining regulations and documentation operates within the *Trust Service Provider's* certification organization. This team collects change requests, carries out modifications, and meets any internal and external information provision related obligations. The statement is approved by the director of the e-Szignó Certification Authority.

The team produces internal, non-public working copies of the regulations as it collects changes, and these undergo internal review before being published. The *Trust Service Provider* strives to only issue new regulations at the least frequent intervals possible.

The *Trust Service Provider* reviews the *Certification Practice Statement* annually or in case of exceptional request for change with priority and performs the necessary changes. The document will receive a new version number even after the smallest change and by taking into account the time required by the endorsement process, the planned date of coming into effect will be determined too.

The accepted document will be published on the webpage of the *Trust Service Provider* 30 days prior to the planned entry into force date and it will be sent for review to the National Media and Infocommunications Authority .

The *Trust Service Provider* will accept remarks connected to new regulations published for 14 days prior to their becoming effective, at the following email address:

info@e-szigno.hu

In case of observations that require substantive changes, the document will be amended.

The *Trust Service Provider* will close and publish the version of the regulation as amended with remarks on the 7th day prior to its becoming effective.

### 9.12.2 Notification Mechanism and Period

The *Trust Service Provider* notifies the *Relying Parties* of new document version issuances as described in Section 9.12.1..

### 9.12.3 Circumstances Under Which OID Must Be Changed

The *Trust Service Provider* issues a new version number in case of even the smallest change to the *Certification Practice Statement*, which is part of the document identifier (OID), so any change to the document will result in an OID change, namely two documents – entered into force – with different content cannot have the same OID.

## 9.13 Dispute Resolution Provisions

The *Trust Service Provider* aims for the peaceful and negotiated settlement of the disputes arising from its operation. The settlement follows the principle of gradual approach.

The *Trust Service Provider* and the *Client* mutually agree that in the case of any disputed issue or complaint arising whatsoever, they will attempt amicable consultation through negotiation before taking the dispute to legal channels. The initiating party will be obliged to notify every other affected party promptly and to inform them fully concerning all of the case's implications.

Questions, objections, and complaints related to the activity of the *Trust Service Provider* or the use of issued *Certificates* shall be addressed to the customer care centre office in written form. The *Trust Service Provider* notifies submitting parties at the address they specify about having received a submission and the time required for investigation, within 3 business days calculated as of receiving a submission. The *Trust Service Provider* is obliged to issue a written response to the submitter within the specified time limit. The *Trust Service Provider* may request the provision of information required for giving a response from the submitter. The *Trust Service Provider* investigates complaints within 30 days, and notifies submitters about the results thereof.

Should a submitter find the response inadequate or if the dispute which had arisen can not be settled based on it without getting the *Trust Service Provider* involved, the submitter may initiate consultation with the *Trust Service Provider* and the *Relying Parties*. All participants of such consultation shall be given written notice regarding the date of consultation 10 business days in advance thereof; and the submission, the *Trust Service Provider's* response, as well as any documents containing other required information shall be sent to them in writing.

Should consultation fail to achieve a result within 30 business days calculated as of a complaint being submitted, the submitter may file a lawsuit with respect to the issue. The *Relying Parties* shall subject themselves to the sole jurisdiction of the II. and III. District Court of Budapest and/or that of the Municipal Court of Budapest.



## 9.14 Governing Law

The *Trust Service Provider* at all times operates in accordance with the Hungarian legislation in force. The Hungarian law is the proper law of the *Trust Service Provider* contracts, regulations, and their execution, and they are to be construed by the Hungarian law.

## 9.15 Compliance with Applicable Law

The applicable regulations:

- REGULATION (EU) No 910/2014 of the EUROPEAN PARLIAMENT AND OF THE COUNCIL of 23 July 2014 on electronic identification and trust services for electronic transactions in the internal market and repealing Directive 1999/93/EC [1];
- Act CCXXII of 2015 on electronic administration and the general rules of trust services [5];
- ETSI EN 319 401 V2.1.1 (2016-02); Electronic Signatures and Infrastructures (ESI); General Policy Requirements for Trust Service Providers [7];
- Act CXII of 2011 on the Right to Freedom Of Information [3];
- Act V of 2013. on the Civil Code. [4].

## 9.16 Miscellaneous Provisions

### 9.16.1 Entire Agreement

No stipulation.

### 9.16.2 Assignment

The providers operating according to this *Certification Practice Statement* may only assign their rights and obligations to a third party with the prior written consent of *Trust Service Provider*.

### 9.16.3 Severability

Should some of the provisions of the present *Certification Practice Statement* become invalid for any reason, the remaining provisions will remain in effect unchanged.

### 9.16.4 Enforcement (Attorneys' Fees and Waiver of Rights)

The *Trust Service Provider* is entitled to claim payment for damages and attorney fees for reimbursement of the damages, losses, expenses caused by its partners. If in a particular case the *Trust Service Provider* does not exercise its claim for damages that does not mean that in similar cases in the future or in case of violation of other provisions of the present *Certification Practice Statement*, it would waive the enforcement of claims for damages.

**9.16.5 Force Majeure**

The *Trust Service Provider* is not responsible for the defective or delayed performance of the requirements set out in the *Qualified Signature Certificate Policy* and the *Certification Practice Statement* if the reason for failure or delay was a condition that is outside the control of the *Trust Service Provider*.

**9.17 Other Provisions**

No stipulation.

## A REFERENCES

- [1] Regulation (EU) No 910/2014 of the European Parliament and of the Council of 23 July 2014 on electronic identification and trust services for electronic transactions in the internal market and repealing Directive 1999/93/EC .
- [2] (Hungarian) Act XXXV of 2001 on Electronic Signatures (repealed from 1st July 2016.) .
- [3] (Hungarian) Act CXII of 2011 on the Right to Freedom Of Information .
- [4] (Hungarian) Act V of 2013. on the Civil Code .
- [5] (Hungarian) Act CCXXII of 2015 on the general rules of electronic administration and trust services .
- [6] 24/2016. (VI. 30.) BM rendelet a bizalmi szolgáltatásokra és ezek szolgáltatóira vonatkozó részletes követelményekről.
- [7] ETSI EN 319 401 V2.1.1 (2016-02); Electronic Signatures and Infrastructures (ESI); General Policy Requirements for Trust Service Providers.
- [8] ETSI EN 319 411-1 V1.1.1 (2016-02); Electronic Signatures and Infrastructures (ESI); Policy and security requirements for Trust Service Providers issuing certificates; Part 1: General requirements .
- [9] ETSI EN 319 412-1 V1.1.1 (2016-02); Electronic Signatures and Infrastructures (ESI); Certificate Profiles; Part 1: Overview and common data structures.
- [10] ETSI EN 319 412-2 V2.1.1 (2016-02); Electronic Signatures and Infrastructures (ESI); Certificate Profiles; Part 2: Certificate profile for certificates issued to natural persons; (Replaces ETSI TS 102 280).
- [11] ETSI EN 319 412-3 V1.1.1 (2016-02); Electronic Signatures and Infrastructures (ESI); Certificate Profiles; Part 3: Certificate profile for certificates issued to legal persons (Replaces ETSI TS 101 861).
- [12] ETSI EN 319 412-4 V1.1.1 (2016-02); Electronic Signatures and Infrastructures (ESI); Certificate Profiles; Part 4: Certificate profile for web site certificates.
- [13] ETSI TS 119 312 V1.1.1 (2014-11); Electronic Signatures and Infrastructures (ESI); Cryptographic Suites.
- [14] MSZ/ISO/IEC 15408-2002 "Information Technology - Methods and Means of a Security - Evaluation Criteria for IT Security" .
- [15] ISO/IEC 19790:2012: "Information technology – Security techniques – Security requirements for cryptographic modules".
- [16] IETF RFC 2560: X.509 Internet Public Key Infrastructure - Online Certificate Status Protocol (OCSP), June 1999.

- [17] IETF RFC 3647: Internet X.509 Public Key Infrastructure - Certificate Policy and Certification Practices Framework, November 2003.
- [18] IETF RFC 4043: Internet X.509 Public Key Infrastructure - Permanent Identifier, May 2005.
- [19] IETF RFC 5280: Internet X.509 Public Key Infrastructure - Certificate and Certificate Revocation List (CRL) Profile, May 2008.
- [20] IETF RFC 6818: Updates to the Internet X.509 Public Key Infrastructure - Certificate and Certificate Revocation List (CRL) Profile, January 2013.
- [21] IETF RFC 6960: X.509 Internet Public Key Infrastructure - Online Certificate Status Protocol (OCSP), June 2013.
- [22] ITU X.509 Information technology - Open Systems Interconnection - The Directory: Public-key and attribute certificate frameworks.
- [23] CA/Browser Forum Baseline Requirements for the Issuance and Management of Publicly-Trusted Certificates, v.1.3.0. CA/Browser Forum, <https://cabforum.org/wp-content/uploads/CAB-Forum-BR-1.3.0.pdf>, 2015.
- [24] FIPS PUB 140-2 (2001 May 25): Security Requirements for Cryptographic Modules.
- [25] CEN Workgroup Agreement CWA 14167-2: Cryptographic module for CSP signing operations with backup - Protection profile - CMCSOB PP.
- [26] EU Trusted Lists of Certification Service Providers, (<https://ec.europa.eu/digital-agenda/en/eu-trusted-lists-certification-service-providers>).
- [27] Magyarország (Hungary): Trusted List ([http://www.nmhh.hu/t1/pub/HU\\_TL.pdf](http://www.nmhh.hu/t1/pub/HU_TL.pdf)).
- [28] e-Szignó Hitelesítés Szolgáltató - eIDAS rendelet szerinti weboldal-hitelesítő tanúsítvány hitelesítési rendek.
- [29] e-Szignó Certification Authority - Qualified Signing Certificate Policies .